## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333 NO.F6/DFS/MS/GH/2014/ \$2 / 6 9 6 Dated: <u>b</u> 6 / 6 6 / 6 4

## FIRE SAFETY CERTIFICATE

Certified that Makkah Palace Guest House located at 161/22, Joga Bai Main Road, Okhla, New Delhi comprised of basement floor (storage & lying vacant partly), ground floor (residence of owner + reception), first floor (lying vacant), second floor (10 guest rooms), third floor (10 guest rooms) and fourth floor (10 guest rooms) was granted NOC by this department vide letter No. F.6/DFS/MS/GH/2010/1763 dated 15-06-2010. The premises was re-inspected by the officer concerned of this department on 28-05-2014 in the presence of the manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class residential (Guest house) with effect from v6/06/14 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on <u>o 6/o 6/14</u> at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Addl. C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi

2. The Manager, M/s Makkah Palace Guest House, 161/22, Joga Bai, Main Road, Okhla, New Delhi.

## Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

## **INSPECTION REPORT**

1. Name & address of the building: Makkah Palace guest house,161/22, Joga Bai, Main Road,

Okhla, New Delhi-25.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/GH/2010/1763 Dated: 15.06.2010

5. Fire Safety directives letter No: Nil

6. Date of inspection

: 28-05-2014

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side

: Mr. Hussain Ahmed, Proprietor

9. Year of Construction

: 1995

10. Applicant's letter No.

:Nil dated 20-05-2014.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building		a a	¥1	
	Road width	06 mts	Provided	MR	
	Gate width	06 mts	Provided	N/A	
	Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	-	<del>-</del>	_	
	• Upper Floors	01	Provided	MR	
	<ul> <li>Basements</li> </ul>	02	Provided	MR	
	b. Width of staircases	-	-	-	
	<ul> <li>Upper Floors</li> </ul>	1.24 mts	Provided	MR	
	• Basements	1.24 mts, 1.10 mts	Provided	MR	
	c. Protection of exits				
	• Fire check door	N/A	N/A	N/A	
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace g. Width of Corridor h. Door Size	01	01	MR	
		N/A	N/A	N/A	
		N/A	N/A	N/A	
	Compartmentation.				
	• Fire check door	N/A	N/A	N/A	



	m3				
	Sealing of electrical shafts	N/A	N/A	N/A	
	<ul> <li>Fire Rating of shaft door</li> </ul>	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
	Smoke Management System.		5		
	Basements	30 a/c per hour	Exhaust Fan Provided	MR	
	Upper floors	12 a/c per hour	N/A	N/A	
5	Fire Extinguishers				
	Total numbers	10	Provided	MR	
	Types	ABC, CO <sub>2</sub>	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	01	Provided	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	N/A	N/A	N/A	
	Location of Main Panel	N/A	N/A	N/A	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooters' Location	N/A	N/A	N/A	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	Size of riser/down-comer	N/A	N/A	N/A	
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	



Yard Hydrants.

		10		
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
3 Pum	nping Arrangements.			
	• Ground Level	- "	-	-
	<ul><li>Discharge of main Pump</li></ul>	N/A	N/A	N/A
	➤ Head of Main pump	N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
e.	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual	N/A	N/A	N/A
	stopping	N/A	N/A	N/A
	> Pump House Access	N/A	N/A	N/A
	<ul><li>Terrace level</li><li>Discharge of pump</li></ul>	900, 180 LPM	Provided	MR
	<ul><li>Head of the pump</li></ul>	40 mt	Provided	MR
	> Power Supply	Required	Provided	MR
25	> Auto Starting of pump	Required	provided	MR
14 <b>Ca</b>	aptive Water Storage for fire fighting	5•		
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N/A	N/A	N/A
	<ul><li>Fire service inlet</li></ul>	N/A	N/A	N/A
	> Access to tank	N/A	N/A	N/A
	<ul> <li>Overhead Tank capacity</li> </ul>	5, 000 liters	Provided	MR
15 Ex	xit Signage.	Required	Provided	MR
	rovision of Lifts.			
10 11	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	N/A	N/A	N/A
	• Fireman's Grounding Switch	N/A	N/A	N/A
	• Fireman's Grounding Switch	IN/A		



	M3	e e				
	Sealing of electrical shafts	N/A	N/A	N/A		
	<ul> <li>Fire Rating of shaft door</li> </ul>	N/A	N/A	N/A		
9	Water Curtain	N/A	N/A	N/A		
3.6	• Fire Dampers	N/A	N/A	N/A		
1	Smoke Management System.					
	Basements	30 a/c per hour	Exhaust Fan Provided	MR		
	<ul> <li>Upper floors</li> </ul>	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers	5				
	Total numbers	10	Provided	MR		
	• Types	$ABC, CO_2$	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming	system.				
	Type of detectors	N/A	N/A	N/A		
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	Required	Provided	MR		
9	Public Address System.	Required	Provided	MR		
10	Automatic Sprinkler System.					
	Basement	Required	Provided	MR		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants			0		
	Size of riser/down-comer	N/A	N/A	N/A		
	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					



079

17	Standby power supply	Required	Provided (D.G Set 15 KVA)	MR
18	Refuge Area.			
4	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room	۰		-
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 CO <sub>2</sub> type fire extinguishers found provided	MR
			near elect. panel	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/GH/2010/1763 dated 15.06.2010, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

1 provincing