GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:- 011-23412593

E-mail ID: cfohq.dlfire@nic.in

No F 6/DFS/MS/GH/2014/ ND2/697

Dated

06/06/14

FIRE SAFETY CERTIFICATE

Issued on ... o 6 o 6/19 at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 64131/Joint. C.P./Lic. (H) dated New Delhi 22-10-2013.

2. MEM-International located at 2154 (8/3) Desh Bandhu Gupta Road, Pahar Ganj, New Delhi.

3. The Commissioner, North Delhi Municipal Corporation with the request to get the height of the building verified under intimation to this department.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

1. Name & address of the building : MEM-International located at 2154 (8/3) Desh Bandhu Gupta

Road, Pahar Ganj, New Delhi.

2. Type of Occupancy : Residential (Guest house) G + 4 floors total guest rooms-27

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2010/3346 dated 14/12/2010

5. Fire Safety directives Letter No. : NA

6 Date of inspection : 25/05/2014

7 Name of the Inspecting Officer : Sh. M. K. Sharma (ADO/CC)

8 Name and designation of Officer

from the building side : Sh. Manoj Gupta (Manager)

9 Year of Construction : 2010

10. Applicant's letter No. : 64131/Joint.C.P./Lic. (H) dated New Delhi the 22/10/2013.

ONI	2 (1 1				
S No		num standards on fire prevention	Existing	Provided at site	Remarks
	and fin	e safety U/R 33	Requirements	(PSS)	MR/NMR
1.	Acces	s of building	<u> </u>		
	•	Road width	NA	9 Mtr.	MR
ı	•	Gate width	NA	NA	NA
	•	Width of internal road	NA	NA	NA
2.	Numb	er, width, Type & Arrangements of	fexits		
•	a. Nun	ber of staircases			
	• Upp	er floors	1 No.	1 No.	MR
	• Base	ements	NA	NA	NA
	b. Width of staircases				
•	• Upp	er floors	0.80 Mtr.	1.25Mtr.	MR
	• Base	ements	NA	NA	NA
	c. Prote	ection of exits			
	Fire	check door	NA	NA	NA

h

Mer

,	Pressurization	NA	NA	NA		
	d. No of continuous staircase to terrace	1 No.	1 No.	MR		
	e. Width Of Corridor	1.0 Mtr.	1.0 Mtr.	MR		
	f. Door Size	1.0 Mtr.	1.0 Mtr.	MR		
3.	Compartmentation					
	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	• Fire Dampers	NA	NA	NA		
4	Smoke managements System	, , , , , , , , , , , , , , , , , , , ,		1 6		
	Basements	NA	NA	NA		
	• Upper floors	12 ACPH	NATURAL	MR		
5	Fire Extinguishers					
	Total numbers	12 Nos.	14 Nos.	MR		
	• Types	ABC, CO ₂ , Wco ₂	ABC, CO ₂ , Wco ₂	MR		
	IS marking	Required	Provided	MR		
6	First – Aid Hose Reels					
*	Total numbers on each floor	01	01	MR		
	 Length of hose reel hose 	30 Mtr.	30 Mtr.	MR		
	Nozzle diameter	05 MM	05 MM	MR		
7 Automatic fire detection and alarming system			1			
	Type of detectors	NA	NA	NA		
	Location of Main Panel	NA	NA	NA		
	 Location of Repeater Panel 	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
8	MOEFA	Required	Provided	MR		
9	Public Address System	Required	Provided	MR		
10	Automatic Sprinkler					
	Basements	NA	NA	NA		
				1		

4

5	* * * * * * * * * * * * * * * * * * * *			
	Sprinkler above false ceiling	NA	NA	NA
11	Internal Hydrants			
	Size of riser/down- comer	NA	NA	NA
	Number of hydrants per floor	NA	NA -	NA
	• Hose Box	NA	NA	NA
2	Yard Hydrants			
I 4	Total number of hydrants	NA	NA	NA
	• Hose Box	NA	NA	NA
3	Pumping Arrangements			
	Ground Level			
	 Discharge of main pump 	NA	NA	NA
	Head of main pump	NA	NA	NA
	Number of main pumps	NA	NA	NA
	 Jockey pump out put 	NA	NA	NA
	Jockey pump head	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Standby Pump Head	NA	NA	NA
*)	auto Staring/Manual stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	o Terrace level	NA	NA	NA
	Discharge of pump	450 LPM	450 LPM	MR
	Head of the pump	30 Mtr.	30 Mtr.	MR
	Power supply	Required	Provided	MR
	Auto starting of pump	Required	Provided	MR
			L T	
4	Captive water Storage for fire fighting	g NA	NA	NA
	Under ground tank capacity	NA	NA	NA
	Draw of connection	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	5,000 ltr.	5,000 ltr.	MR
5	Exit Signage	Required	Provided	MR

4

Men

16	Provision of Lifts	NA	NA	NA
	Pressurization of Lift Shaft	NA	NA	NA
	 Pressurization of lift lobby 	NA	NA	NA
	Communication in lift Car	NA	NA	NA
	Fireman's Grounding Switch	NA	NA	NA
	• Lift Signage	NA	NA	NA
17	Standby power supply	Required	Provided	MR
18	Refuge Area			
	Total area	NA	NA	NA
	Location	NA	NA	NA
19	Fire control room			
	Detector system panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
,	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA NA	NA
20	Special Fire Protection Systems for Protection of special Risks, if any;	Required	ABC,Co ₂	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2010/3346 dated 14/12/2010 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended please.

Name:- Sh. M. K. Sharma

Designation: - A. D.O. (CC)

Doced) buland