GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ 52/668

Dated: 02/06/14

FIRE SAFETY CERTIFICATE

Certified that the Guest House **Park View** located at 15A/60, WEA, Karol Bagh, New Delhi-110005 is comprised of Basement, ground floor plus three upper floors, using basement as Hall/storage, ground floor as reception and 01 guest rooms, first floor having 07 guest rooms, second floor having 08 guest rooms, third floor used as owner's residence (Total 16 guest rooms) was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011/1142 dated 10.06.2011 owned/occupied by Sh. Vikram Chadha. The guest house building was re- inspected by the officers concerned of this department on 26.05.2014 in the presence of Sh. Sunil Chahal (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.18456/Joint C.P./Lic.(H), Dated 30.04.2014)
- 2. Sh. Vikram Chadha (Owner), Guest House Park View, 15A/60, WEA, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

ADOSRO

M115

	The last transfer of the last								
	11	NSPECT	ION REPORT						
	1. Name & address of the buil	ding: G	2. H Park Min	0 10010. 11	- 1-	1			
	2. Type of Occupancy	INSPECTION REPORT Tress of the building: G. H. Park View, ISA Go, WEA, Karol Bagh, Japancy Residential (Guest House) N. D. O : New Case/Repewal							
	3. Type of Case	IOC Letter No. Collegel. Le							
	4. Details of Previous NOC								
	5. Fire Safety directives letter	s letter No : 26 · 05 · 2014							
	 Date of inspection 								
	7. Name of Inspecting Officer								
	8. Name and designation of of	fficers	0 0 0 70	max p. H. B.	0 P.S. Aa	hiya			
	From the building side	:				0			
	9. Year of Construction	:	2001	! Chahal (Mo	inager)				
<u> </u>	10. Applicant's letter No.	: 1	8456/ Joint C	PLIC. (H) do	1 1 5				
S.	Minimum Standards on fire		NBC/BBL	Provided at	Ited 30.00	1.2011			
No.	prevention and fire safety U/R 3	3	Requirement	site	Remarks				
1.	Access to building		requirement	site	MR/NMR				
	 Road width 		Accessible	09mtr					
	Gate width		-	1	MR				
	Width of internal road			180 cms	MR	1			
2.	Number, Width, Type & Arrange					2° 1."			
	a. Number of staircases	ment o	TEXITS		120				
	• Upper Floors								
	• Basements		_	One	MR, Being	Ald			
	b. Width of staircases			-do-	- Nang	UIU			
	• Upper Floor	w			- 00				
	Basements		-	142 cms	MR, Being	Alil			
	c. Protection of exits		-	130 cms	- do -	<u>Via (</u>			
				To Chis	- 00	- !			
	Fire check door								
	• pressurization	×	-	-					
	d. Not of continuous staircases to)	2		`				
	e. Width of Corridor			One					
	e. Width of Corridor f. Door Size	Ī	_	The state of the s					
	1. Door Size	}		425cms, 117cms					
	Competer			83 cms x 205 cms	_	;			
	Compartmentation		9						
	Fire check door			·	And the second s				
	Sealing of electrical shafts								
	 Fire Rating of shaft door 	-		Sealed					
	Water Curtain								
	Fire Dampers				man 116.2 homeograph areas to the standard of				
ļ.			· • • • • • • • • • • • • • • • • • • •	-	-				
	Smoke Management System				Personal section of the second section of the Published second section of				
	• Basements			Thaust Fons	The second secon				
	 Upper floors 		hour	are Provided	MR				
			N	atural Ventilation	MR				

1	NIA						
	PX	12 a/c per					
	·	hour					
-				1			
5.	Fire Extinguishers						
	Total numbers	Two at each Floor	Provided	MR			
	Types	Co, WCo,	- do, -				
	 IS marking 	ISI marked	1SI Marked	MR			
6.	First-Aid Hose Reels		1311 10 10 rked	MR			
	 Total numbers on each floor 	One	Provided	0.0			
	 Length of hose reel hose 	30 m		MR			
i	Nozzle diameter	5 mm	- do -	MR			
7.	Automatic fire detection and alarming		- alox -	MAR			
	Type of detectors	Jystein					
1	Location of Main Panel			#			
A.	 Location of Repeater Panel 			<u> </u>			
- Automotive of the Control of the C	Alternate source of power	-	· · · · · · · · · · · · · · · · · · ·	+			
	Hooters' Location	_	D.G. Set of 20 KVA				
8.	MOEFA		17				
9.	Public Address System	Required	Provided	MR			
10.		- do -	-do-	MR			
10.	Automatic Sprinkler System						
	Basement	Required	Provided	MR			
	Upper Floor	45	1				
	 Sprinkler above false ceiling 		1				
11.	Internal Hydrants						
	 Size of riser/down-comer 		- '				
	 Number of hydrants per floor 			* 4			
	 Hose Box 		-+:	7			
12.	Yard Hydrants		J.				
	 Total number of hydrants 	-					
	Hose Box						
13.	Pumping Arrangements						
	 Ground Level 						
	Discharge of main Pump		_				
	Head of Main pump	_					
	Number of main pumps			facilities and the second seco			
	Jockey Pump out put			1			
	Jockey pump head	•					
	Standby Pump out put	-		-			
	Standby Pump Head		7				
	Auto Starting/Manual						
	stopping						

The state of the s

N/17

15 A/60, WEA, Karol Bagh, New Delli-110005.

Pump House Access					
			y de		
Discharge of pump	_	Licaion	MO BILL		
	×		MR BldCa		
	Required	Provided	-do-		
Auto Starting of pump	-				
Captive Water Storage for fire fighting			1		
	~		_		
Draw-off connection	The state of the s	· ·			
Fire service inlet	-	Provided	MR		
1 (TOUTAEA	7-7/		
 Overhead Tank capacity 		Casalda	ha0 0140		
F-ia C	Realized		MR, Old O MR		
Exit Signage.	The part ca	, , , , , , , , , , , , , , , , , , , ,	, ,,,		
Provision of Lifts.		*	à		
			No Citt		
			-do -		
			-do -		
Lift Signage			-do-		
	-	_	-do -		
Standby power supply	Required	Provided	MR		
Refuge Area.					
> Total Area					
> Location		1			
		,	_		
Fire Control Room			=		
Detector System Panel			1		
Flow Switch Panel					
PA System Panel			:		
Batter backup	0				
 Building Floor Plans 	Kegleired	Provided	MR		
	/		-		
Special Fire Protection System for Protection of special Risks, if any:					
	 Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection System for 	• Terrace level > Discharge of pump > Head of the pump > Power Supply > Auto Starting of pump Captive Water Storage for fire fighting • Underground tank capacity > Draw-off connection > Fire service inlet > Access to tank • Overhead Tank capacity Exit Signage. Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift Car • Fireman's Grounding Switch • Lift Signage Standby power supply Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup • Building Floor Plans Special Fire Protection System for	Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Provided Provided Provided Required Provided Required Provided Fire Signage. Required Required Required Provided Required Provided Provided Required Provided Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Pa System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection System for		



The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6 DFS MS 6H 2011 1142 dated 10.06.2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomax

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Apst. Divisional Officer