GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DFS/MS/School/WZ/ 2014 / 693

Dated: 6 /6 /2014

FIRE SAFETY CERTIFICATE

Certified that S. S International School, Kh. No 489 & 500 to 503, Village Hiranki,

Delhi-110036 comprised of Ground + One upper floor owned/occupied by S. S International

School, have complied with the fire prevention and fire safety requirements in accordance with
the Circular No F.16/Estate/CC/Fire Safety/2011/3298-3398 dated 01/03/2011 issued by
Director of Education and verified by the officer concerned of Fire Service on 15/05/2014 in the
presence of Mrs. Sushma Verma (Principal) and that the building / premises is fit for
occupancy of Group Class B (Educational) building with effect from 6 / 2014 for
a period of three years subject to conditions mentioned below.

Conditions for the validity of Fire Safety Certificate:

- 1 All the fire safety arrangement provided their in shall be maintained in good working at all times.
- 2 Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3 The trained fire fighting staff should be available round the clock.
- 4 Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5 This certificate cannot be treated in any case for regularizations of unauthorized construction
- The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

Issued on $\frac{6/6/19}{}$ at New Delhi

(SANTOKH SINGH) Chief Fire Officer Delhi Fire Service Ph: 011-23414250 cfowz.dlfire@nic.in

Copy to:

- 1. The Principal, S. S International School, Kh. No 489 & 500 to 503, Village Hiranki, Delhi-110036
- 2. The Director of Education, Old Secretariat, Delhi-110054.

		ON REPORT				
•	Name & address of the building: SS In	ternational.	School vill-frie	renke.		
1.	Name & address of the building.	ecational	<u></u>	elhi-36		
2.	1. Name & address of the building:					
3.	5. Type of case					
4.	Details of previous NOC Fire Safety directives letter No Date of inspection	r. of Educa	tion			
5.	Date of inspection :	. 5-14				
7	Name of the Inspecting Officers:	00 (EW)				
٠ ,						
	Su Su	shing vern	44. Principa	zl		
9	Year of Construction :	909				
10	Applicant's letter No.	5914/29/4/19	Dt 2	3.4.14		
04	Year of Construction Applicant's letter No. 1500 Sq. 994ds CA. 560 W2	NOCK- 9	NOS-95			
	Minimum Standards on fire	NBC	Provided at site	Remarks		
	prevention and fire safety U/R 33	Requirement	Trovided at Sive	MR/NMR		
1	Access to building	20h-04 Edy.	1			
N	Road width	Accessable	Accessable	MR		
	Gate width	_do-	-do-	MR		
·	Width of internal road					
2	Number, Width, Type & Arrangement o	f Exits				
	a. Number of staircases					
	Upper Floors		2	MR		
	Basements					
	b. Width of staircases					
	Upper Floors	1.50Mz	1.25+ . do mts	m R		
	• Basements	•				
1/2	c. Protection of exits					
	Fire check door					
10 10 10 10	Pressurization					
100	e. No. of continuous staircases to terrace					
	g. Width of Corridor					
	h. Door Size	1 M to	1 onto	MR		
3	Compartmentation.					
	Fire check door					

#12

	0-11 01 11 1		*	3
	Sealing of electrical shafts		0	27 20 20 20
	Fire Rating of shaft door			-/
	Water Curtain			
	Fire Dampers		/	
4	Smoke Management System.	<u> </u>	18	
	Basements	30 a/c per hour	1 11	
	Upper floors	12 a/c per hour		
*			The same of	*
5	Fire Extinguishers			
	Total numbers	5 ABGCO2	3 +2	MR
	• Types	ISI marked	CO2 + ABC	MR
	IS marking		4.80	MR -
6	First-Aid Hose Reels.	1		
	Total numbers on each floor			
	Length of hose reel hose	30 m	MIN-	
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming			
	Type of detectors			
٠	 Location of Main Panel 		1	
	Location of Repeater Panel	, male (A)		
	Alternate source of power	THE RESERVE OF THE CORNER		
	Hooters' Location		oll	
8	MOEFA			
9	Public Address System.			
10	Automatic Sprinkler System.			
10	Basement			
	Upper Floor		Control of the second of the s	
	Sprinkler above false ceiling			
1.1	Internal Hydrants		1	
	Size of riser/down-comer		MIM	
	Number of hydrants per floor			
12	Hose Box Vard Hydronts			
12	Yard Hydrants.		T	
	Total number of hydrants		And the state of the said	
	Hose Box			

2 1	Din	mping Arrangements.	
3	ı uı	Ground Level	
. 1		> Discharge of main Pump	
		xx 1 CMain numn	
		> Number of main pumps	
		> Jockey Pump out put	
		> Jockey pump head	
		> Standby Pump out put	11/1
	1	> Standby Pump Head	M
		> Auto Starting/ Manual	
		stopping Pump House Access	
		Terrace level	
¥		> Discharge of pump	
		> Head of the pump	
		> Power Supply	
		> Auto Starting of pum	
14		Captive Water Storage for fire fighting.	
-	+	Underground tank capacity	
		> Draw-off connection	
		> Fire service inlet	
		> Access to tank	11/1
		Overhead Tank capacity	
		Exit Signage.	
	6	Provision of Lifts. • Pressurization of Lift Shaft	
		Pressurization of Lift lobby	
		Communication In lift Car	
		Fireman's Grounding Switch	
		Lift Signage	18
	17	Standby power supply	JAL THE STATE OF T
	18.	Refuge Area.	
		> Total Area	
		> Location	
	19	Fire Control Room	
		Detector System Panel	

17-9

		12		
	Flow Switch Panel	:		
	PA System Panel			
	Batter backup	:		
	Building Floor Plans	14	A	
20	Special Fire Protection Systems for Protection of special Risks, if any:			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers.

Signature of the Inspecting Officer

Name

Designation

Buyb 215/14 Name

Designation AAE BN

Signature of the Inspecting Off

Rogie red on 805

21 DIFO (WY)