GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:- 011-23412593

E-mail ID: cfohq.dlfire@nic.in

No F 6 / DFS / MS / GH / 2014 / MO2/ 676

Dated 03/06/14

FIRE SAFETY CERTIFICATE

Certified that the Baba Inn Guest House located at 7768-69, (1-B), Ram Nagar, Pahar Ganj, New Delhi comprises of Ground floor (03 guest rooms + reception + lobby), 1st floor to 3rd floor (06 guest rooms at each floor), 4th floor (05 guest rooms) and Terrace floor (DG + lift room) with total 26 guest rooms was granted NOC by this department vide letter No. F6/MS/DFS/GH/2011/283 dated 14-02-2011. The premises was re-inspected by the officer concerned of this department on 23-05-2014 in the presence of Mr. Mahesh Sharma (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 lodging or rooming houses for 26 guest rooms with effect from -03/06/14- for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph - 011-23414333

Copy to:-

- 9cmc 1. Baba Inn Guest House located at 7768-69, (1-B), Ram Nagar, Pahar Ganj, New Delhi.
- 2. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi 110049 w.r.t. letter No 17843/Joint. C.P./Lic. (H) dated New Delhi 25-04-2014.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

INSPECTION REPORT

1. Name & address of the building : Baba Inn Guest House located at, 7768-69, (1-B), Ram Nagar,

Pahar Ganj, New Delhi.

2. Type of Occupancy

: Residential (Guest house) G + 4 floor (26 Guest Rooms)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/MS/DFS/GH/2011/283 dated 14/02/2011

5. Fire Safety directives Letter No.

: NA

6 Date of inspection

: 23/05/2014

7 Name of the Inspecting Officer

: M. K. Sharma (Assistant Divisional Officer)

8 Name and designation of Officer

from the building side

: Mr. Mahesh Sharma (Manager)

9 Year of Construction

: 2010

10. Applicant's letter No.

: 17843/Joint. C.P./Lic.(H) dated New Delhi the 25/04/2014

S No	Minim	um standards on fire prevention	Existing	Provided at site	Remarks	
	and fin	e safety U/R 33	Requirements	(PSS)	MR/NMR	
1.	Acces	s of building		1.2 m)	
	•	Road width	NA	6 Mtr.	MR	
	•	Gate width	NA	NA	NA	
	•	Width of internal road	NA	NA	NA	
2.	Number, width, Type & Arrangements of exits					
	a. Nur	nber of staircases				
	• Upp	er floors	1 No.	1 No.	MR	
	• Bas	ements	NA	NA	NA	
	b.Width of staircases		* 1			
	• Upp	er floors	0 .80 Mtr.	1.25 Mtr.	MR	
	• Bas	ements	NA	NA	NA	
	c. Protection of exits			<u> </u>		
	Fire	check door	NA	NA	NA	

Marsh

N/4

	• Pressurization			
	1	NA	GNA	NA
	d. No of continuous staircase to terrace	1 No.	1 No.	MR
	e. Width Of Corridor f. Door Size	1.0 Mtr.	1.0 Mtr.	MR
3.		1.0 Mtr.	1.0 Mtr.	MR
J.	compartmentation			
	• Fire check door	NA	NA	NA
	 Sealing of electrical shafts 	NA	NA	NA
	 Fire Rating of shaft door 	NA	NA	NA
	Water Curtain	NA	NA	NA
	Fire Dampers	NA	NA	
4	Smoke managements System		- 17.2	NA
	• Basements	NA	DIA	
	• Upper floors	12 ACPH	NA NA TIUD AX	NA
5	Fire Extinguishers	12/10/11	NATURAL	MR
	Total numbers			
	• Types	12 Nos.	14 Nos.	MR
		ABC, CO ₂ , Wco ₂	ABC, CO ₂ , Wco ₂	MR
	• IS marking	Required	Provided	MR
	First – Aid Hose Reels			
	 Total numbers on each floor 	01	01	MR
	 Length of hose reel hose 	30 Mtr.	30 Mtr.	MR
	Nozzle diameter	05 MM	05 MM	
	Automatic fire detection and alarming system			MR
	Type of detectors	NA	NA	
	Location of Main Panel	NA		NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA -
	Hooters' Location	NA	NA	NA
	MOEFA		NA	NA
	Public Address System	Required	Provided	MR
	AMULUSS SVSIEM	NA	NA	NA
			2 1	
	Automatic Sprinkler			
		NA	NA	NA

new

16	December 11 CI 10			Me
10	Provision of Lifts	NA	Promidual	NA
	Pressurization of Lift Shaft	NA	NA	NA
	 Pressurization of lift lobby 	NA	NA	NA
	Communication in lift Car	Required	Provided	MR
	 Fireman's Grounding Switch 	Required	Provided	MR
	Lift Signage	Required		
17	C. II	1	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area			
	Total area	NA	NA	NA
	 Location 	NA	NA	NA
19	Fire control room			
	Detector system panel	NA	NA	NA
	Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	NA	NA
	Batter backup	NA	NA	NA
	Building Floor Plans	NA	NA	NA
20	Special Fire Protection Systems for	Required	ABC,Co ₂	MR
	Protection of special Risks, if any;		2,002	1111

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/MS/DFS/GH/2011/283 dated 14/02/2011 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended please.

Signature of the Inspecting Officer

Designation :- A. D.O. (CC)

		Sprinkler, above false ceiling	NA	NA	NA
	-			· · · · · · · · · · · · · · · · · · ·	
	Interna	Hydrants	NA	NA	NA
	•	Size of riser/down-comer	NA	NA	NA
	•	Number of hydrants per floor	NA	NA	NA
	•	Hose Box	INA		1 2
	Yard l	Hydrants		NA	NA
	•	Total number of hydrants	NA	NA	NA
		Hose Box	NA	INA	
	Pumr	oing Arrangements			
	1 uniq	1 I			NA
		Discharge of main pump	NA	NA	
	•		NA	NA	NA
	•		NA	NA	NA
	•		NA	NA	NA
		Jockey pump out put	NA	NA	NA
		Jockey pump head	NA	NA	NA
		 Standby Pump out put 	NA	NA	NA
		 Standby Pump Head 	NA	NA	NA
		• auto Staring/Manual stopping	NA	- NA	NA
		Pump House Access		NA	NA
		o Terrace level	NA	450 LPM	MR
		Discharge of pump	450 LPM	30 Mtr.	MR
		• Head of the pump	30 Mtr.	Provided	MR
		 Power supply 	Required	Provided	MR
		 Auto starting of pump 	Required	Provided	
		Auto starting of Part 1			- NA
1	14	aptive water Storage for fire fighting	ng NA	NA	NA NA
1	14 C	tank canacity		NA	
			NA	NA ,	NA NA
		Draw of connection	NA	NA	NA
		• Fire service inlet	Required	Provided	MR
		Access to tank	5,000 ltr.	10,000 ltr.	MR
		 Overhead Tank capacity 	Required	Provided	MR
-	15	Exit Signage	Required		