GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F6/065/an3/school/2014/1402/735 Dated: 16/06/14

FIRE SAFETY CERTIFICATE

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

O1c

To,

The Manager
Lovely Public English School
A-Block,, Yojna Vihar Delhi-92,
Copy:-

The Dy.Director of Education D-Block, Anand Vihar, Delhi.

CONDITIONS:

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building :Lovely Public English School at A-Block,

Yojna Vihar, Delhi-92

2. Building is comprised of :

: Ground +2, upper floors

3. Type of Occupancy

: Educational

4. Type of Case

: Renewal

5. Details of Previous FSC

: F.6/DFS/ MS/2011/1564 Dated 13/07/2011

6. Fire Safety Circular No.

: F.16/Estate/CC/FS/2011/3298 to 3398

dated1.3.11

7. Date of Inspection

: 07.06.2014

8. Name of the Inspecting officers: DO Virendra Singh

9. Name and designation of

Officer from the building side

: Smt.Chawla (Incharger).

10. Year of Construction

:1996

11. 11.Applicant's letter No

: LPES/YV/201415 Dated 24.05.2014

NO.	Minimum Standards on fire prevention and fire safety U/R33	Circular	Provided at	Remark			
1	Access to building	Requirement	Site				
1	Road width	00 144	0.84	AAD			
	The source of th	06 Mtrs.	6 Mtrs.	MR			
	Gate widthWidth of internal road	N/A	N/A	N/A			
		N/A	N/A	N/A			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper Floor	01 No.	2 Nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases	*	55				
	Upper Floor	1.5 M	1.5 & 1.3 M	MR			
	Basement	N/A	N/A	N/A			
	c. Protection of exits						
	Fire check door	N/A	N/A	N/A			
	Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to	02No.	02 No.	MR			
	terrace	all continues at the second					
	g. Width of Corridor	1.5 M	1.5 M	MR			
_	h. Door Size	1.0 Mtrs	1.0 Mtrs	MR			
3	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	Upper floor	N/A	N/A	N/A			
5.	Fire Extinguishers						
	Total numbers	06 Nos.	08 Nos.	MR			
	Types	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			
6	First-aid-Hose Reels.						
	Total numbers of each floor	01No.	01No.	MR			
	 Length of hose reel hose 	30 M	30 M	MR			
	Nozzle diameter	5 MM	5 MM	MR			
7	Automatic fire detection and alarming system).					
	Type of detectors	N/A	N/A	N/A			
	Location of main panel	N/A	N/A	N/A			
	Least's a street to the street	NI/A	N/A	NI/A			

9	Public address System.	N/A	N/A	N/A
10	Automatic Sprinkler System.	N/A	N/A	N/A
	Basement	N/A	N/A	N/A
	upper floor	N/A	N/A	N/A
	sprinkler above false ceiling	N/A	N/A	N/A
11	Internal Hydrants			
	size of riser/down-comer	N/A	100 MM	MR
	Number of hydrants per floor	N/A	1 No.	MR
3	Hose Box	N/A	1 No.	MR
12	Yard Hydrants.	N/A	N/A	N/A
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.	N/A	N/A	N/A
	Ground Level	N/A	N/A	N/A
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main Pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby pump out put	N/A	N/A	N/A
A.Sile	Standby pump Head	N/A	N/A	N/A
	Auto Starting /Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace Level			
	Discharge of pump	450 LPM	450 LPM Provided	MR
	Head of the Pump	40 M	40 M	MR
	> Power supply	Required	Provided	MR
	> Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N/A	N/A	N/A
	Fire service inlet	N/A	N/A	N/A
	> Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	10000 Ltrs.	10000 Ltrs.	MR
5	Exit Signage.	Required	Provided	MR
6	Provision of Lifts.	N/A	N/A	N/A
10	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication in lift car	N/A	N/A	N/A
	Firemen's grounding switch	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A
17	Standby power supply	N/A	Provided	MR
8	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
0		N/A N/A	N/A N/A	N/A
		N/A	N/A	N/A
	Flow switch panel PA system panel			N/A
	PA system panel	N/A	N/A	
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A

, 1

NIS

20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A	
----	--	-----	-----	-----	--

The fire safety arrangements provided in the building were tested/ checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The FSC issued vide letter no. F.6/DFS/MS/2011/1564 dated 13.07.2011 renewal under the circular no. F.16/Estate/CC/FS/2011/3298 to 3398 dated 1.3.11 is recommended.

Signature of the Inspecting Officer Name: Virendra Singh

Designation:DO(ED)

DCFO(NDZ)