GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI - 110001

Fax:- 011-23412593

E-mail ID: cfohq.dlfire@nic.in

No F 6 / DFS / MS / GH / 2014 / M 2 2 17 27

Dated 13/06/14

FIRE SAFETY CERTIFICATE

Certified that the **The Sunder Guest House** located at 9776/8, **Sadar Thana Road**, **Pahar Ganj**, **New Delhi** comprises of Ground floor (02 guest rooms + reception), 1st floor to 3rd floor (06 guest rooms at each floor) and Terrace floor with total 20 guest rooms was granted NOC by this department vide letter No. F6/DFS/MS/GH/2010/2735 dated 21-09-2010. The premises was re-inspected by the officer concerned of this department on 02-06-2014 in the presence of Mr. Pritam (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Residential**, **Sub-Division A-1 lodging or rooming houses** for 20 guest rooms with effect from 13/10/6/14- for a period of **three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to:-

1. The Sunder Guest House located at 9776/8, Sadar Thana Road, Pahar Ganj, New Delhi.

2. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 20383/Joint. C.P./Lic. (H) dated New Delhi 26-05-2014.

3. The Commissioner North Delhi Municipal Corporation with a request to measure the height and appraise this department.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.

2. Any loss of life or property due to non-functional fire safety measures shall be at the

responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

14/5

INSPECTION REPORT

1. Name & address of the building : The Sunder Guest House located at 9776/8, Sadar Thana Road,

Pahar Ganj, New Delhi.

2. Type of Occupancy : Residential (Guest house) G+3+Terrace floor total guest rooms-20

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2010/2735 dated 21/09/2010

5. Fire Safety directives Letter No. : NA

6 Date of inspection : 02/06/2014

7 Name of the Inspecting Officer : Sh. M. K. Sharma (ADO/CC)

8 Name and designation of Officer

from the building side : Mr. Pritam (Manager)

9 Year of Construction : 2010

10. Applicant's letter No. : 20383/Joint.C.P./Lic. (H) dated New Delhi the 26/05/2014.

S No	Minimum standards on fire prevention	Existing	Provided at site	Remarks
	and fire safety U/R 33	Requirements	(PSS)	MR/NMR
1.	Access of building		*	
	Road width	NA	9 Mtr.	MR
	Gate width	NA	NA	NA
	Width of internal road	NA	NA	NA
2.	Number, width, Type & Arrangements	of exits	· ·	
	a. Number of staircases			
	Upper floors	1 No.	1 No.	MR
	Basements	NA	NA	NA
	b.Width of staircases			1 2
	• Upper floors	0.80 Mtr.	1.25 Mtr.	MR
	Basements	NA	NA	NA
	c. Protection of exits			
	Fire check door	NA	NA	NA

Men

	Upper floor	NA	NA	NA
	Basements	NA	NA	NA
10	Automatic Sprinkler			
)	Public Address System	Required	Provided	MR
}	MOEFA	Required	Provided	MR
.	Hooters' Location	NA	NA	NA
	Alternate source of power	NA	NA	NA
	• Location of Repeater Panel	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	Type of detectors	NA	NA	NA
7	Automatic fire detection and alarming sys	tem		
	Nozzle diameter	05 MM	05 MM	MR
	 Length of hose reel hose 	30 Mtr.	30 Mtr.	MR
	Total numbers on each floor	01	01	MR
6	First – Aid Hose Reels			
	IS marking	Required	Provided	MR
	• Types	ABC, CO ₂ , Wco ₂	ABC, CO ₂ , Wco ₂	MR
	Total numbers	10 Nos.	12 Nos.	MR
5	Fire Extinguishers			-
	Upper floors	12 ACPH	NATURAL	MR
	Basements	, NA	NA	NA
4	Smoke managements System			
1	• Fire Dampers	NA	NA	NA
	Water Curtain	NA	NA	NA
	• Fire Rating of shaft door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	NA
	Fire check door	NA	NA	NA
3.	Compartmentation			
	f. Door Size	1.0 Mtr.	1.0 Mtr.	MR
	e. Width Of Corridor	1.0 Mtr.	1.0 Mtr.	MR
	d. No of continuous staircase to terrace	1 No.	1 No.	MR
	• Pressurization	NA	NA	NA

MIZ

	• 5	Sprinkler above false ceiling	NA	NA	NA.	
1	Internal	Hydrants				
	• 9	Size of riser/down- comer	NA	NA	NA	
	•]	Number of hydrants per floor	NA	NA	NA	
	•]	Hose Box	NA	NA	NA	
)	Yard H	vdrants			***************************************	
	•	Total number of hydrants	NA	NA	NA	
	•]	Hose Box	NA	NA	NA	
	Pumping Arrangements					
	0	Ground Level				
	•	Discharge of main pump	NA	NA	NA	
	•	Head of main pump	NA	NA	NA	
	•	Number of main pumps	NA	NA	NA	
	•	Jockey pump out put	NA	NA	NA	
	•	Jockey pump head	NA	NA	NA	
	•	Standby Pump out put	NA	NA	NA	
	•	Standby Pump Head	NA	NA	NA	
	•	auto Staring/Manual stopping	NA	NA	NA	
	•	Pump House Access	NA	NA	NA	
	0	Terrace level	NA	NA	NA	
	•	Discharge of pump	450 LPM	450 LPM	MR	
	•	Head of the pump	30 Mtr.	30 Mtr.	MR	
	•	Power supply	Required	Provided	MR	
	•	Auto starting of pump	Required	Provided	MR	
14	Captive	water Storage for fire fighting	NA	NA	NA	
	•	Under ground tank capacity	NA	NA	NA	
	•	Draw of connection	NA	NA	NA	
	•	Fire service inlet	NA	NA	NA	
	•	Access to tank	Required	Provided	MR	
	•	Overhead Tank capacity	2500 ltr.	2500 ltr.	MR	
5	Exit Si		Required	Provided	MR	

NA

6	Provision of Lifts	NA	NA	NA	
c	Pressurization of Lift Shaft	NA	NA	NA	
	Pressurization of lift lobby	NA	NA	NA	
	Communication in lift Car	NA	NA	NA	
	Fireman's Grounding Switch	NA	NA	NA	
	Lift Signage	NA	NA	NA	
7	Standby power supply	Required	Provided	MR	
8	Refuge Area				
	Total area	NA	NA	NA	
	• Location	NA	NA	NA	
9	Fire control room				
	Detector system panel	NA	NA	NA	
	Flow Switch Panel	NA NA	NA	NA	
2	PA System Panel	NA	NA	NA	
	Batter backup	NA	NA	NA	
	Building Floor Plans	NA	NA	NA	
20	Special Fire Protection Systems for	Required	ABC,Co ₂	MR	
	Protection of special Risks, if any;	v	1	-	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2010/2735 dated 21/09/2010 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended please.

Name: - Sh. M. K. Sharma

Designation: - A. D.O. (CC)