FORM 'H'
FORM FOR ISSUING FIRE SAFETY CERTIFICATE
[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

No. F6/OFS/MS/2014/62/80/

Dated: 27/06/14

FIRE SAFETY CERTIFICATE

Certified that the Moments Mall located at Plot No. 67, DIT Industrial Area, Nazafgarh Road, Kirti Nagar, New Delhi - 110015 comprised of 2 Basement + Ground + 2 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2011/993 dated 26-05-2011. The premises was re inspected by the officers concerned of this department on 05-06-2014 in the presence of Mr. Rampal Tyagi (Head – Fire & Safety) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile Building" Group F with effect from 27/o6/17 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on .2.7/06/19 at New Delhi by.

Santokh Singh Chief Fire Officer Delhi Fire Service

E-mail: cfowz.dlfire@nic.in

Phone: 011-23414250

Copy to:

 Sh. Rampal Tyagi (Head – Fire & Safety), Moments Mall, Plot No. 67, Nazafgarh Road, New Delhi – 110015.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock:
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name & address of the building: Moments Mall, Plot No. 67, Nazafgarh Road, Kirti Nagar, New Delhi – 110015

2. Type of Occupancy

: Mall (Mercantile Group - F)

3. Type of Case

: Renewal

4. Details of previous NOC : Letter No. F6/DFS/MS/2011/993 dated 26-05-2011 & F6/DFS/MS/2011/2511 dated 13-10-2011 (for change of occupancy from Industrial to Mercantile)

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2007/1796 dated 09-07-07

6. Date of inspection

: 05-06-2014

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Rampal Tyagi (Head – Fire & Safety)

9. Year of Construction

: 2011

10. Applicant's letter No.

: F5/MM/KN dated 06-05-2014 (Form J)

S	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR
No	prevention and fire safety U/R 33	Requirements	site	
1.	Access of building			
	 Road width 	60 m	Provided	MR
	 Gate width 	6 m	Provided	MR
	 Width of internal road 	6 m	Provided	MR
2.	Number, width, Type & Arrangem		1 C ₋₁	
	a. Number of staircases			
	 Upper floors 	14	Provided	MR
	 Basements 	16 + 2 Ramps	Provided	MR
	b. Width of staircases			
	 Upper floors 	Old Case	Old Case	MR
	Basements	Old Case	Old Case	MR
	c. Protection of exits			
	 Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor 	Required	Provided	MR
		Required	Provided	MR
		Required	Provided	MR
		Old Case	Old Case	MR
	f. Door Size	Old Case	Old Case	MR
3.	Compartmentation		1	19
	 Fire check door 	Required	Provided	MR
	 Sealing of electrical shafts 	Required	Provided	MR
	 Fire Rating of shaft door 	Required	Provided	MR
	 Water Curtain 	Required	Provided	MR
	 Fire Dampers 	Required	Provided	MR

1/24

4.	Smoke managements System						
	Basements	30 a/c per hour	Provided	MR			
	Upper floors	12 a/c per hour	Provided	MR			
5.	Fire Extinguishers	1					
	Total numbers	291 nos.	Provided	MR			
	• Types	ABC, CO ₂ &	Provided	MR			
		WCO ₂					
	 IS marking 	ISI marked	Provided	MR			
6.	First – Aid Hose Reels						
	 Total numbers on each 	16	Provided-	MR			
	floor	36 m	Provided	MR			
	 Length of hose reel hose 	5 mm	Provided	MR			
	 Nozzle diameter 			a a			
7.	Automatic fire detection and alarm		v.				
	 Type of detectors 	Smoke & Heat	Provided	MR			
	 Location of Main Panel 	Required	Provided	MR			
	 Location of Repeater 	Required	Provided	MR			
	Panel	Required	Provided	MR			
	 Alternate source of power 	Required	Provided	MR			
	Hooters' Location						
8.	MOEFA	Required	Provided	MR			
9.	Public Address System Required Provided MR						
10.	Automatic Sprinkler System						
	Basements	Required	Provided	MR			
	• Upper Floor	Required	Provided	MR			
	Sprinkler above false	Required	Provided	MR			
11.	ceiling Internal Hydrants			3			
	Size of riser/down-comer	150 mm	Provided	MR			
	 Number of hydrants per 	16	Provided	MR			
	floor		TTOVICCO	IVIIX			
	Hose Box	Required	Provided	MR			
12.	Yard Hydrants			1			
	Total number of hydrants	15	Provided	MR			
	Hose Box	Required	Provided	MR			
13.	Pumping Arrangements						
	Ground Level						
	 Discharge of main pump 	2280 lpm	Provided	MR			
	Head of main pump	75 m	Provided	MR			
	Number of main pumps	2	Provided	MR			
	Jockey pump out put	180 lpm	Provided	MR			
	Jockey pump head	75 m	Provided	MR			
	Standby Pump out put	2280 lpm	Provided	MR			
	Standby Pump Head	75 m	Provided	MR			
	Auto Staring/Manual	Required	Provided &	MR			
	stopping Pump House Access	5	Functional				
	 Terrace level 	Required	Provided	MR			
	Discharge of pump	000.1		NO			
	Head of the pump	900 lpm	Provided	MR			
L	o. a.e pamp	40 m	Provided	MR			

	Power supply	Required	Provided	MR	
	Auto starting of pump	Required	Provided	MR	
14.	Captive water Storage for fire figh	ting			
	 Under ground tank capacity 	2,00,000 litres	Provided	MR	
	Draw of connection	Required	Provided	MR	
	Fire service inlet	Required	Provided	MR	
	Access to tank	Required	Provided	MR	
	 Overhead Tank capacity 	30, 000 litres	Provided	MR	
15	Exit Signage	Required	Provided '	MR	
6.	Provision of Lifts				
	Pressurization of Lift Shaft	Required	Provided	MR	
	Pressurization of lift lobby	Required	Provided	MR	
	Communication in lift Car	Required	Provided	MR	
	Fireman's Grounding Switch	Required	Provided	MR	
	➤ Lift Signage	Required	Provided	MR	
7.	Standby power supply	Required	Provided	MR	
8.	Refuge Area				
	Total area	Not Required	Not Required	Not Required	
	Location	Not Required	Not Required	Not Required	
9.	Fire control room				
	Detector system panel	Required	Provided	MR	
	Flow Switch Panel PA System Panel Battery backup Building Floor Plans	Required	Provided	MR	
		Required	Provided	MR	
		Required	Provided	MR	
		Required	Provided	MR	
0.	Special Fire Protection Systems for Protection of special Risks, if any;	CO ₂ Flooding System for HT & LT Panel	Provided	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2011/993 dated 26-05-2011 & F6/DFS/MS/2011/2511 dated 13-10-2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the In

Signature of the Inspecting Officer

Name

MUKESH YERMA

Name

Designation ADO WW)

Designation

The file to be sent after