GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

No. F6/DF3/ms/2014/c/ws/52/8/2

Dated:

30/6/14

FIRE SAFETY CERTIFICATE

Issued on 30/6/19 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

- 1. Assistant Commissioner Excise (Hotel /Clubs), GNCT of Delhi, L & N block, I.P Estato, Vikas Bhawan, I.P Estate, New Delhi-110002.
- 2. The Hony. Secretary, Panchsheel Club located at Panchsheel Park, New Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building : Panchsheel Club located at Panchsheel Park, New Delhi

2. Type of Occupancy : Assembly (Club)

3. Type of Case : Renewal

4. Details of previous NOC : F.6/DFS/MS/EH/2011/563 dated 31-03-2011

5. Fire Safety directives letter No : Order No. 4/22/2004/HP-III/356-359 dated 22/03/2005.

6. Date of inspection : 24-06-2014

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

9. from the building side : Mr. K.D. Pantola, Manager

10. Year of Construction : 2009-10

11. Applicant bletter No. : nil dated 10-05-2014

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC/BBL Requirement	Provided at site	Remarks MR/NMR	
	Access to building		8		
	Road width	06 mts	Provided	MR	
	Gate width	4.5 mts	Provided	MR	
	 Width of internal road 	03 mts	Provided	MR	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases	-	_		
	• Upr Fleors	02	Provided (03)	MR	
	• Basements	01	01	MR	
	b. Width of staircases	-		-	
	 Upper Floors 	1.5 mts each	1.5, 1.25, 0.97 mts	MR	
	• Basement	Old case	1.10 mts	MR	
	c. Protection of exits				
	Fire check door	N/A	N/A	N/A	
	 Pressurization 	N/A	N/A	N/A	
	d. No. of continuous staircases to terrace	02	02	MR	
	e. Width of Corridor	N/A	N/A	N/A	
	f. Door Size	N/A	N/A	N/A	
	Compartmentation.	2	11//11	* 1/ 2 2	

				V		
	 Fire check door 	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	• Basements	30 a/c per hour	Exhaust fan provided	MR		
	Upper floors	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers					
	• Total numbers	10	Provided	MR		
	• Types	ABC, CO_2	Provided	MR		
	IS marking	ISI marked	Provided	MR		
	First-Aid Hose Reels.					
	 Total numbers on each floor 	01	Provided	MR		
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	N/A	N/A	N/A		
	 Location of Main Panel 	N/A	N/A	N/A		
			STATE STATE OF THE			
e	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
				1771		
	MOEFA	Required	Provided	MR		
	Public Address System.	Required	Provided	MR		
)	Automatic Sprinkler System.			9 ×		
	• Basement	Required	Provided in store	MR		
	• Upper Floor	Required in kitchen & restaurant at first floor	Provided	MR		
	 Sprinkler above false ceiling 	N/A	N/A	N/A		
,	Internal Hydrants					
	Size of riser/down-comer	100 mm	Provided	MD		
	 Number of hydrants per floor 		Fiovided	MR		
	Hose Box	01	Provided	MR		
		01	Provided	MR		



2	Yard Hydrants.			
	Total number of hydrants	N/A	N/A	N/A
9	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	N/A	N/A	N/A
	Head of Main pump	N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
8	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual	N/A	N/A	N/A
	stopping	N/A	N/A	N/A
	> Tump House Access			
	Terrace level	900, 180 LPM	Provided	MR
	Discharge of pump	40 mts	Provided	MR
	Head of the pumpPower Supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for fire fighting.	Maintained by ma	ail	
	Underground tank capacity	35,000 liters	Provided	MR
	Draw-off connection	Required	Provided	MR
	> Fire service inlet	Required	Provided	MR
	> Access to tank	Required	Provided	MR
	 Overhead Tank capacity 	15,000 liters	Provided	MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.		ā	
	 Pressurization of Lift Shaft 	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	Required	Provided	MR
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR

?



Standby power supply	Required	Provided (125, 62 KVA)	MR*
Refuge Area.		*1 **	>
> Total Area	N/A	N/A	N/A
> Location	N/A	N/A	N/A
Fire Control Room			2
Detector System Panel	N/A	N/A	N/A
Flow Switch Panel	N/A	N/A	N/A
PA System Panel	Required	Provided	MR
Batter backup	Required	Provided	MR
Building Floor Plans	N/A	N/A	N/A
Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 CO ₂ type fire extinguishers found provided near elect.	MR
	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup • Building Floor Plans Special Fire Protection Systems for	Refuge Area. > Total Area	Refuge Area. Total Area N/A Location N/A N/A N/A Fire Control Room Detector System Panel Flow Switch Panel PA System Panel PA System Panel Batter backup Building Floor Plans Special Fire Protection Systems for Required KVA) N/A N/A N/A N/A Required KVA) N/A N/A N/A N/A N/A Provided Provided Required N/A N/A N/A N/A N/A N/A N/A N/

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/EH/2011/563 dated 31-03-2011, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

2016/14

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)