GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/School/2014/ \$2 / 840

Dated: 08/07/19

FIRE SAFETY CERTIFICATE

Certified that the building of **Bal Bharti Public School** located at Pusa Road, New Delhi-110005 is comprised of Basement, ground floor plus three upper floors was issued NOC by this department vide letter No.F.6/DFS/MS/2011/1285 dated 21.06.2011. The School building was re-inspected by the officer concerned of this department on 27.06.2014 in the presence of Sh. L.V. Sehgal (Principal) and found that the school management have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Educational w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- The Principal, Bal Bharti Public School, Pusa Road, New Delhi-110005.
- Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi – 110 054.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	M12							
	INSPECT	ION REPORT						
	1. Name & address of the building: 80/ 86 aread Printing Co.							
	2. Type of Occupancy :	Educational (School)						
	. The or case	New Case/Renewal						
	4. Details of Previous NOC	Letter No. <u>F.6/DFS/MS/2011/1285</u> Date <u>21.06.201</u> 27.06.2014						
	, 23 (21(6) 140							
	6. Date of inspection							
	7. Name of Inspecting Officer							
	8. Name and designation of officers							
	From the building side	Sh. L.V. Sel	igal (Principal)	4				
	. Tear of constitution	Before 1995	gar Corragar)					
	10. Applicant's letter No.	1911/88/2014	dated 11:06	2011.				
S.	Minimum Standards on fire	NBC/BBL	Provided at					
No.	prevention and fire safety U/R 33	Requirement		Remarks				
1.	Access to building	The strict of th	Jice	MR/NMR				
	 Road width 	Accessible	lamtr	MR				
	Gate width		06 mts	MR				
	Width of internal road		00000	11/1				
2.	Number, Width, Type & Arrangement	of Evita						
	a. Number of staircases	DIEXILS	T	!				
	• Upper Floors							
	• Basements	Two	Two	MR				
	b. Width of staircases	-do-	-do-	MR				
	Upper Floor							
	Basements	150 cms Each	170cms Each	MR				
	c. Protection of exits	150 cms Each	170 cms, 175 cms	MR				
	Fire check door			T .				
	• pressurization		1	And the second s				
	d. No. of continuous staircases to	-		Square pr				
	terrace to			***				
	e. Width of Corridor		One	American				
	f. Door Size	-	253 cms, 249 cms					
			110 cms x 205 cms					
3.	Compartmentation		The process can be					
	Fire check door		·					
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain 	-		-				
			Sealed	•				
			· ·					
	• Fire Dampers	-		Comm.				
4.	Smoke Management System	-						
		T						
	Basements	30 a/c per	Exhaust Fans	Nae				
	 Upper flcors 		are Provided	MR				
		No	rtural Ventilation	MR				



	M16.	and the second s	a a a a a a a a a a a a a a a a a a a	
		12 a/c per		
		hour		ž
5.	Five F. A.			
J.	Fire Extinguishers			
	• Total numbers	four ateach. Floo	Provided	MR
	• Types	ABC, Co2	- de -	MR
-	• IS marking	ISI marked	1SI Marked	MR
6.	First-Aid Hose Reels			
	 Total numbers on each floor 	Two	Provided	MR
	Length of hose reel hose	30 m	- do -	MR
1	 Nozzle diameter 	5 mm	- do:-	MR
7.	Automatic fire detection and alarming	system		1 7 7
	 Type of detectors 	-		
1	 Location of Main Panel 			
4	 Location of Repeater Panel 			
1	 Alternate source of power 		02 D. G. Set of 100 KV	4
	 Hooters' Location 	2	18 SO KVA	+
8.	MOEFA			
9.	Public Address System		Parill	h a
10.	Automatic Sprinkler System	1	Provided	MR
	• Basement	Realizad	Partie	MR
	Upper Floor	Required	Provided	14//0
	 Sprinkler above false ceiling 	· ·		
11.	Internal Hydrants			
	Size of riser/down-comer		1000	
	Number of hydrants per floor		100 m.m	MR
	Hose Box		One	MR
12.	Yard Hydrants		- do-	MR
	Total number of hydrants		J.	
	* Hose Box		One -	MR
13.	Pumping Arrangements		-do-	MR
	• Ground Level			
	Discharge of main Pump			
	> Head of Main pump			4
	Number of main pumps	-		-
	> Jockey Pump out put			
	> Jockey pump head	Common Co		-
	Standby Pump out put			
	Standby Pump Head	-		
	Auto Starting/Manual	-		
	stopping			5.2
<u></u>	J			



	Pump House Access	-		
	Terrace level			
	Discharge of pump	900 LPM	0. 10 10	
	> Head of the pump		900 LPM, 180 LPM	MR (02
	> Power Supply	30 M Required	30 M Each Provided	MR
	Auto Starting of pump		roovided	MR.
14.	Captive Water Storage for fire fighting		,	
	 Underground tank capacity 	_		
	Draw-off connection			
	Fire service inlet		0	
	Access to tankOverhead Tank capacity		Provided	MR
		10		
		15000 Ltr	15000 Ltr	MR
15.	Exit Signage.	15000 Ltr Required	Provided	MR
6.	Provision of Lifts.			3
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 			
	Communication In lift Car	-	,	1
	 * Fireman's Grounding Switch 	•	_	_
	Lift Signage	- 2		2
• • • • • • • • • • • • • • • • • • • •		_	20 E	
.7.	Standby power supply	Required	Provided	MR
8.	Refuge Area.			
	> Total Area			
	> Location		- A	
		2		
9.	Fire Control Room	8		-
	Detector System Panel			
	Flow Switch Panel			1
z	PA System Panel			
	Batter backup		Sec.	
	Building Floor Plans		_	
).	Special Fire Protection System for Protection of special Risks, if any:			



The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2011/1285 dated 21.06.2011 renewal under rule 35 of the

Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name P.S. Dahiya

Designation ASSH. Divisional Officer.

Signature of Inspecting Officer

Name

Designation

Prenewal F.S.C. is put up for Kind approval & signature please