FORM FOR ISSUING FIRE SAFETY CERTIFICATE [Refer sub - rule (1) of rule 35] GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE FILDFI) MS FHIZOIN WZ/ 857 14/7/14 Dated:

FIRE SAFETY CERTIFICATE

Certified that the M/s Pacific & Asia Restaurants (A Unit of M/s Ravi Kishore Enterprises). located at No. 2, First Floor, Plot No. G - 3, Cascade Shopping Centre, Netaji Subhash Place, New Delhi - 110034 was issued FSC vide Letter No. F6/DFS/MS/2011/EH/1421 dated 04-07-2011 in a building comprised of G+1 Upper Floor. The premises was re inspected by the officers concerned of this department on 01-207-2014 in the presence of Mr. Ravinder Bhatia (Partner) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule. 2010 and that the premises is fit for occupancy class "Assembly" Group D with effect from 14/7/14 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules. 2010.

Issued on 14/7/19 at New Delhi by:

Copy to:

1. Deputy Health Officer (Rohini Zone). Public Health Department (NDMC). Sector - V, Delhi 110085.

2. Sh. Ravinder Bhatia. No. 2, G – 3. Cascade Shopping Centre. Netaji Subhash Place, Pitampura. New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovi.nic in.

INSPECTION REPORT

1. Name & address of the building: Pacific & Asia Restaurants (A Unit of M/s Ravi Kishor Enterprises), First Floor, No. 2, G = 3, Cascade Shopping Centre, Netaji Subhash Place, Pitampura, Delhi – 110034.

2. Type of Occupancy

: Assembly (G + 1 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F6/DFS/MS/2011/EH/1421

dated 04-07-2011

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 01-07-2014

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Ravinder Bhatia (Partner)

9. Year of Construction

: 2005

10. Applicant's letter No.

: Nil dated 17-06-2014

| S No | Minimum standards on fire prevention and fire safety U/R 33 | BBL Requirements | Provided at site | Remarks MR/NMR |
|---------|---|---------------------|------------------|-------------------|
| 1. | Access of building | | | |
| | Road width | 6 m | Provided | MR |
| | Gate width | NA | NA | NA . |
| | Width of internal road | NA | NA | NA |
| 2. | Number, width, Type & Arrange | ements of exits | | , |
| | a. Number of staircases | | | |
| | Upper floors | 2 | 4 / | MR |
| | Basements | NA | NA | NA |
| | b. Width of staircases | | | |
| | Upper floors | Old Case | Old Case | MR |
| | Basements | NA | NA | NA |
| | c. Protection of exits | | | |
| | Fire check door | NA | NA | NA |
| | Pressurization | NA | NA | NA |
| | d. No of continuous | NA | NA | NA |
| - | staircase to terrace | * * | | |
| - | e. Width Of Corridor | NA | NA | NA |
| 7 | f. Door Size | Old Case | Old Case | Old Case |
| 3. | Compartmentation | | | |
| | Fire check door | Required in | Provided _ | MR |
| | | Kitchen | | |
| | Sealing of electrical | Required | Provided | MR |
| | shafts | | | |

3. Type of Case

: Renewal

4. Details of previous NOC dated 04-07-2011

: Letter No. F6/DFS/MS/2011/EH/1421

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 01-07-2014

7. Name of the Inspecting Officer: DO (West) & ADO (MN)

8. Name and designation of Officer

from the building side

: Sh. Ravinder Bhatia (Partner)

9. Year of Construction

: 2005

10. Applicant's letter No.

: Nil dated 17-06-2014

| S No | | n standards on fire on and fire safety U/R | BBL Requirements | Provided at site | Remarks MR/NMR | |
|---------|---|--|---------------------|--|-------------------|--|
| 1. | Access of building | | | | | |
| | | oad width | 6 m | Provided / | MR | |
| | • 6 | fate width | NA | NA | NA | |
| | • \> | Vidth of internal road | NA | NA | NA | |
| 2. | Number, width, Type & Arrangements of exits | | | | | |
| | a. N | Jumber of staircases | | | | |
| | | pper floors | 2 | 4 | MR | |
| | • B | asements | NA | NA | NA | |
| | b. V | Vidth of staircases | | | | |
| | • L | pper floors | Old Case | Old Case | MR | |
| | • B | asements | NA | NA | NA | |
| | c. P | rotection of exits | | | | |
| | · F | ire check door | NA | NA | NA · | |
| | • P | ressurization | NA | NA | NA | |
| | d. N | lo of continuous | NA | NA | NA | |
| | S | taircase to terrace | | | | |
| | 8 | Vidth Of Corridor | NA | NA | NA | |
| | f. L | Door Size | Old Case | Old Case | Old Case | |
| 3. | Compartmentation | | | | 1 | |
| | • [| ire check door | Required in Kitchen | Provided _ | MR | |
| | | lealing of electrical hafts | Required | Provided | MR | |
| | | ire Rating of shaft | NA | NA | NA | |
| | E | Water Curtain | NA | NA | NA | |
| | | ire Dampers | NA | NA | NA | |
| 4. | | nanagements System | | | | |
| | | Basements | 30 a/c per hour | NA . | NA | |
| | 1 | Jpper floors | 12 a/c per hour | and the second s | MR | |
| 5. | | inguishers | 1 | | / | |
| | | Total numbers | 10 nos. | Provided | MR | |

| | • Types | ABC & CO ₂ | Provided | MR |
|------|---|-----------------------|----------|--|
| | IS marking | ISI marked | Drovidad | NAID. |
| 6. | First – Aid Hose Reels | 131 marked | Provided | MR |
| | Total numbers on each | 2 | Provided | MR |
| | floor | 2.0 | | |
| | Length of hose reel hose | 30 m | Provided | MR |
| | Nozzle diameter | 6.5 mm | Provided | NAD |
| 7. | Automatic fire detection and ala | | Provided | MR |
| /. | Type of detectors | | Provided | MR |
| | Location of Main Panel | 1 | Provided | MR |
| | Location of Repeater | NA NA | NA | NA NA |
| | Panel | | IVA | INA |
| | Alternate source of | Required / | Provided | MR |
| | power | Required / | 110,100 | THE STATE OF THE S |
| | · Hooters' Location | Required / | Provided | MR |
| 8. | MOEFA | Required (| Provided | MR |
| 9 | Public Address System | Required (| Provided | MR |
| .10. | Automatic Sprinkler System | | 11011000 | 1711 |
| | Basements | NA | NA | NA |
| | Upper Floor | Required | Provided | MR |
| | Sprinkler above false ceiling | Required 1 | Provided | MR |
| 11. | Internal Hydrants: | | | |
| | Size of riser/down- | NA | NA | NA |
| | comer | | 1324 | 100 |
| | Number of hydrants per floor | NA | NA | NA |
| | Hose Box | NA | NA | NA |
| 12. | | | 1 1 1 1 | 1177 |
| | Total number of | NA | NA | NA . |
| | hydrants | | | |
| | • Hose Box | NA | NA | NA |
| 13. | Pumping Arrangements: | | | |
| | • Ground Level | N. F. | | |
| | Discharge of main | NA | NA | NA |
| | pump | NA . | NA | NA |
| | Head of main pump Number of main pumps | NA | NA - | NA |
| | Jockey pump out put | NA NA | NA | NA |
| | Jockey pump head | NA · | NA NA | NA |
| | Standby Pump out put | NA | NA: | NA. · |
| | Standby Pump Head | NA | NA NA | NA NA |
| | Auto Staring/Manual | 1.42-1 | INT | 11/1 |
| | stopping | NA | NA | .NA |
| | Pump House Access | | | 1.4.07 |
| | Terrace level | 450 lpm. 180 / | Provided | MR |
| | Discharge of pump | lpm | | |
| | - Head of the pump | 40 m | Provided | MR |
| | Power supply | Required | Provided | MR |
| | Auto starting of pump | Required | Provided | MR |
| 14. | Captive water Storage for fire fig | hting: | | |

| | Nozzle diameter | 6.5 mm | Provided | MR · |
|-----|--|---------------|------------|----------|
| 7. | Automatic fire detection and alar | I | | |
| | Type of detectors | Smoke / | Provided | MR |
| | Location of Main Panel | First Floor | Provided | MR |
| | • Location of Repeater | NA | NA NA | NA |
| | Panel | 1111 | 132 € | 1112 |
| | Alternate source of | Required / | Provided | MR |
| | power | recquired | 1101100 | |
| | • Hooters' Location | Required / | Provided | MR |
| 8. | MOEFA | ļ | Provided | MR |
| 9. | Public Address System | Required (| Provided | MR |
| 10. | Automatic Sprinkler System | required t | Trovided | IVIIX |
| IV. | Basements | NA | NA | NA |
| | | Required | Provided | MR |
| | • Upper Floor | Required / | Provided | MR |
| | Sprinkler above false spiling | Required | TTOVICE | IVIIX |
| 1.1 | ceiling | | | |
| 11. | Internal Hydrants: | NA | NA | NA |
| | Size of riser/down- | INA | 17.71 | NA |
| | comer | NA | NA | NA |
| | Number of hydrants per floor | INF | INA | INA |
| | | NA | NA | NA |
| 1.3 | Hose Box Vand Hadronts | 11/1 | 1877 | 177.7 |
| 12. | Yard Hydrants | NA | NA NA | NIA |
| | Total number of | IVA | 1.7.77 | ŅΑ |
| | hydrants | NA | NA | NA |
| 1.0 | • Hose Box | INA | 11// | 1874 |
| 13. | Pumping Arrangements: | | | |
| | Ground Level | NIA | NIA | NIA |
| | Discharge of main | NA | NA | NA |
| | pump | NA . | NA | NA |
| | Head of main pump | NA . | NA | NA |
| | Number of main pumpsJockey pump out put | NA | NA | NA NA |
| | Jockey pump bead | NA NA | NA TNA | NA NA |
| | Standby Pump out put | NA . | NA. | NA NA |
| | Standby Pump Head | NA NA | | NA I |
| | Auto Staring/Manual | INA | NA | 1771 |
| | stopping | NA | NA · | .NA |
| | Pump House Access | 1873 | 1,777 | 1.1777 |
| | Terrace level | 450 lpm, 180 | Provided | MR |
| | Discharge of pump | lpm | Trovided | IVIIV |
| | Head of the pump | 40 m | Provided | MR |
| | - Power supply | Required | Provided | MR |
| | Auto starting of pump | Required | Provided | MR |
| 14 | Captive water Storage for fire fi | | Trovided | 1111 |
| | Under ground tank | INA | NA | NA - |
| | capacity | 1 74 5 | | 1 N. A |
| | Draw off connection | NA T | NA | NA . |
| | - Fire service inlet. | NA TOTAL | NA | NA |
| | - Access to tank | NA | Provided | MR |
| | Overhead Tank | 5000 litres (| Provided : | MR |
| | capacity | (| | |
| 115 | Exit Signage | Required / | Provided | MR |
| 16. | Provision of Lifts | | | |
| 9 | | | | |

| | Pressurization of Lift | NA | NA | NA |
|-----|---|----------------------------|----------------------------|-------------------|
| | Shaft Pressurization of lift | NA | NA | NA |
| | lobby Communication in lift | NA | NA | NA |
| | Car Fireman's Grounding | NA | NA | NA |
| | Switch > Lift Signage | NA | NA | NA |
| 17. | Standby power supply | Required | Provided | MR |
| 18. | Refuge Area Total area Location | NA NA | NA NA | NA NA |
| 20. | Detector system panel Flow Switch Panel PA System Panel Battery backup Building Floor Plans | NA NA NA NA NA | NA NA NA NA NA | NA NA NA NA NA NA |

The fire protection systems provided in the building were test checked and

found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2011/EH/1421 dated 04-07-2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Aspecting Pricer

Signature of the Inspecting Officer

Name

MUKESH VERMA

Name

Designation ADO (MN)

Designation