GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001**

NO. F6/DFS/MS/School/2014/WZ/877

Dated: 17/07/2014

FIRE SAFETY CERTIFICATE

Certified that Saraswati Shishu Vidyalaya Gali No-1-A, Swatantra Nagar, Narela, <u>Delhi-110040</u> comprised of <u>Ground + one upper floor</u> owned / occupied by <u>Saraswati Shishu</u> Vidyalaya has already been issued fire safety certificate vide letter no. F.6/DFS/MS/2011/1006 Dated 27/05/2011. The premises was re-inspected by the officer from this department on dated 24/06/2014 in the presence of Smt. Kamlesh Mrig (Manager) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition. The premises have therefore deemed complied with the requirements of Circular issued by Director of Education letter dated 17/01/2005 and the building / premise is fit for occupancy of Group Class B (Educational) with effect from 17 / 07/2014 for a period of three years, subject to compliance of the conditions mentioned below:

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

Issued on 17/67/14 at New Delhi by

Chief Fire Officer Ph: 011-23414250

Copy to:

- 1. The Principal, Saraswati Shishu Vidyalaya Gali No-1-A, Swatantra Nagar, Narela, Delhi-800
- 2. The Director of Education, Old Secretariat, Delhi

Ground + one floor

		PEROPE		*		
1	1. Name & address of the building : Sahah walk Shishy volyglagg bali No. 1A					
1. 2.	Name & address of the building : Sarah wall Shishu Vingalagar Narely Type of Occupancy : Educational Swatantas Nagas Narely Belli-40					
3.	Type of Case : New ease/Renewal : $\frac{1}{1006}$ $\frac{1}{100$					
4.	Details of previous NOC : Free	5/0F3/M3/2	e ell (coo ac			
5.	Fire Safety directives letter No :	is of Educal	ion - 2005			
. 6.	Date of inspection : 24	4.6.14				
7.	A Comment	DOBW				
8.	a langer					
	from the building side					
9.	Year of Construction : 2	004	and a selle of	+ 17.6.14		
10.	Applicant's letter No. : Us	Mo. SSV/01/2	-0/3-2019	0		
Plot a	rea-320 Sq. Yards. 200 Sq. ya	o's of student- 210	No's of class room-	effice.		
,		Dir. of Edu.	Provided at site	Remarks		
	Minimum Standards on fire prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building		ma sastale			
1	Road width	Accessable	with two Hose	MR		
,	Gate width		_ length			
	 Width of internal road 					
•	Number, Width, Type & Arrangement	of Exits	1			
2	· a. Number of staircases					
	Upper Floors	01	02	MR		
	Basements b. Width of staircases					
-	Upper Floors	1.50Mz	1708.75Mts	mr.		
		1 30				
	Basements C. Protection of exits	Quantity (
	Fire check door					
				1		
	Pressurization					
	e. No. of continuous staircases to terrace					
	g. Width of Corridor	olderse	old case	oldcase		
	h. Door Size	olg cust	Over Cover			
3	Compartmentation.					
	Fire check door					
	 Sealing of electrical shafts 		NA			
	 Fire Rating of shaft door 					
	Water Curtain	. /	_			
A CONTRACTOR OF THE PARTY OF TH	Fire Dampers					
1	Smoke Management System.					
4	Basements	30 a/c per hour	111			
and a second	• Upper floors	12 a/c per hour	MI	•		
		· · · · · · · · · · · · · · · · · · ·				
-	Eiro Extinguishers					

	from the building side :	-004	O	/
- 1		No. SSV/01/	2017-2014	14.17.6.10
	area-320 Sq. Yando. 200 Sq. 4	lo's of student- 21 c	No's of class room	1- 8
	310 Sq. Gardo, 200 39.4	whols. 210	on	e office.
	Minimum Standards on fire prevention and fire safety U/R 33	Dir. of Edu. Requirement	Provided at site	Remarks MR/NMR
1	Access to building			
	Road width	Accessable	Accessable with Two Hos	MR
	Gate width		length	<u> </u>
	Width of internal road	Characteristic		***
2	Number, Width, Type & Arrangement	of Exits		
	· a. Number of staircases			_
	Upper Floors	0)	02	mR
	Basements			-
	b. Width of staircases			
	Upper Floors	1.50Mz	1708 55 mts	mR-
	Basements	1 30		"" (
	c. Protection of exits	-		
	Fire check door			
	 Pressurization 			
	e. No. of continuous staircases to terrace		Company of the Compan	•
	g. Width of Corridor			-
	h. Door Size	oldase	oldcase	oldcase
3	Compartmentation.			
	Fire check door			
	Sealing of electrical shafts	- 3		
	Fire Rating of shaft door	1	ALF	
	Water Curtain			
	Fire Dampers		· · · · ·	
4	Smoke Management System.		<u> </u>	*
	Basements	30 a/c per hour	.4 10	
	Upper floors	12 a/c per hour	NI	•
5	Fire Extinguishers			
•	Total numbers			MR
	• Types	5 ABG	ABG	
	IS marking	ISI marked		MR
			yes	MR
6	First-Aid Hose Reels.			
	Total numbers on each floor	One at each floor	0	MR

				1		
62	Length of hose reel hose	30 m	· P		mr	
	Nozzle diameter	5 mm	P	· m	K	
7	Automatic fire detection and alarming s	system.				
	Type of detectors		1			
•	Location of Main Panel					
	Location of Repeater Panel		1		1	
	Alternate source of power	× .				
	Hooters' Location		IA			
8	MOEFA					
9	Public Address System.					
10	Automatic Sprinkler System.					
10				·		
	• Basement					
7 9	• Upper Floor		1			
	Sprinkler above false ceiling					
11	Internal Hydrants		10/			
181	Size of riser/down-comer		JIK			
	Number of hydrants per floorHose Box	/	1			
		-/	0	***		
12	Yard Hydrants.					
	Total number of hydrants	/	•			
	Hose Box					
13	Pumping Arrangements.	*	9	10° 10° 10° 10° 10° 10° 10° 10° 10° 10°		
	Ground Level					
	Discharge of main Pump					
	Head of Main pump		•		_	
	Number of main pumps				· · · · · · ·	
	Jockey Pump out put	1	M			
	Jockey pump head					
	Standby Pump out put		7 1	1, 1		
	Standby Pump Head					
	Auto Starting/ Manual					
	stopping		*			
	Pump House Access		1 1			
	Terrace level	/				
-	Discharge of pump	220LPM	8	OLPH	MR	
	Head of the pump	hom	4	OM	MR	
	Power Supply			,		
1.4	Auto Starting of pump	Company of the Compan				
14	Captive Water Storage for fire fighting.					
	Underground tank capacity		114			
	> Draw-off connection	N 1971 Stagging Stage	The			

0	MOEFA			1
9	Public Address System.			- 1
10	Automatic Sprinkler System.			
2	BasementUpper FloorSprinkler above false ceiling			
11	Internal Hydrants			
	 Size of riser/down-comer Number of hydrants per floor Hose Box 		11/14	
12	Yard Hydrants.			
2	Total number of hydrantsHose Box			
13	Pumping Arrangements.			
	 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/ Manual stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump 	220LPM 40M	2202PM 40M	MR MR
4	Captive Water Storage for fire fighting.			
	 Underground tank capacity Draw-off connection Fire service inlet Access to tank 		14	•
5	Overhead Tank capacity Exit Signage.	2500 lts	2500 lbs	MR
6	Provision of Lifts.			- Company of the Company
	Pressurization of Lift Shaft			1

	 Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	4/4
!7	Standby power supply	
18	Refuge Area.	
	Total AreaLocation	
19	Fire Control Room	
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 	
20	Special Fire Protection Systems for Protection of special Risks, if any:	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/2011/1654 dated 20/07/2011 Renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation

400 (BN)

407/Defo (2)