## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/285/ms/2014/w2/906

Dated: 22/07/2014

## FIRE SAFETY CERTIFICATE

Certified that the M/S Asian Paints Ltd. at Khasra No. 111/6 & 111/15, Phirni Road, Mundka, New Delhi-110041 comprised of Ground Floor only owned / occupied by M/S Asian Paints Ltd. was earlier issued Fire Safety Certificate Vide Letter No.F6/DFS/MS/2011/1194 Dated 13.06.2011. The premises was re-inspected by the officer concerned of Fire Service on 05.07.2014 in the presence of Sh. Ravinder Kumar (Comm. Officer) and observed that Fire prevention and fire safety arrangements provided in the premises, found in good working condition. The premises have therefore, deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the building / premises is fit for occupancy class Storage (Group-H) with effect from 22 / 97 / /2014 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

### **Conditions for the validity of Fire Safety Certificate:**

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on <a href="https://www.dfs.Delhigovt.nic.in"><u>WWW.dfs.Delhigovt.nic.in</u></a>

Issued on 22/07/14 at New Delhi by.

(SANTOKH SINGH), CHIEF FIRE OFFICER.

Phone:-23414250

#### Copy to :-

- 1. Sh. Dipanjan Nath, Asian Paints Ltd., Khasra No. 111/6 & 111/15, Phirni Road, Mundka, New Delhi-110041.
- 2. Administrative Officer, N.D.M.C., Narela Zone, Narela, Delhi-110040.

# **INSPECTION REPORT**

1. Name & address of the building: Asian Paints, Khasra No. 111/6, 111/15,

Phirni Road, Mundka, New Delhi-41.

2. Type of Occupancy

: Storage (Group 'H')

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F6/DFS/MS/2011/1194 dated 13/6/2011

5. Fire Safety directives Letter No.: NBC (Part-IV)

6. Date of inspection

: 05/07/2014

7. Name of the Inspecting Officer: Ashok Kumar Jaiswal (A.D.O. Jwala Puri)

8. Name and designation of Officer

from the building side : Ravinder Kuamr (Comm. Officer)

9. Year of Construction

: 2011

10. Applicant's letter No.: Nil dated 20/06/2014

S No	Minimum standards on fire	DOE / NBC-IV	Provided at	Remarks	
	prevention and fire safety U/R 33	Requirements	site	MR/NMR	
1.	Access of building				
	<ul> <li>Road width</li> </ul>	6 Mtr.	12 Mtr	MR	
6	<ul> <li>Gate width</li> </ul>	5 Mtr.	5 Mtr.	MR	
_	<ul> <li>Width of internal road</li> </ul>		3 Mtr.	MR	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases				
	<ul> <li>Upper floors</li> </ul>	NR	NR	NR	
	<ul> <li>Basements</li> </ul>	NR	NR	NR	
8 9	Width of staircases			25 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	
1	<ul> <li>Upper floors</li> </ul>	NR	NR	NR	
	<ul> <li>Basements</li> </ul>	NR	NR	NR	
	Protection of exits				
	• Fire check door	NR	NR	NR	
	<ul> <li>Pressurization</li> </ul>	NR	NR	NR	
	b. No of continuous	NA	NA	NA	
	staircase to terrace			INA.	
	c. Width Of Corridor	NA	NA	NA	
_	d. Door Size	Old Case	Old Case -	Old Case	
3.	Compartmentation	1	•		
	<ul> <li>Fire check door</li> </ul>	NR	NR	NR	
	<ul> <li>Sealing of electrical shafts</li> </ul>	NR	NR	NR	
	<ul> <li>Fire Rating of shaft door</li> </ul>	NR	NR	NR	
	Water Curtain	NR	NR	NR	
	<ul> <li>Fire Dampers</li> </ul>	NR	NR	NR	
4.	Smoke managements System			1417	
	Basements	No Basement	NA	NA	

6. Date of inspection

: 05/07/2014

7. Name of the Inspecting Officer: Ashok Kumar Jaiswal (A.D.O. Jwala Puri)

8. Name and designation of Officer

from the building side : Ravinder Kuamr (Comm. Officer)

9. Year of Construction

: 2011

10. Applicant's letter No.: Nil dated 20/06/2014

S No	Minimum standards on fir prevention and fire safety U/R 33	DOE / NBC-I' Requirements	V Provided at site	Remarks MR/NMR		
1.	Access of building					
	Road width	6 Mtr.				
	Gate width	5 Mtr.	12 Mtr	MR		
	Width of internal ro		5 Mtr. 🥏	MR		
2.	Number width Type & A.	pad 3 Mtr.	3 Mtr.	MR		
	Number, width, Type & Arrangements of exits  a. Number of staircases					
	Upper floors	NR				
	Basements		NR	NR		
İ	Width of staircases	NR	NR	NR		
Ī	• Upper floors	ND				
	Basements	NR	NR	NR		
-	Protection of exits	NR	NR	NR		
+						
-	• Fire check door	NR	NR	NR		
-	• Pressurization	NR	NR	NR		
	b. No of continuous	NA	NA	NA		
-	staircase to terrace			TVA		
-	c. Width Of Corridor	NA	NA	NA		
. (	d. Door Size	Old Case	Old Case	Old Case		
-	Compartmentation  Fire check door			old case		
100	THE CHECK GOOF	NR	NR	NR		
	<ul> <li>Sealing of electrical shafts</li> </ul>	NR	NR	NR		
	<ul> <li>Fire Rating of shaft door</li> </ul>	NR	NR	NR		
	<ul> <li>Water Curtain</li> </ul>	NR	ND			
	<ul> <li>Fire Dampers</li> </ul>	NR	NR	NR		
S	moke managements System		NR	NR		
	• Basements	No Basement	NA	NA		
	• Upper floors / GF	Exhaust Fan	Provided	MR		
Fi	re Extinguishers					
	• Total numbers	12	25	MR		
	• Types	ABC /Co <sub>2</sub> /Foam	Provided	MR		
	IS marking	ISI Marked	Provided	MR		

NIIZ

6.	First – Aid Hose Reels			3
	Total numbers on each floor	3	10	MR
	Length of hose reel     hose	30 Mtr.	30 Mtr.	MR
	Nozzle diameter	5 mm	5 mm	MR
7.	Automatic fire detection and a	alarming system		
	Type of detector	Smoke / Beam	Beam /	MR
	Location of Main Panel	GF	Provided	MR
	• Location of Repeater Panel	GF	Provided /	MR
	Alternate source of power	Required	Provided	MR
	Hooters' Location	GF	Provided	MR
8.	MOEFA	NR	NR	NR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	Basements	NA	NA	NA
	• Upper Floor / GF	Required	Provided	MR
	Sprinkler above false ceiling	NR	NP	NR
11.	Internal Hydrants	0		
	Size of riser/down-comer	150 mm	Provided	MR
	Number of hydrants per floor	5	Provided	MR
	Hose Box	5	Provided	MR
12.	Yard Hydrants			
	Total number of hydrants	5	10	MR
	Hose Box	5	10	MR
13.	Pumping Arrangements			1
. •	Ground Level			×
	Discharge of main pump	2280 LPM	2280 LPM /	MR
)	<ul><li>Head of main pump</li></ul>	65 MH	65 MH	MR
	<ul><li>Number of main pumps</li></ul>	2	2	MR
	Jockey pump out put	220 LPM	220 LPM	MR
	Jockey pump head	65 MH	65 MH	MR
	Standby Pump out put	2280 LPM	2280 LPM	MR
	Standby Pump Head	65 MH	65 MH	MR
)	Auto Staring/Manual	Required	Provided 6	MR
-	stopping			
	Pump House Access	Required	Provided 🕜	MR
	Terrace level	5	1	
-	Discharge of pump	NR	NR	NR
,	Head of the pump	NR	NR	NR

	Location of Main	GF	Provided	MR			
	Panel	20 cd <sub>3</sub> cm	(	8			
	Location of Repeater Panel	GF	Provided /	MR			
	Alternate source of power	Required	Provided /	MR			
	Hooters' Location	GF	Provided	MR			
8.	MOEFA	NR	NR	NR			
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System		1				
10	Basements	NA	NA	NA			
	Upper Floor / GF	Required	Provided	MR			
	Sprinkler above false ceiling	NR	NP	NR ,			
11.	Internal Hydrants						
	Size of riser/down- comer	150 mm	Provided	MR			
	Number of hydrants per floor	5	Provided	MR			
	Hose Box	5	Provided	MR			
12.	Yard Hydrants						
	Total number of hydrants	5	10	MR			
	Hose Box	5	10	MR			
13.	Pumping Arrangements						
	Ground Level			, ,			
	<ul> <li>Discharge of main pump</li> </ul>	2280 LPM	2280 LPM /	MR			
	Head of main pump	65 MH	65 MH	MR			
	Number of main pumps	2	2	MR			
	> Jockey pump out put	220 LPM	220 LPM /	MR			
	Jockey pump head	65 MH	65 MH	MR			
	<ul><li>Standby Pump out put</li><li>Standby Pump Head</li></ul>	2280 LPM 65 MH	2280 LPM 65 MH	MR			
	<ul><li>Standby Pump Head</li><li>Auto Staring/Manual</li></ul>	Required	Provided 6	MR			
	stopping stopping	Required	Tiovided	IVIIX			
	<ul><li>Pump House Access</li></ul>	Required	Provided <i>C</i>	MR			
	Terrace level						
	<ul><li>Discharge of pump</li></ul>	NR	NR	NR			
	> Head of the pump	NR	NR	NR			
	> Power supply	NR	NR	NR			
	> Auto starting of pump	NR	NR	NR			
14.	<ul><li>Captive water Storage for fire</li><li>Under Ground tank</li></ul>	50,000 Ltr.	50,000 Ltr. 🗸	MR			
	capacity						
	> Draw of connection	NR	NP	NR			
	Fire service inlet	NR	Provided <	NR			
	Access to tank	Required	Provided r	MR			
	<ul> <li>Overhead Tank capacity</li> </ul>	10,000Ltr.	Provided	MR			
				1			

		N113		
15	Exit Signage	Required	Provided	MR
16.	Provision of Lifts	•	Tovided	IVIN
	Pressurization of Lift Shaft	NR	NR	NR
	Pressurization of lift lobby	NR	NR	NR
	Communication in lift Car	NR	NR	NR
	Fireman's Grounding Switch	NR	NR	NR
	➤ Lift Signage	NR	NR	NR
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area		···oviaca	IVIIX
	Total area	NR	NR	NR
	Location	NR	NR	NR
19.	Fire control room			1417
	Detector system panel	NR	NR	NR
	Flow Switch Panel	NR	NR	NR
	PA System Panel	NR	NR	NR
	Batter backup	NR	NR	NR
	Building Floor Plans	NR	NR	NR
20.	Special Fire Protection	NR	NR	
	Systems for Protection of		1417	NR
	special Risks, if any;		15	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2011/1194 dated 13/06/2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal Designation : A.D.O. (Jwala Puri)

D.O./(Co) /17

18-7-14.