GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ MDZ/930

Dated: 24/07/19

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Singh Sons** located at 7A/10-11, WEA, Karol Bagh, New Delhi-110005 is comprised of Basement, ground floor plus three upper floors, using basement as storage, ground floor as reception, office & 03 guest rooms, first, second & third floor each having 12 guest rooms respectively (Total 39 guest rooms) and a pantry with staff room on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011/2140 dated 02.09.2011 owned/occupied by Sh. Amarjeet Singh. The guest house building was re- inspected by the officer concerned of this department on 16.07.2014 in the presence of Sh. Jaiveer (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for 39 guest rooms occupancy Group 'A' residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

ofc (W)

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No. 24338/Joint C.P./Lic.(H), Dated 07.07.2014)
- 2. Sh. Amarjeet Singh (Owner), Hotel Singh Sons, 7A/10-11, WEA, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT Hotel Singh Sons, 7A/10-11, WEA, Karol Bagh, N.D-05. 1. Name & address of the building: Residential (Guest House) 2. Type of Occupancy Renewal 3. Type of Case F.6/DFS/MS/GH/2011/2140 dated 02.09.2011 4. Details of Previous NOC 5. Fire Safety directives letter No N/A 16.07.2014 6. Date of inspection Dv. C.F.O Rajesh Panwar 7. Name of Inspecting Officer 8. Name and designation of officers Sh. Jaiveer (Manager) From the building side 9. Year of Construction 2004-2005 24338/Joint. C.P/Lic (H) dated 07.07.2014 10. Applicant's letter No. Provided at site Remarks NBC/BBL S. No. Minimum Standards on fire prevention special area MR/NMR Requirement and fire safety U/R 33 Access to building 1. M/R Accessible 06 mtr Road width Gate width Width of internal road Number, Width, Type & Arrangement of Exits 2. a. Number of staircases M/R, Old Case **Upper Floors** One One M/R, Basements Two Two b. Width of staircases Upper Floor 125 cms M/R, Old Case 125 cms Basements 125 cms 125 cms, 90 cms M/R, Old Case c. Protection of exits N/A N/A N/A Fire check door Pressurization N/A N/A N/A No. of continuous staircases to terrace One M/R One Width of Corridor 135cm, 255 cm Door Size N/A 80cm X 204 cm N/A 3. Compartmentation N/A N/A N/A Fire check door Sealing of electrical shafts Sealed Fire Rating of shaft door N/A N/A N/A Water Curtain N/A N/A N/A Fire Dampers N/A N/A N/A Smoke Management System 4. Exhaust Fans are M/R 30 a/c per hour Basements provided Natural M/R 12 a/c per hour Upper floors Ventilation Fire Extinguishers 5. M/R Two at each floor Provided Total numbers Water Co2, ABC Provided M/R Types ISI marked IS marking ISI marked M/R First-Aid Hose Reels 6. Provided M/R One Total numbers on each floor M/R Provided 30 m Length of hose reel hose 5 mm M/R Provided Nozzle diameter

7.	Automotic five detection and classics and			0	
1.	Automatic fire detection and alarming sy	N/A	NI/A	* I.V	MAAD
	Type of detectorsLocation of Main Panel	N/A N/A	N/A	NA	
	Location of Main Panel Location of Repeater Panel	N/A	N/A		N/A
	Alternate source of power		N/A		N/A
		Required	D.G set of 125 KVA		M/R
	Hooters' Location	N/A	N/A		N/A
8.	MOEFA	Required	Provided	6	M/R
9.	Public Address System	Required	Provided		M/R
10.	Automatic Sprinkler System				
	Basement	Required	Provided		M/R
	Ground Floor Ground Floor	N/A	N/A		N/A
11.	Sprinkler above false ceiling Internal Hadronian	N/A	N/A		N/A
11.	Internal Hydrants	NI/A	NI/A	1	NI/A
	Size of riser/down-comer Number of hydrants per floor	N/A N/A	N/A N/A		N/A N/A
	Number of hydrants per floorHose Box	N/A N/A	N/A N/A		N/A N/A
12.	Yard Hydrants	IN/A	IN/A		IN/A
12.		NI/A	NT/A		NI/A
	Total number of hydrants Hara Poy	N/A	N/A		N/A
13.	Hose Box Pumping Arrangements	N/A	N/A		N/A
13.	Pumping Arrangements				
	 Ground Level Discharge of main Pump 	DT/A	DT/A		NI/A
	Discharge of main PumpHead of Main pump	N/A	N/A		N/A
	Number of main pumps	N/A	N/A		N/A
	> Jockey Pump out put	N/A	N/A		N/A
	> Jockey pump head	N/A	N/A		N/A
	> Standby Pump out put	N/A	N/A		N/A
	Standby Pump Head	N/A	N/A		N/A
	Auto Starting/Manual	N/A	N/A	1	N/A
	Stopping	N/A	N/A		N/A
	Pump House Access	N/A	N/A		N/A
	Terrace level			4, 4	
	Discharge of pump	900 LPM	450 LPM		, Old Case
	Head of the pump	30 M	30 M	M/R	, Old Case
	Power Supply	Required	Provided		M/R
	Auto Starting of pump	N/A	N/A		N/A
14.	Captive Water Storage for fire fighting				
	 Underground tank capacity 	N/A	N/A		N/A
	> Draw-off connection	N/A	N/A		N/A
	> Fire service inlet	N/A	N/A		M/R
	Access to tank	N/A	N/A		N/A
	Overhead Tank capacity	15000 ltr	5000 ltr	M/R	Old Case
		Required	Provided		M/R
15.	Exit Signage.				
16.	Provision of Lifts.				
	 Pressurization of Lift Shaft 	N/A	N/A		N/A
	 Pressurization of Lift lobby 	N/A	N/A		N/A
	Communication In lift Car	Required	Provided		M/R
	Fireman's Grounding Switch	Required	Provided		M/R
	Lift Signage	Required	Provided		M/R

17.	Standby power supply	Required	Provided	M/R
18.	Refuge Area.			
	Total AreaLocation	N/A	N/A	N/A
		N/A	N/A	N/A
19.	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch PanelPA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	Required	Provided	M/R
		N/A	N/A	N/A
20.	Special Fire Protection System for	N/A	N/A	N/A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2011/2140 dated 02.09.2011 renewal under rule 35 of Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Offi

Signature of Inspecting Officer

Name: Rajesh Panwar

Name

Designation: - Dy. C.F.O (NDZ)

Designation