GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. F6/08/08/9/4/2014/M02/93/

Dated: 25/07/14

FIRE SAFETY CERTIFICATE

Certified that the M/S New Royal Guest House,1643, S.P.Mukherji Marg, Delhi-6, comprised of Ground floor reception only(Rest commercial use others properties), 1st floor (25 Rooms + pantry), 2rd floor (22 Rooms), 3rd floor (21 Rooms) and 4th floor (24 Rooms), was granted NOC by this department vide letter No. F6/DFS/MS/GH/2011/2481 dated 10-10-11. The premises was re-inspected by the officer concerned of this department on 19-07-2014 in the presence of Sh. Balvinder Uppal (owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential (Guest House) first floor to fourth floor, total 92 guest rooms in all with effect from (22 J...2014 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued .25/97./19. at New Delhi by.

(Dr.G.C.Misra) Chief Fire Officer T.No.011-23414333

> ofc 4

Copy to: -.

- The Joint. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 25041/Joint. C.P./Lic.(H) dated11.07.14.
- 2. M/S New Royal Guest House,1643, S.P.Mukherji Marg, Delhi-6.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire
 equipments and method of smooth and speedy safe evacuation of occupants in case of
 emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate on form J, six month prior to its expiry.

H136

INSPECTION REPORT

1. Name & address of the building : M/S New Royal Guest House,1643, S.P.Mukherji Marg, Delhi-6.

2. Building is comprised of : G+4, Ground floor reception only and rest commercial others property,

(Guest House at 1st floor to 4th floor, Total 92 rooms). (Old Case)

3. Type of Occupancy : Lodging House

4. Type of Case : Old Case

5. Details of Previous NOC : No.F.6/DFS/MS/GH/2011/2481, dated-10.10.2011

6. Fire Safety direction letter No :Nil.

7. Date of Inspection : 19.07.2014

8. Name of the Inspecting Officers: : Vedpal (ADO)

9. Name and designation of officer

from the building side : Sh. Balvinder Uppal (Owner)

10. Year of Construction :1941.

11. Applicant's letter No. : No.25041/Joint.C.P./Lic.(H) dated 11.07.14.

11. Ap	plicant's letter No. : No.23	041/Joint.C.P./Lic.(n) ua	led 11.07.14.			
S.N	Minimum Standards on fire	Old NOC	Provided at	Remarks		
	prevention and fire safety U/R33	Requirements	Site	(P.S.S. Area)		
1	Access to building					
	Road width	N.A.	12 m	MR		
	Gate width	N.A.	N.A.	N.A.		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement of Exits.					
	a. Number of Staircases			8		
	Upper Floor	01no.	01no.	MR		
	Basement	N.A.	N.A.	N.A.		
	B. Width of Staircases					
	Upper Floor	150cm.	150cms	MR		
	Basement	N.A.	N.A.	N.A.		
	c. Protection of exits	N.A.	N.A.	N.A.		
	Fire check door	N.A.	N.A.	N.A.		
	Pressurization	N.A.	N.A.	N.A.		
	e. No. of continuous staircases	1no.	1no.	MR		
	to terrace.					
	g. Width of Corridor	N.A.	N.A.	N.A.		
	h. Door Size	N.A.	N.A.	N.A.		
3	Compartmentation					
	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	30a/c per hour	N.A.	N.A.		
	Upper floor	12 a/c per hour	N.A.	N.A.		

h

j.	Fire Extinguisher Total numbers	T 00 -	140			
		08 nos.	16 nos.	MR		
	types IS marking	CO ₂ & ABC	CO ₂ & ABC	MR		
G		ISI marked	ISI marked	MR		
6	First-aid-Hose Reels.					
	Total numbers of each floor	01no.	01no.	MR		
	Length of hose reel hose	30 m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	N.A.	N.A.		
	Location of main panel	N.A.	N.A.	NA.		
	Location of repeater panel	N.A.	N.A.	N.A.		
	Alternate source of power	N.A.	N.A.	NA.		
	Hooters	N.A.	N.A.	N.A.		
8	MOEFA	Required	Provided	MR.		
9	Public address System.	Required	Provided	MR		
10	Automatic Sprinkler System.	required	riovided	IVIT		
	Basement	N.A.	N.A.	N.A.		
	upper floor	N.A.	N.A.			
	sprinkler above false ceiling	N.A.		N.A.		
11	Internal Hydrants	IV.A.	N.A.	N.A.		
1 1	size of riser/down-comer	N.A.	N. A			
	Number of hydrants per floor		N.A.	N.A.		
	Hose Box	N.A.	N.A.	N.A.		
10		N.A.	N.A.	N.A.		
12	Yard Hydrants.			1.		
	Total number of hydrants	N.A.	N.A.	N.A.		
10	Hose Box	N.A.	N.A.	N.A.		
13	Pumping Arrangements.					
	Ground Level	N.A.	N.A.	N.A.		
	Discharge of main Pump	N.A.	N.A.	N.A.		
	Head of Main Pump	N.A.	N.A.	N.A.		
	Number of main pumps	N.A.	N.A.	N.A.		
	Jockey pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	Standby pump out putStandby pump Head	N.A.	N.A.	N.A.		
	,	N.A.	N.A.	N.A.		
	Auto Starting /Manual stoppingPump House Access	N.A.	N.A.	N.A.		
	Terrace Level	N.A.	N.A.	N.A.		
	Discharge of pump	Required	Provided	MR		
		225 LPM	450LPM	MR		
	Head of the PumpPower supply	40 Mtrs.	40Mtrs.	MR		
	Auto Starting of pump	Required	Provided	MR		
	Auto Starting of pump	N.A.	N.A.	N.A.		

Jul 1

M/S New Royal Guest House, 1643, S.P. Mukherji Marg, Delhi-6

14	- Pure viale Storage for Fire Fin	nting.		
	Underground tank capacity Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A.
	Overhead Tank capacity	N.A.	N.A.	N.A.
15	Exit Signage.	2500Ltrs.	5000Ltrs.	MR
16	Provision of Lifts.	Required	Provided	MR
-	Pressurization of Lift Shaft	N.A.	Provided	MR
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication in lift car	N.A.	N.A.	N.A.
	Firemen's grounding switch	N.A.	N.A.	N.A.
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area.	Required	D.G. Set	MR
-	Total area			
	Location	N.A.	N.A.	N.A.
9	Fire Control Room	N.A.	N.A.	N.A.
and the same of th	Detector system panel			man harman and a second a second and a second a second and a second a second and a second and a second and a
	Flow switch panel	N.A.	N.A.	N.A.
	PA system panel	N.A.	N.A.	N.A.
	Batter backup	N.A.	N.A.	N.A.
	Building Floor Plans	N.A.	N.A.	N.A.
)	Special Fire Protection	N.A.	N.A.	N.A.
1	Special Fire Protection systems for of special Risks, if any:	N.A.	N.A.	N.A.

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the NOC issued vide letter No.F.6/DFS/MS/GH/2011/2481 dated 10.10.11 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Signature of the Inspecting Officer

Name: Vedpal Designation: ADO