GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:- 011-23412593

E-mail ID: cfohq.dlfire@nic.in

No F 6 / DFS / MS / Hotel / 2014 / M92 | 80

Dated 05 08 114

FIRE SAFETY CERTIFICATE

Certified that The Lalit Hotel located at Barakhamba Avenue, Connaught Place, New Delhi.comprised of lower basement, upper basement, ground + 21 upper floor was granted NOC by this department vide letter No. F6/DFS/MS/2011/2021 dated 19/08/11. The premises was re-inspected by the officer concerned of this department on 14/07/14 in the presence of Mr.Kanan (Chief Engineer) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Sub division A-6 Starred Hotel of Group 'A' Residential Building with effect from The 12-14- for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued onat New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph-011-23414333

of c ML

Copy to:-

- 1. Sh. Vivek Shukla, General Manager, The Lalit Hotel Barakhamba Avenue, Connaught Place, New Delhi.
- 2. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi -110049.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT

The Lalit Hotel Barakhamba Avenue, 1. Name & address of the building:-

Connaught Place, New Delhi.

Sub Division A-6 Starred Hotel of Group 'A' 2. Type of occupancy:-

Residential Building

3. Type of case:-

4. Details of previous NOC:-

No. F6/DFS/MS/2011/2021 dated

19/08/11.

Renewal

5. Fire safety directives No.-

6. Date of inspection:-

7. Name of the inspecting officer:-

N/A 14/07/14

Dy. C.F.O. Rajesh Panwar & A.D.O. Manoj Kumar Sharma

8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Kanan (Chief Engineer)

Old.

23686/Joint C.P./Lic. (H) Dated 01/07/14 Lower basement, upper basement, ground +

Old Case

21 upper floor

				Old Case	
S.No.	Minimum Standards on fire	Required	Provided at site	Remarks	
_ 11 , _ 1	Prevention and fire safety			MR/NMR	
	U/R 33				
1.	Access to Building			1 m	
	1) Road width	15 mtr.	15 mtr.	MR	
	2) Gate width	5 mtr.	6 mtr.	MR	
	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrangement of Exits				
4.	A. Number of staircases				
	1. Upper floors	3 Nos.	3 Nos.	MR	
	2. Basements	5 Nos.	5 Nos.	5 Nos.	
	B. Width of staircase		* 1	1 m	
	1. Upper floors	1.10 mtr.	1.10 mtr. each.	MR	
		each.) (D	
	2. Basements	1.10 mtr.	1.10 mtr. each.	MR	
		each.			
	C. Protection of exits		D 11.1	MR	
	1. Fire check door	Required	Provided	MR	
	2. Pressurization	Required	Provided	MR	
	D. No. of continuous	1 Nos.	1 Nos.	IVIIX	
	staircase to terrace	27/4	N/A	N/A	
	E. Width of corridor	N/A	1 mtr. X 2	MR	
	F. Door size	1 mtr. X 2	1 IIIII. A 2	IVIIC	
3.	Compartmentation	T - 1	Provided	MR	
	1) Fire check door	Required	Provided	MR	
	2) Sealing of electrical shafts	Required	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A N/A	N/A	
	4) Water curtain	N/A	Provided	MR	
	5) Fire Dampers	Required	Provided	IVIIC	
4.	Smoke Management System	<u>n</u>			



				A COL
	1) Basements	30 a/c per	Mechanical	MR
		hour	30 ACPH	
	2) Upper floors	12 a/c per hour	Provided	MR
5.	Fire Extinguishers			
	1) Total numbers	182 Nos.	200 Nos.	MR
	2) Types	ABC & CO2	ABC & CO2	MR
	3) ISI marking	ISI	Yes	MR
6.	First-Aid Hose Reel			
	1) Total number of eachfloor	3 Nos.	3 at each floor	MR
	2) Length of hose reel hose	30 m	30 m	MR
	3) Nozzle diameter	5 mm	5 mm	MR
7.	Automatic Fire Detection &	Alarming Syst	em	
	1) Type of detectors	Required	Provided	MR
	2) Location of main panel	Ground floor	Ground floor	MR
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	Required	Provided	MR
	5) Hooter's Location	Every floor	Every floor	MR
8.	MOEFA	Required	Provided	MR
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System			
	1) Basement	Required	Provided	MR
	2) Upper floors	Required	Provided	MR
	3) Sprinkler above false	Required	Provided	MR
	ceiling	1		
11.	Internal Hydrants			
	1) Size of riser/down-comer	150 mm.	150 mm.	MR
	2) Number of hydrants per	3 Nos.	3 Nos.	MR
	floor			
	3) Hose box at each floor	3 Nos.	3 Nos.	MR
12.	Yard Hydrants			
	1) Total number of hydrants	10 Nos.	10 Nos.	MR
	2) Hose box	10 Nos.	10 Nos.	MR
13.	Pumping Arrangement			
	1) Ground level			n .
	a) Discharge of main	2800 LPM	2800 LPM	MR
	pump	22.114		
	b) Head of main pump	80 mtr.	80 mtr.	MR
	c) Number of main	2 Nos.	2 Nos.	MR
	pump		21105.	1
	d) Jockey pump out put	180 LPM	450 LPM	MR
	e) Jockey pump head	80 mtr.	80 mtr.	MR
	f) Stand by pump	2800 LPM	2800 LPM	MR
	output		2000 121 111	
	g) Stand by pump head	80 mtr.	80 mtr.	MR
	h) Auto starting/Manual	Required	Provided Provided	MR
	stopping	required	TTOVIGCU	IVII
	2) Terrace level			
	a) Discharge of pump	N/A	N/A	N/A
	b) Head of pump	N/A	N/A	N/A N/A
	c) Power supply	N/A	N/A	N/A N/A
			N/A	
	d) Auto starting of	N/A		
	d) Auto starting of pump	N/A	IN/A	N/A

war

Special Fire Protection System	for Protection of	of special Risk if	MR
Special Fire Protection System for Protection of special Risk, if			
e) Building floor plan	Required	Provided	MR
a) Battery backup	Kequired	Provided	MR
			MR
			MR
,			MR
The state of the s			N/A
		N/A	N/A
			N/A
	*		MR
	1	THE STREET A PROPERTY OF THE STREET	MR
		Provided	MR
car	Required	Provided	MR
lobby	Required	Provided	MR
shaft	Required	Provided	MR
CONT OF THE PROPERTY OF THE PR			
Exit Signage.	Required	Provided	MR
d) Over head tank capacity	20,000 ltrs.	50,000 ltrs.	MR
			MR
		Service and Company of the Company	MR
The state of the s			MR
capacity		×	MR
	a) Draw-off connection b) Fire service inlet c) Access to tank d) Over head tank capacity Exit Signage. Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage Stand by Power Supply Refuge Area Total area location Fire Control Room a) Detector system panel b) Flow switch panel c) PA system panel d) Battery backup	capacity a) Draw-off connection b) Fire service inlet c) Access to tank d) Over head tank capacity Exit Signage. Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage Required Stand by Power Supply Refuge Area Total area location N/A Fire Control Room a) Detector system panel b) Flow switch panel c) PA system panel c) PA system panel c) Required	capacity a) Draw-off connection b) Fire service inlet c) Access to tank d) Over head tank capacity Exit Signage. Provided Provided Provided Provided Provided Provided Provided Provided Exit Signage. Pressurization of lift shaft Pressurization of lift lobby C) Communication in lift car d) Fireman's switch e) Lift signage Required Provided Required Provided Refuge Area N/A N/A N/A N/A Pire Control Room N/A N/A Provided Provided Provided Provided Provided Provided Provided Provided Refuge Area N/A N/A Presurred Provided Refuge Area N/A Required Provided Provided

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rule it is recommended to grant fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / for FSC is recommended please.

Rajesh Panwar Dy. C.F.O. (NDZ)

Manoj Sharma Assistant Divisional Officer