## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/52 ) 1014

Dated: 12/08/14

## FIRE SAFETY CERTIFICATE

Certified that the Hotel Pals Inn located at 29/6, East Patel Nagar, New Delhi-110008 is comprised of Basement, ground floor plus three upper floors (Half of third floor i.e 03 rooms being used as personal use by the owner), the basement used as hall/storage, ground floor as reception, lobby, office & 02 guest rooms, first & second floor each having 07 guest rooms respectively, half of third floor having 03 guest rooms with pantry (Total 19 guest rooms) was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2012/61 dated 06.01.2012 for 16 guest rooms owned/occupied by Smt. Pritam Kaur. The guest house building was re-inspected by the officers concerned of this department on 18.07.2014 in the presence of Sh. Kuldeep Lagwal (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential (addition of 03 guest rooms at third floor, Total= 16+03 = 19 rooms) w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 12 / 58 / 14 at New Delhi.

(SANTOKH SINGH)
Chief Fire Officer
Ph: 011-23414250

Copy to:-

- 1. The Addl. Commissioner of Police (Lic.)

  1<sup>st</sup> floor, P.S., Defence Colony, New Delhi.

  (Re. No. 21632-633/Addl. C.P./Lic.(H), Dated 05.06.2014)
- 2. Smt. Pritam Kaur (Owner), Hotel Pals Inn, 29/6, East Patel Nagar, N.D-08.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	INSPE	CTION REPORT					
	<ol> <li>Name &amp; address of the building</li> </ol>	Hotel Pala Two	2916 Fact	Padal Maria			
	2. Type of Occupancy	: Hotel Pals Inn, 29/6, East Patel Nagar, N.D.  Residential (Guest House)  : New Case/Renewal					
	The or case						
	4. Details of Previous NOC	Letter No. F.6/DFS/MS/GH/2012/61 Date 06.01.2012					
		18:07.2014					
	6. Date of inspection						
	7. Name of Inspecting Officer	A.O. C. K. Tanasa a o o o o o o					
	8. Name and designation of officer			U			
	From the building side  9. Year of Construction  Sh. Kuldeeb Lagwal (Manc						
	9. Year of Construction	- Delore 20	0	U			
S.	10. Applicant's letter No.	21632-633 Add	1. C.P. /LIC. (H)	dated 05.06.201			
No.	i dana di ili e	NBC/BBL	Provided at	Remarks			
1.	prevention and fire safety U/R 33	Requirement	site	MR/NMR			
1.	Access to building						
	Road width	Accessible	12 mtr	MR			
	Gate width	-	ISScmo	MR			
	<ul> <li>Width of internal road</li> </ul>						
2	Number, Width, Type & Arrangemen	t of Exits	*				
	a. Number of staircases						
	• Upper Floors	-	One	000 BILLO.			
	<ul> <li>Basements</li> </ul>	Two	Two	MR, Old Cose			
	b. Width of staircases		7000	IV/K			
	Upper Floor		96 cms	N-0 0:10			
	• Basements			MR, Old Case			
	c. Protection of éxits		178cms, 80cms	- do -			
	<ul> <li>Fire check door</li> </ul>						
	• pressurization						
	d. No. of continuous staircases to						
	terrace		0.				
	e. Width of Corridor		One				
	f. Door Size		122 cms, 125 cms	and the state of t			
7			87 cms x 208 cms	-			
3.	Compartmentation			The state of the s			
	Fire check door			-			
	Sealing of electrical shafts	-					
	<ul> <li>Fire Rating of shaft door</li> </ul>		Sealed				
	Water Curtain						
	• Fire Dampers						
4.	Smoke Management System						
	* Basements	70 -/-	Exhaust fons	A STATE OF THE STA			
	Upper floors	30 a/c per	are Provided	MR			
		hour	Vatural Ventilatio				

Ī		12 a/c per				
ading and places and		hour	-	!		
	Fire Extinguishers					
	Total numbers	Two at each floor	Provided	5-0		
	<ul><li>Types</li></ul>	Co2, WCo2	- do -	MR		
	<ul><li>IS marking</li></ul>	ISI marked	1SI Marked	MR		
	First-Aid Hose Reels		13/ Markea	MR		
	<ul> <li>Total numbers on each floor</li> </ul>	One	Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	- do -	MR		
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	-do+	MR		
	Automatic fire detection and alarming	system				
	Type of detectors					
ì	<ul> <li>Location of Main Panel</li> </ul>	_				
	<ul> <li>Location of Repeater Panel</li> </ul>					
	<ul> <li>Alternate source of power</li> </ul>		D.G Sef of 75 KVA			
	<ul> <li>Hooters' Location</li> </ul>		7,3			
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	- do -	- do -	MR		
10.	Automätic Sprinkler System		ii I			
	• Basement	Required	Provided	MR		
	<ul> <li>Upper Floor</li> </ul>	· /-				
-	<ul> <li>Sprinkler above false ceiling</li> </ul>			1		
11.	Internal Hydrants					
	<ul> <li>Size of riser/down-comer</li> </ul>	-		-		
	<ul> <li>Number of hydrants per floor</li> </ul>	-		+		
	<ul> <li>Hose Box</li> </ul>			1		
12.	Yard Hydrants		J.			
	<ul> <li>Total number of hydrants</li> </ul>					
	<ul> <li>Hose Box</li> </ul>	Canada				
13.	Pumping Arrangements					
	<ul> <li>Ground Level</li> </ul>		*	7, 7, 1		
	Discharge of main Pump		_			
	Head of Main pump			<u> </u>		
	<ul><li>Number of main pumps</li><li>Jockey Pump out put</li></ul>					
	> Jockey pump out put > Jockey pump head		,			
	> Standby Pump out put		-	_		
	> Standby Pump Head			-		
	> Auto Starting/Manual			×		
	stopping			_		

## 29/06, East Patel Nagar, New Delli - 110008.

	> Pump House Access	V 20					
	Terrace level	4					
	➤ Discharge of pump						
	➤ Head of the pump		450 LPM	MR, Old Cas			
	> Power Supply			-do -			
	> Auto Starting of pump	Required	30 M Poovided	-do -			
14.	Captive Water Storage for fire fighting						
	Underground tank capacity		T				
	Draw-off connection						
	Fire service inlet						
	Access to tank			-			
	Overhead Tank capacity		_	_			
			Socoltr	MR, Old Cas			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.	ž.		4			
	<ul> <li>Pressurization of Lift Shaft</li> </ul>						
	<ul> <li>Pressurization of Lift lobby</li> </ul>						
	<ul> <li>Communication In lift Car</li> <li>Fireman's Grounding Switch</li> </ul>		0				
		_	Provided	MR			
	Lift Signage	Required	- do -	MR			
		-de -	-do -	MR			
17.	Standby power supply	Required -do - Required	Provided	MR			
18.	Refuge Area.						
	> Total Area	(* 1)		,			
	Location		1, 85,10				
19.	Fire Control Room						
	<ul> <li>Detector System Panel</li> </ul>						
	Flow Switch Panel			1			
	PA System Panel			ž.			
	Batter backup     Building Floor Plans	Required	Provided	MR			
	Building Floor Plans	- pur o cy	- Correct	1.17			
20.	Special Fire Protection System for						

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no.

F.6/DFS/MS/GH/2012/61 dated 06-01-2012 renewal under rule 35 of the

Delhi Fire Service rules 2010 is recommended.

Note: The Guest House building is comprised of Basement, Ground Floor plus three lepper floors.

The owner of the Guest House has been converted the staffrooms and stores in to six rooms at third floor. The basement used as storage, Ground Floor as reception, Lobby, Office & 02 Guest rooms, first & Second Floor each having 07 Guest rooms respectively, Half of the third Floor i.e 03 Guest rooms & remaining 03 rooms Being used as personal use with bantry. (Total 19 Guest rooms). This department has no objection for addition of 03 Guest rooms at half of third Floor and renewal of FSC please.

Signature of Inspecting Officer

Name S. K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation ABSH. Divisional Officer.