## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001

NO. F6/DFS/MS/School/2014/SZ/ 1040

DATED: 20/08/14

## FIRE SAFETY CERTIFICATE

Certified that Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi – 110043(Near Sector-16B,Dwarka) comprised of ground floor plus two upper floors owned/occupied by Green View Public School was granted NOC by this department for Ground plus one upper floor vide letter No.F6/DFS/MS/2006/1443 Dated. 03.07.2006. The management have deemed complied with the fire prevention and fire safety requirements in accordance circular No.F.16/Estate//CC/Fire Saftey/2011/3298 to 3398 dated 01.03.2011 issued by Directorate of Education, Govt. of NCT of Delhi and verified by the officer concerned of this department on 08.8.2014 in presence of Smt. Renu Dabas (Principal) and that the school building is fit for occupancy of class B, 'Educational Building' for ground plus two upper floors with effect from \(\frac{10}{20}\) of \(\frac{1}{2}\) for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40, and subject to conditions printed overleaf.

Issued on 20/08/19 at New Delhi by

(SANTOKH SINGH) Chief Fire Officer Ph: 011-23414250

Copy to:

1. The Dy. Director (Education), G.N.C.T. of Delhi, Old Secretariat, New Delhi-54.

2. The Principal, Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi – 110043.

ou On

## CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of the Licensing Department shall always be permitted and followed.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with a copy of the certificate, six months prior to its expiry.

		NSPECTION REPO	Constitution in Constitution i		
1	Name & address of the building	Green View Public School, Dwarka Vihar, Kakrola Road, Najafgarh, New Delhi-110043.( Near Sector-16B, Dwarka)			
2	Type of Occupancy	Educational Building "B"			
3	Type of case	Renewal			
4	Details of previous NOC	F6/MS/DFS/2006/1443 dated 03.07.2006			
	Fire safety directives letter No	Directorate of Education:F/16/Estate/CC/fire Safety/2011/3298-			
5		3398, Dated 1.3.2011			
6	Date of inspection	08.08.2014			
7	Name of the inspecting Officers :	ADO S.P. Bhardwaj			
8	Name and designation of officers from the building side	Mrs. Renu Dabas (Principal)			
9	Year of construction	2003			
3	Applicant's letter No.	GVPS/DFS/2014/217 dated Ground+1 upper floor			
10		28.7.2014			
		Management has constructed one more upper floor ( No G+2 upper floo			
S. NO.	Minimum Standards on fire prevention	NBC Requirement	Provide	d at site	Remarks
	and fire safety U/R 33				MR / NMR
1	Access to building				
	1) Road width	6 Mtrs.	9 Mtrs.		MR
	2) Gate width	Approachable For FE	4.80 Mtrs.& 3	3.20 Mtrs.	old case
	3) Width of internal road	N/A	N/A		N/A
2	Number, width Type & arrangement of	exits			
	a. Number of staircases				
	1. Upper floors	Old Case	3 Nos.		MR
	2. basements	N/A	N/A		N/A
	b. Width of staircase		IN/A		TW/A
	1. Upper floors	1.5 Mtrs.	3Nos. 1.5 Mt	rs.each	MR
	2. basements	N/A	N/A		N/A
	c. Protection of exits				
	1. Fire check door	N/A	N/A		N/A
	2. Pressurization	N/A	N/A		N/A
	d. No. of continuous staircase to		3 Nos.		MR
	terrace	and the same of th	2		The Attitudes 1900
	e. Width of corridor	1.25 Mtrs.	1.50 to 2.35		MR
	f. Door size	1 Mtr.	1.05 to 1.10 N	/ltrs	MR
3	Compartmentation.	. IVILI.	1.00 to 1.10 N		1011 (
-	1. Fire check door	N/A	N/A		N/A
	2. Sealing of electrical shafts	N/A	N/A		N/A
	3. Fire Rating of shaft door	N/A	N/A		N/A
	4. water curtain	N/A	N/A		N/A
	5. Fire dampers	N/A	N/A		N/A
4	Smoke Management system.	IN/A	II.N.W		IIA/M
4	basement basement		N/A		N/A
	DUSCHICHT.	4			13//
	upper floors	12 0/0 oboves	Natural Vent.		MD
5	upper floors Fire Extinguishers	12 a/c charge	I valuiai veiil.		MR
	total numbers	One No. One OF APO 16 Nos.			MR
		One No. Co2 OR ABC	Co2 & ABC		MR
	Types	for every 300 Sq.Mtrs.	ICOZ & ARC		IIVITS

6	First-Aid Hose Reels.				
	total numbers on each floor	Old case	3 Nos.each floor	MR )	
	Length of Hose reel hose	30 m	Provided	MR	
	Nozzle Diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming	system			
	Type of detectors	N/A	N/A	N/A	
	location of Main Panel	N/A	N/A	N/A	
	location of Repeater panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	hooter's location	N/A	N/A	N/A	
8	MOEFA	N/A	N/A	N/A	
9	Public Address System.	N/A	Provided	old case	
10	Automatic Sprinkler System.				
	basement	N/A	N/A	N/A	
	upper floors	N/A	N/A	N/A	
	sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants		1	1.47.	
	Size of riser/down-corner	N/A	N/A	N/A	
	Number of Hydrants per floor	N/A	N/A	N/A	
	hose Box	N/A	N/A	N/A	
12	Yard Hydrants.		TW/	14//	
	total number of hydrants	N/A	N/A	N/A	
	hose box	N/A	N/A	N/A	
13	Pumping arrangements	1077	IVA	114/7	
	1. Ground level				
	a. Discharge of main Pump	N/A	N/A	N/A	
	b.Head of main pump	N/A	N/A	N/A	
	c.Number of main pumps	N/A	N/A	N/A	
	d.jockey pump out put	N/A	N/A	N/A	
	e.jockey pump head	N/A	N/A	N/A	
	f. Standby Pump output	N/A	N/A	N/A	
	g.Stanby Pump head	N/A	N/A	N/A	
	h.Auto Starting/Manual stopping	N/A	N/A	N/A	
	pump house access	N/A	N/A	N/A	
	2.Terrace level	IN/A	IIV/A	IIV/A	
	a. Discharge of pump	450 Lpm.	450 LPM	MR	
	b. head of the pump	40 Mtrs.	40 Mtrs.	MR	
	c. Power supply	Required	Provided Provided	MR	
	d. Auto starting of pump	Required	Provided	MR	
	a. Auto starting or pullip	required	ILIONIAEA	INIT	
14	Captive water storage for fire fighting				
	Underground tank capacity	N/A	N/A	N/A	
	a. Draw-off connection	N/A	N/A	N/A	
	b. fire service inlet	N/A **	N/A	MR	
	c.Access to tank	N/A	N/A	N/A	
	Over head tank Capacity	10000 Lts.	10,000 Ltrs.	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of lifts.				
is .	a. Pressurization of lift shaft	N/A	N/A	N/A	
	b. pressurization of lift lobby	N/A	N/A	N/A	
	c. communication in lift car	N/A	N/A	N/A	
	d. Fireman's grounding switch	N/A	N/A	N/A	
	e. Lift signage	N/A	N/A	N/A	

. . /

17	Standby power supply	N/A	N/A	N/A
10	Refuge Area.	Not Required		
	total area			
	location			
19	Fire control room			
	a. detector system Panel	N/A	N/A	N/A
	b. Flow switch Panel	N/A	N/A	N/A
	c. PA system Panel	N/A	N/A	N/A
	d. Batter backup	N/A	N/A	N/A
	e. Building floor plans	N/A	N/A	N/A
20	Special Fire Protection systems	s for protection of spe	ecial risks, if any:	V/A

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, renewal of FSC issued vided letter no.F6/MS/DFS/2006/1443 for fround plus one upper floor is recommended for ground plus two upper floors under rules 35 of the Delhi Fire Service Rules 2010.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name

S.P. Bhardwaj

Designation

ADO (Dwarka)