GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ \$2 /1063

Dated: 22 / 08 / 14

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Star Palace** located at 15A/17, WEA, Karol Bagh, New Delhi-110005 is comprised of Basement, ground floor plus three upper floors, using basement as storage, ground floor as reception & shops, first & second floor each having 10 guest rooms respectively, third floor having 09 guest rooms (Total 29 guest rooms) and two staff room with pantry on terrace was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011-12/1928 dated 10.08.2011 owned/occupied by Sh. Paras Ram. The guest house building was reinspected by the officers concerned of this department on 20.08.2014 in the presence of Sh. J.S. Rawat (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 22 \ 8 \ 14 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph: 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.)
 1st floor, P.S., Defence Colony, New Delhi.
 (Re. No. 23243/Joint C.P./Lic.(H), Dated 18.06.2014)
- Sh. Paras Ram (Owner), Hotel Star Palace, 15A/17, WEA, Karol Bagh, New Delhi-110005.

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

•	INS	PECTIO	ON REPORT				
W	 Name & address of the buildi 	ing: H	otel Star Pa	lace ICALIA III	TO VOLIDA		
		: R	esidential (G	They House	ZH, KUYOI Bagh, N. D		
	3. Type of Case	: N	ew Case/Rene	wal			
	4. Details of Previous NOC	: Letter No E.C. A. Colonala					
	5. Fire Safety directives letter No	0 : _	-	- 10/1/2011-11	10,08.7		
	6. Date of inspection	:	20:08.2014 D.O S.K. Tomar & ADO P.S. Dahiya				
	7. Name of Inspecting Officer	: 1					
	8. Name and designation of office						
	From the building side	: _	Sh. G.S.1	Rawat CMana	oer)		
	9. Year of Construction	:	1990-	91			
 S.	10. Applicant's letter No.	: 2	3243/ Joint	C.P. ILIC. CH) de	ated 18.06.2014		
No.	Minimum Standards on fire		NBC/BBL	Provided at	Remarks		
1.	prevention and fire safety U/R 33		Requirement	site	MR/NMR		
1.	Access to building						
	• Road width		Accessible	Obmtr	MR		
	• Gate width		_	155cms, 200 cms	MR		
	 Width of internal road 		_				
2.	Number, Width, Type & Arrangem	nent of	Exits	N			
	a. Number of staircases						
	• Upper Floors		-	One	Do 0 0110		
	 Basements 			-do-	MR, Old Case		
	b. Width of staircases			- 000 -	-do-		
	Upper Floor			125 cms	No.0 0110		
	Basements		~		MR, Old Case		
	c. Protection of exits	}		125 cms	- do -		
	Fire check door	-					
	• pressurization						
	d. Not of continuous staircases to			2 26			
	terrace	-	-	0.			
	e. Width of Corridor	-	-	One			
2	f. Door Size	-		1 So cms			
				79 cms x 203 cms			
3.	Compartmentation						
	Fire check door			_			
	Sealing of electrical shafts						
	 Fire Rating of shaft door 	-		Sealed	-		
	Water Curtain						
	Fire Dampers	-					
١.	Smoke Management System	**					
	* Basements		30 2/2 25	Exhaust Fano			
	Upper floors		30 a/c per hour	are Provided	MR		
			nour	Matural Ventilati			

	N114-	Mr.	2	-
		12 a/c per hour	-	
5.	Fire Extinguishers	3		
		four at each floor	Provided	MR
	IS marking	Co ₂ , WCo ₂	-dor	MR
6.	First-Aid Hose Reels	131 marked	151 Marked	MR
No seemen at opinion have	Total numbers on each floorLength of hose reel hose	<u>One</u> 30 m	Provided - do-	MR
7.	Nozzle diameter	5 mm	- do:	MR
	Automatic fire detection and alarming			
Ì	 Type of detectors Location of Main Panel Location of Repeater Panel 	-		+
	 Alternate source of power Hooters' Location 	:	D.G. Set of 62.5 KVA	Mor
8.	MOEFA	Required	Provided	MR
9.	Public Address System	- do -	-do-	MR
10.	Automatic Sprinkler System			
The same and a self-same and a	BasementUpper Floor	Required	Provided	MR
	 Sprinkler above false ceiling 			
11.	Internal Hydrants			/
	Size of riser/down-comerNumber of hydrants per floor			
	 Hose Box 			
12.	Yard Hydrants		J.	
The state of the s	Total number of hydrantsHose Box			
13.	Pumping Arrangements			
	Ground LevelDischarge of main Pump		-	10.
	> Head of Main pump			
	Number of main pumpsJockey Pump out put			
	Jockey pump head			
	Standby Pump out putStandby Pump Head			
	➢ Standby Pump Head➢ Auto Starting/Manual		_:	_
	stopping			

	Dump House Assess	T						
*	Pump House AccessTerrace level							
	Discharge of pump	_	450 LPM	MR, Old Cas				
	Head of the pumpPower Supply		30 M Provided	-do-				
		Required	Provided	MR				
	> Auto Starting of pump							
14.	Captive Water Storage for fire fighting							
	 Underground tank capacity 		<u>—</u>					
	Draw-off connection	-	-	<u></u>				
	Fire service inlet	_	~					
	Access to tank		-	_				
	Overhead Tank capacity	-	5000 Ltr	MR, Old Ca.				
15.	Exit Signage.	Required	Provided	MR				
16.	Provision of Lifts.	7						
	Pressurization of Lift Shaft							
	 Pressurization of Lift lobby 	_		^				
	Communication In lift Car		Provided	N20				
	 * Fireman's Grounding Switch 	0 . 1		MR				
	Lift Signage	Keg. wired	-do-	MR				
		-do-	-do-	MR				
17.	Standby power supply	Required -do- Required	Provided	MR				
18.	Refuge Area.	,	* *	×				
	Total Area		-					
	Location			-				
19.	Fire Control Room							
	 Detector System Panel Flow Switch Panel PA System Panel Batter backup Building Floor Plans 							
			,	1				
			30 V					
		Parital	Provided	MR				
		Required	1 sovided					
			:					
20	6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		i .					
20.	Special Fire Protection System for Protection of special Risks, if any:	_	_	_ 3				

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2011-12/1928 dated 10.08.2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S. K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya
Designation Appth. Divisional Oppicer