GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110001

No. F6/DFS/ MS/ School/2014/MDZ/1060

Dated: 21/08/14

FIRE SAFETY CERTIFICATE

Certified that the Rajkiya Sarvoda /a Kanya Vidyalaya, Chander Nagar, Delhi-51, comprised of ground plus three upper floors owned/occupied by Rajkiya Sarvodaya Kanya Vidyalaya, have complied with the fire prevention and fire safety requirements in accordance with the circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01.03.11 issued by the Director of Education and verified by the officer concerned of this department on dated 02.08.14 in the presence Principal of the school and found that the building is fit for occupancy class B 'Educational Building' with effect from .21/.09/19....... for a period of three years, subject to conditions printed overleaf.

Issued on 21/08/// at New Delhi by

(Santokh Singh)
Chief Fire Officer
Ph-011-23414250

olc fr

To,

The Principal

Rajkiya Sarvodaya Kanya Vidyalaya, Chander Nagar, Delhi-51

Copy to:-.

 The Joint Director of Education (Land & Estate)

Directorate of Education, Lucknow Road, Delhi -54

2. The Principal

Rajkiya Sarvodaya Bal Vidyalaya, Chander Nagar, Delhi-51

CONDITIONS:

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule(1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 2. All the means of escape shall be kept free of all type of obstruction all the time.
- All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

: Rajkiya Sarvodaya Kanya Vidyalaya, Chander 1.Name & address of the building

Nagar, Delhi-51.

2. Building is comprised of

: G+3

3. Type of Occupancy

: Educational

4. Type of Case

: New Case

5. Details of Previous NOC

: Nil

6. Fire Safety direction letter No

: F.16/Estate/CC/Fire safety/2011/3298 to 3398

dated 01.03.11

7. Date of Inspection

: 02.08.14

8. Name of the Inspecting Officers:

: Suresh Singh (ADO)

9. Name of the designation of Officer

from the building side

: Principal

10. Year of Construction

: 1989

DSIIDC/CPM(FD-VI)/2014-15/71 dated 30.07.14

	Olicant sietter no	DC/CPM(ED-VI)/ Requirement F	Provided at	Remarks	
No	safety requirements as per circular no. 3298 to 3398	-	Site	MR/NMR	
	Dated. 01.03.11				
	Road width Gate width	6 m	8 m	MR _	
			N.A	N.A	
		N.A	N.A	N.A	
	Number, Width, Type and Arrangen	nent of Exits	1		
2	a. Number of Staircases				
	Upper Floor	2 no.	2 no	MR	
	Basement	N.A	N.A	N.A	
	B. Width of Staircases			NAD	
	Upper Floor	1.5 m	1.25 m each	MR	
	Basement	N.A	N.A	N.A	
	c. Protection of exits	N.A	N.A	N.A	
	Fire check door	N.A	N.A	N.A	
	Pressurization	N.A	N.A	N.A	
	e. No. of continuous staircases to	1 no.	1 no.	MR	
	terrace	1.5 m	2.4 m	MR	
	g. Width of Corridor	1.5 m	1 m	MR	
	n. D001 312e				
3	Compartmentation.	N.A	N.A	N.A	
	Fire check door	N.A	N.A	N.A	
	Sealing of electrical shafts Fire rating of shaft door	N.A	N.A	N.A	
	Water curtain	N.A	N.A	N.A	
	Fire Dampers	N.A	N.A	N.A	
	- Na - Tomont System				
4		30a/c per hou		N.A	
	Basement Upper floor	12a/c per hou	ur N.A	N.A	

Fire Extinguisher	The state of the s				
Total numbers	20 no.	20 no.	MR		
types	CO ₂ & ABC	CO ₂ & ABC	MR		
IS marking	ISI marked	ISI marked	MR		
First-aid-Hose Reels.					
Total numbers of each floor	02 no.	Provided	MR		
Length of hose reel hose	30 m	Provided	MR		
Nozzle diameter	5 mm	Provided	MR		
Automatic fire detection and alarming system.					
Type of detectors	N.A	N.A	N.A		
Location of main panel	N.A	N.A	N.A		
Location of repeater panel Alternate source of power Hooters	N.A	N.A	N.A		
	N.A	N.A	N.A		
	N.A	Provided	MR /		
MOEFA	N.A	N.A	N.A		
Public address System.	N.A	Provided	MR		
Automatic Sprinkler System.					
basement	N.A	N.A	N.A		
	N.A	N.A	N.A		
sprinkler above false ceiling	N.A	N.A	N.A		
Internal Hydrants					
size of riser/down-comer Number of hydrants per floor Hose Box	N.A	N.A	N.A		
	NΑ	N A	N.A		
			N.A		
Yard Hydrants	T.A.	10.7	N.A		
	ΝΔ	NA	N.A		
			N.A		
Pumning Arrangements	IN.A	IV.A	IN.A		
	I NI A	I NI A	T B I A		
The state of the s			N.A		
			N.A		
Standby pump out put			N.A		
Standby pump Head			N.A		
Auto Starting / Manual			N.A		
stopping	N.A	N.A	N.A.		
Pump House Access	NΔ	NΔ	N.A		
Terrace Level	14.7	14.73	IV.A		
Discharge of pump	450 LPM	450 LPM	MR		
Head of the Pump			MR		
Power supply		Provided	MR /		
Tower suppry			N.A		
Auto Starting of pump	14.74	14.74	IV.A		
	Total numbers types IS marking First-aid-Hose Reels. Total numbers of each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarmi Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main Pump Number of main pumps Jockey pump out put Jockey pump out put Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump	types IS marking IS marking First-aid-Hose Reels. Total numbers of each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters N.A Public address System. Automatic Sprinkler System. N.A Automatic Sprinkler System. basement upper floor sprinkler above false ceiling N.A Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box N.A Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump N.A	Total numbers types IS marking ISI marked ISI nake In provided ISI marked ISI nake IN.A IN.A IN.A IN.A IN.A IN.A IN.A IN.A		

	1 .
M	172
	13

14	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	N.A	N.A	N.A	
	Draw-off connection	N.A	N.A	N.A	
	Fire service inlet	N.A	N.A	N.A	
	Access to tank	N.A	N.A	N.A	
	Overhead Tank capacity	10,000 Liters	10,000 Liters	MR 0	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage	N.A	N.A	N.A	
		N.A	N.A	N.A	
		N.A	N.A	N.A	
		N.A	N.A	N.A	
		N.A	N.A	N.A	
17	Standby power supply	N.A	N.A	N.A	
18	Refuge Area.				
	Total area Location	N.A	N.A	N.A	
		N.A	N.A	N.A	
19	Fire Control Room				
	Detector system panel	N.A	N.A	N.A	
	Flow switch panel PA system panel Batter backup Building Floor Plans	N.A	N.A	N.A	
		N.A	N.A	N.A	
		N.A	N.A	N.A	
		N.A	N.A	N.A	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A	N.A	N.A	

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under the circular No. 3298 to 3398 dated 01.03.11

Jengh 12.8.14

Signature of the Inspecting Officer

Name Suresh Singh

Designation ADO (Shah)

