GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, Tel: 011-23414333

No.F6/ DFS/ MS/School/2014/ 57_ /1104

Dated: 01) 09 /14

FIRE SAFETY CERTIFICATE

Certified that Amity International School, Located at 44,M block, Saket, New Delhi-110017 comprised of basement, ground and 03 upper floors, owned/occupied by Amity School Management was issued NOC vide letter no.F6/DFS/MS/2011/2059 dated: 19/08/2011 by this department. The school building was reinspected by the officer concerned of this department on 20/08/2014 in the presence of Mr. G Hazra (Admn. Officer) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class- Educational (School) with effect from the date of issue of this certificate for a period of three years, subject to compliance of the below mentioned conditions.

Issued on -- 2-1-4--- at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer

Ole Milally MADO(BLD)

Copy to: -

Mr.G Hazra Amity International School, 44,M,Block Saket, New Delhi-110017

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. The basement shall be used as per the provisions of National Building Code.
- 5. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building :Amity International School,44,M Block Saket, New Delhi-110017

Type of Occupancy

: Educational (School)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2011/2059 Dated: 19/08/2011

5. Fire Safety directives letter No: Nil

6. Date of inspection

: 20/08/2014

7. Name of the Inspecting Officers : D.B.Mukherjee, ADO(BCP)

8. Name and designation of officers

from the building side

: WG CDR G.Hazra (Administrative Officer)

9. Year of Construction

:1990 & 1995

10. Applicant's letter No.

: Nil dated: 27/06/2014

(The school is running in two blocks comprised of basement, ground and 3 upper floors and both blocks are connected at each floor level through corridor)

| S. No. | | mum Standards on fire tion and fire safety U/R 33 | BBL/NBC Requirement | Provided at Site | | Remarks MR/NMR |
|-------------------------|--------------|--|------------------------|--------------------|--------|-------------------|
| 1 | Access to | building | | | | |
| | • R | oad width | 09 mtrs. | Provided | | MR |
| | | ate width | 05 mtrs. | Provided | 8 | MR |
| | • W | idth of internal road | N/A | N/A | | N/A |
| 2 | Number, | Width, Type & Arrangeme | nt of Exits | | | 9 |
| a. Number of staircases | | | | | | |
| • | Upper F | oors | 02 | 02 | | MR |
| • | Basemer | nts | 02 | 04 | , | MR |
| b. Wie | dth of stair | cases | | | | IVIK |
| • | Upper Fl | oors | 1.50 m | 1.41 m & 1.48m | | MR |
| • | Basemen | tsc. Protection of exits | 1.50m | 1.51m,1.02m,1.16m, | &1.48m | MR |
| • | Fire chec | k door | N/A | N/A | | N/A |
| • | Pressuriz | ation | N/A | N/A | | N/A |
| e. No. | of continu | ous staircases to terrace | 01 | 02 | | MR |
| g. Wid | lth of Corr | idor | N/A ~ | N/A | | N/A |
| ı. Doo | or Size | _ | N/A | N/A | ¥ | N/A |

| 1 3 | AN A SIG | MIG | | | | |
|-----|---|---------------------|-------------------------------|---------------------------------------|--|--|
| 1 | Compartmentation. | | | | | |
| | Fire check door | N/A | NI/A | <u> </u> | | |
| | Sealing of electrical shafts | N/A | N/A | N/A | | |
| | Fire Rating of shaft door | | N/A | N/A | | |
| | Water Curtain | N/A | N/A | N/A | | |
| | Fire Dampers | N/A | N/A | N/A | | |
| 4 | Smoke Management System. | N/A | N/A | N/A | | |
| | Basements | 30 a/c per hou | F 1 | | | |
| | Upper floors | 12 a/c per hou | Turis | MR | | |
| 5 | Fire Extinguishers | are per nou | r Natural ventilation | MR | | |
| | • Total numbers | Required | | | | |
| • | • Types | ABC,Co ₂ | 56 nos | MR | | |
| | IS marking | Required | Provided | MR | | |
| 6 | First-Aid Hose Reels. | Required | Provided | MR | | |
| | Total numbers on each floor | 01 | 00 | 181 | | |
| | Length of hose reel hose | 30m | 02 nos. Provid | led MR | | |
| | Nozzle diameter | 5mm | Provided | MR | | |
| 7 | Automatic fire detection and alarming | | Provided | MR | | |
| | Type of detectors | N/A | | , , , , , , , , , , , , , , , , , , , | | |
| | | IV/A | N/A | N/A | | |
| | Location of Main Panel | N/A | N/A | N/A | | |
| | Location of Repeater Panel | N/A | N/A | N/A | | |
| | Alternate source of power | N/A | N/A | N/A | | |
| | Hooters' Location | N/A | N/A | N/A | | |
| | MOEFA | N/A | N/A | | | |
| | Public Address System. | N/A | N/A | N/A | | |
| 0 | Automatic Sprinkler System | * ^ | 14/71 | N/A | | |
| 32 | Basement | Required | Provided | MD | | |
| | Upper Floor | N/A | N/A | MR | | |
| | Sprinkler above false ceiling | N/A | N/A | N/A | | |
| 1] | Internal Hydrants | | 11//1 | N/A | | |
| | • Size of riser/down-comer | Required | Provided | MR | | |
| 1 | Number of hydrants per floor | Required | Provided 02 nos at each floor | | | |
| | Hose Box | Required | Provided Provided | MR | | |
| | | required | Yard Hydrants. | | | |
| Y | Yard Hydrants. | required | 1 TO FIGURE | IVIK | | |
| Y | | Not Required | But Provided | MR | | |

| 13 | Pumping Arrangements | | | | | |
|----|---|----------|-------------------|-------|--|--|
| | Ground Level | | | | | |
| | Discharge of main Pump | N/A | N/A | N/A | | |
| | Head of Main pump | N/A | N/A | N/A | | |
| | Number of main pumps | N/A | N/A | N/A | | |
| | Jockey Pump out put | N/A | N/A | N/A | | |
| | Jockey pump head | N/A | N/A | N/A | | |
| | Standby Pump out put | N/A | N/A | N/A | | |
| | Standby Pump Head | N/A | N/A | N/A | | |
| | Auto Starting/ Manual stopping | N/A | N/A | N/A | | |
| | Pump House Access | N/A | N/A | N/A | | |
| | Terrace level | 8 | | 14/21 | | |
| | Discharge of pump | Required | 900 lpm & 220 lpm | MR | | |
| | Head of the pump | Required | 54m & 34.5m | MR | | |
| | Power Supply | Required | Provided | MR | | |
| | Auto Starting of pump | Required | Provided | MR | | |
| 14 | Captive Water Storage for fire fighting | | | | | |
| | Underground tank capacity | N/A | N/A | N/A | | |
| | Draw-off connection | N/A | N/A | N/A | | |
| | Fire service inlet | Required | Provided | MR | | |
| | Access to tank | N/A | N/A | N/A | | |
| | Overhead Tank capacity | 10000 L | 10000 L | MR | | |
| | Exit Signage. | Required | Provided | MR | | |
| | Provision of Lifts. | | | | | |
| | Pressurization of Lift Shaft | N/A | N/A | N/A | | |
| | Pressurization of Lift lobby | N/A | N/A | N/A | | |
| | Communication In lift Car | N/A | N/A | N/A | | |
| | Fireman's Grounding Switch | N/A | N/A | | | |
| | • Lift Signage | N/A | | N/A | | |
| - | C4 II | | N/A | N/A | | |
| + | Standby power supply Refuge Area | N/A | N/A | N/A | | |
| + | | | , = 1 | | | |
| | Total Area | N/A | N/A | N/A | | |
| | > Location | N/A | N/A | N/A | | |

| 19 | Fire Control Room | | | |
|----|--------------------------------------|----------|----------------------------------|-----|
| | Detector System Panel | N/A | N/A | N/A |
| | Flow Switch Panel | N/A | N/A | N/A |
| | PA System Panel | N/A | N/A | N/A |
| | Batter backup | N/A | N/A | N/A |
| | Building Floor Plans | N/A | N/A | N/A |
| 20 | Special Fire Protection Systems for | Required | One Co ₂ extinguisher | MR |
| | Protection of special Risks, if any: | | provided near electric | * |
| | | | panels. | - |

The fire protection systems provided in the school were test checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter no F6/DFS/MS/2011/2059 Dated: 19/08/2011 renewal under rules 35 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly DFA is put up for approval pl.

July 25/8/14

20 (South) 25/8/1

Signature of the Inspecting Officer Name (D.B.Mukherjee) Designation :- Assistant Divisional Officer