GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI – 110001

Fax:- 011-23412593 E-mail ID:cfohq.dlfire@nic.in

No f6/065/005/School/2014/1073 Dated: 27/08/14

FIRE SAFETY CERTIFICATE

Certified that the Kamlesh Balika Vidhalaya, Kothi No.5, Kotla Road, New Delhi comprises of Ground floor was granted NOC by this department vide letter No. F6/DFS/MS/2006/3751 dated 22-12-2006. The premises was re-inspected by the officer concerned of this department on 20-08-2014 in the presence of Mrs. Chhama Sharma (Head Mistress) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Group B "Educational Building" Ground floor with effect from 27/2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 on the conditions printed below.

Issued on ... 2.7. /... /... at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to:-

1. Mrs. Chhama Sharma (Head Mistress) Kamlesh Balika Vidhalaya, Kothi No.5, Kotla Road, New Delhi.

2. Amoolya Kumar Sharma Secretary, Kamlesh Balika Vidhalaya Society (Regd.) 5, Kotla Road, New Delhi-110002.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

| 2. Ty | ame & address of the building | · Kamles | | | | | | | | |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|----------------------------------------------------------------|------------------------------|-----------------------------------------------------|--------------------|-------|-----------------------------------------------|-------------------------------|--|-----------------------|
| | | . Italilies | sh Balika Vidhalaya, | Balika Vidhalaya, Kothi No. 5, Kotla Road, New Delh | | | | | | |
| 3. Ty | pe of Occupancy | : Educati | : Educational (Ground floor) | | | | | | | |
| | rpe of Case | : Renewal | 1 | | | | | | | |
| 4. Details of previous NOC5. Fire Safety directives Letter No.6 Date of inspection7 Name of the Inspecting Officer | | : F6/DFS/MS/2006/3751 Dated 22/12/2006 : NA : 20/08/2014 | | | | | | | | |
| | | | | | | | : M. K. Sharma (Assistant Divisional Officer) | | | |
| | | | | | | | | ne and designation of Officer | | Tarina (115515tant D1 |
| | | | from the building side | · Mrc Chi | hama Channa (II M. | -4- \ | | | | |
| 9 Ye | ear of Construction | : old | nhama Sharma (H.Master) | | | | | | | |
| | oplicant's letter No. | | | | | | | | | |
| | | | o. Nill- Dated 03/07/ | 2014 | | | | | | |
| S No | Minimum standards on fire p | revention | Requirements | Provided at site | Remarks | | | | | |
| ¥ | and fire safety U/R 33 | | | | MR/NMR | | | | | |
| | Access of building | | | | | | | | | |
| | Road width | | 6 Mtr. | 9 Mtr. | MR | | | | | |
| | Gate width | | 4.5 Mtr. | 4.5 Mtr. | MR | | | | | |
| | Width of internal road | | NA | NA | NA | | | | | |
| • | Number, width, Type & Arrangements of exits | | | | | | | | | |
| a. Number of staircases | | | | | | | | | | |
| | • Upper floors | | NA | NA | NA | | | | | |
| | Basements | | NA | NA | NA | | | | | |
| | b. Width of staircases | | | V + | | | | | | |
| | • Upper floors | | NA | NA | NA | | | | | |
| | • Basements | | NA | NA | NA | | | | | |
| | cProtection of exits | | | | 11/1 | | | | | |
| | Fire check door | | NA | NA | NA | | | | | |
| | Pressurization | | | | INA | | | | | |
| | | | NA | NA | NA | | | | | |

| | d. No of continuous staircase to terrace | NA | NA | NA | |
|----|-------------------------------------------------------------------|----------------------|----------------------|-------|--|
| | e. Width Of Corridor | NA | NA | NA | |
| | f. Door Size | NA | NA | NA | |
| 3. | Compartmentation | | | | |
| | Fire check door | NA | NA | NA | |
| | Sealing of electrical shafts | NA | NA | NA | |
| | Fire Rating of shaft door | NA | NA | NA | |
| | Water Curtain | NA | NA | NA | |
| | Fire Dampers | NA | NA | NA | |
| 4 | Smoke managements System | | | | |
| | Basements | NA | NA | NA | |
| | Upper floors | NA | NA | NA | |
| 5 | Fire Extinguishers | | | | |
| | Total numbers | 5 Nos. | 5 Nos. | MR | |
| | Types | ABC, CO ₂ | ABC, CO ₂ | MR | |
| | • IS marking | Required | Provided | MR | |
| 6 | First – Aid Hose Reels | | | | |
| | Total numbers on each floor | NA | NA | NA | |
| | Length of hose reel hose | NA | NA | NA | |
| | Nozzle diameter | NA | NA | NA | |
| 7 | Automatic fire detection and alarming sys | | 1111 | 142 k | |
| | Type of detectors | NA | NA | NA | |
| | | NA | NA NA | NA NA | |
| | Location of Main Panel Location of Panel Location of Main Panel | | | | |
| | • Location of Repeater Panel | NA | NA | NA | |
| | • Alternate source of power | NA | NA | NA | |
| - | Hooters' Location | NA | NA | NA | |
| 8 | MOEFA | NA | NA | NA | |
| 9 | Public Address System | NA | NA | NA | |
| 10 | Automatic Sprinkler | | | | |
| | Basements | NA | NA | NA | |
| | Upper Floor | NA | NA | NA | |
| | Sprinkler above false ceiling | NA | NA | NA | |
| | | | | | |

ML

| | Internal Hydrants | | | |
|----|------------------------------------------------|-------|---------|-------|
| | Size of riser/down- comer | NA | NA | 27.4 |
| | Number of hydrants per floor | NA | NA | NA |
| | Hose Box | NA | NA NA | NA |
| 12 | Yard Hydrants | | . NA | NA |
| | Total number of hydrants | NA | 271 | |
| | Hose Box | NA NA | NA | NA |
| 13 | Pumping Arrangements | IVA | NA | NA |
| | Ground Level | | | |
| | Discharge of main pump | 7.7.4 | | |
| | Head of main pump | NA | NA | NA |
| | | NA | NA | NA |
| | ramoer of main pumps | NA | NA | NA |
| | sockey pump out put | NA | NA | NA |
| | Jockey pump head | NA | NA | NA |
| | Standby Pump out put | NA | NA | NA |
| | Standby Pump Head | NA | NA | NA |
| | auto Staring/Manual stopping | NA | NA | NA |
| | Pump House Access | NA | NA | NA |
| | o Terrace level | | | |
| | Discharge of pump | NA | NA | NA |
| | Head of the pump | NA | NA | NA |
| | Power supply | NA | NA | NA . |
| | Auto starting of pump | NA | NA | NA |
| 4 | | | 1, 74.1 | |
| - | Captive water Storage for fire fighting | NA | NA | NA |
| | Under ground tank capacity | NA | NA | NA |
| | Draw of connection | NA | NA | NA |
| | Fire service inlet | NA | NA | NA |
| | Access to tank | NA | NA | NA |
| | Overhead Tank capacity | NA / | NA | NA |
| 5 | Exit Signage | NA | NA | NA |
| 5 | Provision of Lifts | NA | NA | NA NA |

N/6

| | • Pressurization of Lift Shoft | 774 | | |
|----|--------------------------------------------------------------------------|-----|----|-------|
| | Tressurization of Lift Shall | NA | NA | NA |
| | ressurization of filt lobby | NA | NA | NA |
| | Communication in lift Car | NA | NA | NA |
| | Fireman's Grounding Switch | NA | NA | NA |
| | Lift Signage | NA | NA | NA |
| 17 | Standby power supply | NA | NA | NA NA |
| 18 | Refuge Area | | | INA |
| | Total area | NA | NA | NA |
| | • Location | NA | NA | NA |
| 19 | Fire control room | | | 1111 |
| | Detector system panel | NA | NA | NA |
| - | Flow Switch Panel | NA | NA | NA |
| | PA System Panel | NA | NA | NA |
| | Batter backup | NA | NA | NA |
| | Building Floor Plans | NA | NA | NA |
| 20 | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA |
| | or special Kisks, II any; | | | |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no F6/DFS/MS/2006/3751 dated 22/12/2006 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended please.

Signature of the Inspecting Officer

Name :- M.K. Sharma

Designation :- A. D.O. (Co

Dalca ...