GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333 NO.F6/DFS/MS/2014/ \$7 / 1149 Dated: **08/09/14**

FIRE SAFETY CERTIFICATE

Issued on ______ at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. Chief Architect, DMRC Ltd., Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi-110001.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Lajpat Nagar Metro Station, New Delhi

2. Type of Occupancy

: Assembly (D-7)

3. Type of Case

: renewal

4. Details of previous NOC

: F6/DFS/MS/2010/2800 dated 27/09/2010.

5. Fire Safety directives letter No : F.6/DFS/MS/BP/2008/2989 dated 31/10/2008

6. Date of inspection

: 27.08.2014

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side

: Mr. Parvesh Kumar (Fire Inspector),

9. Year of Construction

: 2005

10. Applicant's letter No.

: DMRC//O&M/Fire/NOC/L-6/2014/35 dated 17.07.2014

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	09 mts	Provided	MR	
	• Gate width	06 mts	Provided	MR	
	Width of internal road	06 mts	Provided	MR	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				
	• Upper Floors	03 Nos. (Ground to concourse); 04 Nos. (concouto platform)	Provided Provided	MR	
	 Basements 	N/A	N/A	N/A	
	b. Width of staircases	-	- i, tas.	_	
	Upper FloorsBasements	Ground to concourse (4.12 3.88, 2.20 mts) concourse platform (4.20, 4.20, 2.09, 2. mts)	to Trovided	MR	
	c. Protection of exits	N/A	N/A	N/A	
	Fire check door	-	_	•	
	Pressurization	Required	Provided	MR	
		N/A	N/A	N/A	
	e. No. of continuous staircases to terrace	02	02	MR	
	g. Width of Corridor h. Door Size	2.0 m	2.5 m	MR	
y	II. DOOF SIZE	1.5 m	1.5 m	MR	
3	Compartmentation.	9			
	Fire check door	Required	Provided	MR	
	 Sealing of electrical shafts 	Required	Provided	MR	

	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour 12 a/c per hour	N/A	N/A	
	• Opper noors	12 a/c per nour	N/A	N/A	
5	Fire Extinguishers				
	Total numbers	30	Provided	MR	
	• Types	CO ₂ , W.CO ₂	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.				
	Total numbers on each floor	03	Provided	MR	
	• Length of hose reel hose	45 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	Required	Smoke Detectors Provided	MR	
	Location of Main Panel	Required	Provided at Station Control Room	MR	
	Location of Repeater Panel	Required	Provided at Station Concourse level	MR	
	Alternate source of power	Required	D.G Set Provided	MR	
2	Hooters' Location	Required	Provided at all levels	MR	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.		* 7		
	Basement	N/A	N/A	N/A	
	Upper Floor	N/A	N/A	N/A	
	Sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants				
	Size of riser/down-comer	100 mm	Provided	MR	
	 Number of hydrants per floor 	Required	Provided	MR	
	Hose Box	Required	Provided	MR	
12	Yard Hydrants.				

1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			D :1 1		
	Total number of hydrants	Required	Provided	MR	
	Hose Box	Required	Provided	MR	
13	Pumping Arrangements.				
	Ground Level	-	-	-	
	Discharge of main Pump	1800 LPM	Provided	MR	
	Head of Main pump	70 mts.	Provided	MR	
	Number of main pumps	02	Provided	MR	
W	Jockey Pump out put	180 PM	Provided	MR	
	Jockey pump head	70 mts	Provided	MR	
	Standby Pump out put	1800 LPM	Provided	MR	
	Standby Pump Head	70 mts.	Provided	MR	
	Auto Starting/ Manual stopping	Required	Provided	MR	
	Pump House Access	Required	Provided	MR	
	Terrace level	-	-	-	
	Discharge of pump	N/A	N/A	N/A	
	➤ Head of the pump	N/A	N/A	N/A	
	Power Supply	N/A	N/A	N/A	
	> Auto Starting of pump	N/A	N/A	N/A	
14	Captive Water Storage for fire fighting.				
	Underground tank capacity	50,000 lts	Provided	MR	
	> Draw-off connection	Required	Provided	MR	
	> Fire service inlet	Required	Provided	MR	
	Access to tank	Required	Provided	MR	
	Overhead Tank capacity	N/A	N/A	N/A	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	Required	Provided	MR	
	Fireman's Grounding Switch	Required	Provided	MR	
	Lift Signage		Provided	MR	
		Required	Tiovided	IVIIX	

17	Standby power supply	Required	D.G.Set Provided	MR	
18	Refuge Area.				
e e	> Total Area	N/A	N/A	N/A	
	> Location	N/A	N/A	N/A	
19	Fire Control Room		9.9		
	Detector System Panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	 Building Floor Plans 	N/A	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	CO ₂ trace tube flooding system found provided near elect. panel	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

The shortcomings earlier issued by this department vide letter No. F.6/DFS/MS/Metro/2014/362 dated 11.02.2014 has been complied by the DMRC management.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/2010/2800 dated 27/09/2010, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Accordingly DFA is put up for signature please.

M.K.CHATTOPADHYAY Asstt. Div. Officer (M.Road)