## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001 Fax:-011-23412593 E-mail ID: cfohq.dlfire@nic.in

No. F6/DFS/MS/GH/2014/ MOZ/1202

Dated 15/09/14

## FIRE SAFETY CERTIFICATE

Certified that Discotheque "The Kitty Su" at the Lalit Hotels, (Bhart hotels Ltd), , Bharakhamba, Connaught Place, New Delhi comprise of Ground floor (Dance floor, Private sitting areas, a bar area, lobby) owmer/occupied by the Lalit Hotels have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service rule, 2010 and verified by the officer concerned of Delhi Fire Service on 26/08/2014 in the presence Sh. Kannan Chief Engg. and that the building/premise is fit for occupancy Class—D (Assembil) sub Division D-3 with effect from 1.2.1.2.9.14... for a period of 03 (three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(**Dr. G. C. Misra**) Chief Fire Officer Delhi Fire Service Ph – 011-23414333

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 1146/49/Joint. C.P./Lic. (Amist.) dated New Delhi 08-01-2014.

2. General Manager The Lalit Hotels (Bhart hotels Ltd), Bharakhamba, Connaught Place, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

## **INSPECTION REPORT**

1. Name & address of the building : "The kitty Su" located at The lalit Hotels, Barakhamba,

Connaught Place, New Delhi.

2. Type of Occupancy : Residential Building

3. Type of Case : Renewal

4. Details of previous NOC : NA

5. Fire Safety directives Letter No. : F6/MS/DFS/Hotel/2011/2021 dated 19/08/2011

6. Date of inspection : 26/08/2014

7 Name of the Inspecting Officer : Sh.M. K. Sharma (Assistant Divisional Officer)

8 Name and designation of Officer

from the building side : Mr. Kanan(Chief Engeineer)

9 Year of Construction : Old.

10. Applicant's letter No. : 1446/49/Joint.C.P/Lic.(Amist.) date New Delhi 08-01-2014.

S No	Minimum standards on fire prevention	Existing	Provided at site	Remarks	
	and fire safety U/R 33	Requirements		MR/NMR	
1.	Access of building	1			
	Road width	15 Mtr.	15 Mtr.	MR	
	Gate width	05 Mtr.	06 Mtr.	MR	
	Width of internal road	NA	NA	NA	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases (Each block)	7, 141-1			
	Upper floors	3 Nos.	3 Nos.	MR	
	Basements	5 Nos.	5 Nos.	5 Nos.	
	b.Width of staircases		•	1	
	Upper floors	1.10Mtrs. eacg	1.10Mtrs.each	MR	
	Basements	1.10Mtrs.each	1.10Mtrs.each	MR	
	c. Protection of exits				
	• Fire check door	Required	Provided	MR	
	Pressurization	Required	Provided	MR	

12/10-

	d. No of continuous staircase to terrace	1 Nos.	1 Nos.	MR
	e. Width Of Corridor	NA	NA	NA
	f. Door Size	1 Mt.X2	1 Mt.X2	MR
	Compartmentation			
	Fire check door	Required	Provided	MR
	Sealing of electrical shafts	Required	Provided	MR
	<ul> <li>Fire Rating of shaft door</li> </ul>	NA	NA	NA
1	Water Curtain	NA	NA	NA
	• Fire Dampers	Required	Provided	NA
	Smoke managements System			
	Basements	30 ACPH	30 ACPH Mechanical	MR
	<ul> <li>Upper floors</li> </ul>	12 ACPH	Provided	MR
	Fire Extinguishers			
	Total numbers	182 Nos.	200 Nos.	MR
	• Types	ABC, CO <sub>2</sub>	ABC, CO <sub>2</sub>	MR
	IS marking	ISI	Yes	MR
	First – Aid Hose Reels			
	Total numbers on each floor	03	03 at each floor	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 Mtr.	30 Mtr.	MR
100	<ul> <li>Nozzle diameter</li> </ul>	05 MM	05 MM	MR
	Automatic fire detection and alarming	system		,
	Type of detectors	Required	Provided	MR
and the second s	<ul> <li>Location of Main Panel</li> </ul>	Ground floor	Ground floor	MR
	<ul> <li>Location of Repeater Panel</li> </ul>	NA	NA	NA
	Alternate source of power	Required	Provided	MR
	<ul> <li>Hooters' Location</li> </ul>	Every floor	Every floor	MR
	MOEFA	Required	Provided	MR
P. Marin S. C. and Salah Salah	Public Address System	Required	Provided	MR
	Automatic Sprinkler			
	<ul> <li>Basements</li> </ul>	Required	Provided	MR
	<ul> <li>Upper Floor</li> </ul>	Required	Provided	MR
	<ul> <li>Sprinkler above false ceiling</li> </ul>	Required	Provided	MR

	Size of riser/down- comer	150 MM	150	
	Number of hydrants per floor		150 MM	MR
	• Hose Box		3 Nos	MR
2 Ya	rd Hydrants	3 Nos	3 Nos	MR
	<ul><li>Total number of hydrants</li><li>Hose Box</li></ul>	10Nos	10Nos	MR
Pur		10Nos	10Nos	MR
	nping Arrangements			
	Ground Level		-	•
	Discharge of main pump	2800 LPM	2800 LPM	MR
	riedd of main pump	80Mtrs.	80Mtrs.	MR
•	rathoer of main pumps	02Nos	02Nos	MR
•	Jockey pump out put	180 LPM	450 LPM	MR
•	Jockey pump head	80 Mtr.	80 Mtr.	MR
•	Standby Pump out put	2800 LPM	2800LPM	MR
	Standby Pump Head	80 Mtrs.	80Mtrs.	MR
•	auto Staring/Manual stopping	Required	Provided	
•	Pump House Access	Required	Provided	MR
0	Terrace level			MR
•	Discharge of pump	NA	NA	NI A
•	Head of the pump	NA	NA	NA
•	Power supply	NA	NA	NA
•	Auto starting of pump	NA	NA NA	NA NA
	C - F-m.p		INA	NA
Captiv	e water Storage for fire fighting			
•	Under ground tank capacity	2,00,000 ltrs.	2.00.000	:
•	Draw of connection	Required	2,00,000 ltrs.	MR
	Fire service inlet	•	Provided	MR
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	Required	Provided	MR
Exit Sig		20,000 Ltr.	50,000 Ltr.	MR
	on of Lifts	Required	Provided	MR

	<ul><li>Pressurization of Lift Shaft</li><li>Pressurization of lift lobby</li></ul>	Required	Provided	MR
	Communication in lift Car	Required	Provided	MR
	N ×	Required	Provided	MR
	Theman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided	MR
18	Refuge Area			
	Total area	NA NA	NA	NA
	• Location	NA	NA	NA
19	Fire control room	-		
	Detector system panel	Required	Provided	MR
	Flow Switch Panel	Required	Provided	MR
	PA System Panel	Required	Provided	MR
	Batter backup	Required	Provided	MR
	Building Floor Plans	Required	Provided	MR
20	Special Fire Protection Systems for	Required	Provided	MR
	Protection of special Risks, if any;			1411

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rule, it is recommended to grant fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / for FSC is recommended please.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - A. D.O. (CC)

Do COIL MR