## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

Fax:-011-23412593 No. F6/DFS/MS/GH/2014/ H02/1230 E-mail ID: cfohq.dlfire@nic.in Dated 22/09/14

## FIRE SAFETY CERTIFICATE

Certified that the Hotel Swati Deluxe located at 17A/32 W.E.A Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Four Upper floor, using basement as storage, Ground floor as reception, office and restaurant, first second, third & four floor each having eleven guest room respectively (Total 44 guest rooms) was granted NOC by this department vide letter No.F6/DFS/MS/GH/2011-12/2150 dated 02-09-2011. The premises was re-inspected by the officer concerned of this department on 19-09-2014 in the presence of Mr. Parveen (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub-Division A-1 Guest House for 44 guest rooms with effect from -2-2-1-2014 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ..... 2. 2. . /. 0. 3. /. 1. 4. . . . . at New Delhi by.

(Dr. G. C. Misra) Chief Fire Officer Delhi Fire Service Ph - 011-23414333

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi – 110049 w.r.t. letter No 26650/Joint. C.P./Lic. (H) dated New Delhi 16-07-2014.

2. Mr. Parveen (Manager) Hotel Swati Deluxe, 7A/32 W.E.A Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

## **INSPECTION REPORT**

: Hotel Swati Deluxe, located at 7A/32 W.E.A Karol Bagh, 1. Name & address of the building

New Delhi.

: Residential (Guest house) B+G+4 Floor total guest rooms-44 2. Type of Occupancy

: Renewal 3. Type of Case

: F6/DFS/MS/GH/2011-12/2150 dated 02/09/2011 4. Details of previous NOC

5. Fire Safety directives Letter No. : NA

6 Date of inspection : 18/09/2014

: M. K. Sharma (Assistant Divisional Officer) 7 Name of the Inspecting Officer

8 Name and designation of Officer

: Mr. Parveen (Manager) from the building side

9 Year of Construction : 2001

10. Ap	oplicant's letter No. : 26649/Jo	oint.C.P./Lic.(H) dt N	New Delhi 16/07/2014	lel Brish
S No	Minimum standards on fire prevention	Requirements	Provided at site	Remarks
	and fire safety U/R 33			MR/NMR
1.	Access of building			
	Road width	NA	9 Mtr.	MR
	Gate width	NA	NA	, NA
	Width of internal road	NA	NA	NA
2.	Number, width, Type & Arrangements of exits			
	a. Number of staircases			
	Upper floors	1 No.	1 No.	MR
	Basements	1 No.	1 No.	MR
	b. Width of staircases			
	• Upper floors	1.0 Mtr.	1.12 Mtr.	MR
	Basements	1.0 Mtr.	1.12 Mtr.	MR
	c. Protection of exits			
	Fire check door	NA	NA	NA

	• Pressurization	NA	NA	NA
	No of continuous staircase to terrace	01	01	MR
	e. Width Of Corridor	1.0 Mtr.	1.0 Mtr.	MR
	E. Door Size	1.0 Mtr.	1.0 Mtr.	MR
			The same	
(	Compartmentation	NA	NA	NA
	Fire check door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	NA
	<ul> <li>Fire Rating of shaft door</li> </ul>	NA	NA	NA
	<ul> <li>Water Curtain</li> </ul>	NA	NA	NA
	• Fire Dampers	1424		
	Smoke managements System	20 A CDI I	Exhaust fans	MR
	• Basements .	30 ACPH	NATURAL	MR
	• Upper floors	12 ACPH	NATURAL	
5	Fire Extinguishers	e e		MR
100	Total numbers	18 Nos.	20 W	
	• Types	ABC, CO <sub>2</sub> , Wco <sub>2</sub>	ABC, CO <sub>2</sub> , Wco <sub>2</sub>	MR
	<ul> <li>IS marking</li> </ul>	Required	Provided	MR
6	First – Aid Hose Reels			
0	Total numbers on each floor	01 each	01 each	MR
	<ul> <li>Length of hose reel hose</li> </ul>	30 Mtr.	30 Mtr.	MR
	Nozzle diameter	05 MM	05 MM	MR
	Automatic fire detection and alarming	system		
7		NA	NA	NA
	Type of detectors	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	• Location of Repeater Panel	NA	NA	NA .
	Alternate source of power	NA	NA	NA
	Hooters' Location		Provided	MR
8	MOEFA	Required		MR
9	Public Address System	Required	Provided	IVII
10	Automatic Sprinkler	400		MD
	Basements	Required	Provided	MR

( ,-

	Upper Floor	Required	Provided	MR
	Sprinkler above false ceiling	NA	NA	NA
11	Internal Hydrants	3		
	Size of riser/down- comer	NA	NA	NA
	Number of hydrants per floor	NA	NA	NA
	Hose Box	NA	NA	NA
12	Yard Hydrants			1111
	Total number of hydrants	NA	NA	NA
	Hose Box	NA	NA	NA
13	Pumping Arrangements			1471
	o Ground Level			
	<ul> <li>Discharge of main pump</li> </ul>	NA	NA	NA
	<ul> <li>Head of main pump</li> </ul>	NA	NA	NA
	<ul> <li>Number of main pumps</li> </ul>	NA	NA	NA
	<ul> <li>Jockey pump out put</li> </ul>	NA	NA	NA
	<ul> <li>Jockey pump head</li> </ul>	NA	NA	NA
	Standby Pump out put	NA	NA	NA
	Standby Pump Head	NA	NA	NA
	auto Staring/Manual stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	o Terrace level			
	Discharge of pump	450 LPM	450LPM	MR
	Head of the pump	30 Mtr.	30 Mtr.	MR
	Power supply	Required	Provided	MR
	Auto starting of pump	Required	Provided	MR
1.1				
14 (	Captive water Storage for fire fighting	NA	NA	NA
	Under ground tank capacity	NA	NA	NA
	Draw of connection	NA	NA	NA
	Fire service inlet	NA	NA	NA
	Access to tank	Required	Provided	MR
	Overhead Tank capacity	5,000 Ltr.	5,000 Ltr.	MR

15	Exit Signage	Required	Provided	MR	
16	Provision of Lifts				
	Pressurization of Lift Shaft	NA	NA	NA	
	<ul> <li>Pressurization of lift lobby</li> </ul>	NA	NA	NA	
	Communication in lift Car	NA	NA	NA	
	• Fireman's Grounding Switch	NA	NA	NA	
	Lift Signage	NA	NA	NA	
17	Standby power supply	Required	Provided	MR	
18	Refuge Area				
	Total area	NA	NA	NA	
	• Location	NA	NA	NA	
19	Fire control room				
	Detector system panel	NA	NA	NA	
	Flow Switch Panel	NA	NA	NA	
	PA System Panel	NA	NA	NA	
	Batter backup	NA	NA	NA	
	Building Floor Plans	NA	NA	NA	
20	Special Fire Protection Systems for Protection of special Risks, if any;	Required	ABC	MR	

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2011-12/2150 dated 02/09/2011 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended please.

Signature of the Inspecting Officer

Name :- M.K. Sharma
Designation :- A. D.O. (CC)