## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F6/OFS/ms/EH/2014/NOZ/925

Dated: 24/07/19

## **FIRE SAFETY CERTIFICATE**

Certified that the Restaurant/Eating House at Swaminarayan Akshardham, N.H.24, Off.Nizammuddin Bridge, Akshardham Setu,Delhi 92 ,owned/occupied by M/s Suvasini Charitable Trust, comprised of ground plus one upper floor was granted fire safety certificate vide letter no. F.6/DFS/MS/EH/2011/1532 dated 08.07.2011. The Restaurant was inspected by the officers concerned of this department on 14.07.2014 in the presence of Sh.Jayesh Gadhia, and found that the Restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and that the building is fit for occupancy Group D Assembly Building "Restaurant" with effect from 2-4.63. J.1.9..... for a period of three years, subject to conditions printed overleaf.

Issued on ....24.1.27./.1.9...... at New Delhi by

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

To,

- Sh.Jayesh Gadhia
   M/s Suvasini Charitable Trust,
   Swaminarayan Akshardham, N.H.24,
   Off.Nizammuddin Bridge, Akshardham Setu,
   Delhi 92
- 2. Dy.Health Officer EDMC Health Department Shahadra (South Zone) Karkardooma,Shahadra,Delhi.

## **CONDITIONS:**

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized if any.
- 6. All comments/ directions of the Licensing Department shall always be permitted and followed.
- 7. "The owner /occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form'J'[sub rule(1) of rule 37] along with a copy of this certificate,six months prior to its expiry"
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: Restaurant / Eating House at Swaminarayan Akshardham

N.H.24,Off.Nizammuddin Bridge, Akshardham Setu,Delhi- 92

2. Building Comprised of

:Ground + one upper floor

2. Type of Occupancy

: Assembly (Restaurant/ Eating House)

3. Type of Case

: Renewal

4. Details of Previous FSC

: F.6/DFS/MS/EH/2014/1532 Dated 08.07.2011

5. Fire Safety directives No

: NBC Part IV

6. Date of Inspection

: 17/07/2014


7. Name of the Inspecting Officer :DO Virendra Singh 8. Name of the designation of Officer

: Sh.Jayesh Gadhia (Manager)

From the building side 9. Year of Construction

: 2009

	plicant's letter No : Dated 2	23/06/2014					
Sl.no.	Minimum Standards on fire	NBC Part IV	Provided at	Remarks			
	prevention and fire safety U/R33	Requirement	Site	MR/NMR			
1	Access to building						
	Road width	12 Mtrs	30 Mtrs.	MR			
	Gate width	N/A	N/A	N/A			
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A			
2	Number, Width, Type and Arrangement of Exits						
	a. Number of Staircases						
	Upper Floor	02 Nos	03 Nos.	MR			
	<ul> <li>Basement</li> </ul>	N/A	N/A	N/A			
	B. Width of Staircases						
_	<ul> <li>Upper Floor</li> </ul>	1.5 M	1.35 ,1.46 M	❖ MR			
	• Basement	N/A	N/A	N/A			
	c. Protection of exits	8	9 - ax 3 - V				
	<ul> <li>Fire check door</li> </ul>	N/A	N/A	N/A			
	• Pressurization	N/A	N/A	N/A			
	e. No. of continuous staircases to	N/A	N/A	N/A			
	terrace g. Width of Corridor	2.0.14					
	h. Door Size	2.0 M 2.0 Mtr.	3.0 M	MR			
3	Compartmentation.	Z.U IVITT.	3.0 M ,1.8 M	MR			
	Fire check door	N/A	N/A	NI/A			
wa <sup>2</sup>	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Sealed	N/A MR			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basement	N/A	N/A	N/A			
	<ul> <li>Upper floor</li> </ul>	Required	Provided	MR			
5.	Fire Extinguisher						
	<ul> <li>Total numbers</li> </ul>	08 nos.	12 Nos.	MR			
	<ul><li>types</li></ul>	ABC & Co2	ABC & Co2	MR			
	IS marking	ISI marked	ISI marked	MR			





	First-aid-Hose Reels.  • Total numbers of each floor	2 nos.	3 nos.	MR				
	Length of hose reel hose	30 m	30 m	MR				
	Nozzle diameter	E mm	5 mm	MR				
		5 mm	3111111					
,	Automatic fire detection and alarming system.							
	Type of detectors	N/A	Heat& smoke	MR				
	<ul> <li>Location of main panel</li> </ul>	N/A	Provided	MR				
	<ul> <li>Location of repeater panel</li> </ul>	N/A	Provided	MR				
	<ul> <li>Alternate source of power</li> </ul>	N/A	Provided	MR				
	Hooters's location	N/A	Provided	MR				
8	MOEFA	Required	Provided	MR				
9	Public address System.	N/A	Provided	MR				
10	Automatic Sprinkler System.	N/A	N/A	N/A				
	Basement	N/A	N/A	N/A				
		N/A	N/A	N/A				
	upper floors  - violater shows false spiling	N/A	N/A	N/A				
	sprinkler above false ceiling	,,	<u> </u>	*				
11	Internal Hydrants	100 MM	100 MM	MR				
	size of riser/down-comer  Number of hydropts r	2 Nos.	3 Nos.	MR				
	Number of hydrants r	2 Nos.	3 nos.	MR				
	Hose Box	2 1403.						
12	Yard Hydrants.	N/A	N/A	N/A .				
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	IN/A	1.4,7.1					
13	Pumping Arrangements.	N/A	N/A	N/A				
	Ground Level	N/A	N/A	N/A				
	> Discharge of main Pump	N/A	N/A	N/A				
	> Head of Main Pump	N/A	N/A	N/A				
	> Number of main pumps	N/A	N/A	N/A				
	<ul><li>Jockey pump out put</li><li>Jockey pump head</li></ul>	N/A	N/A	N/A				
		N/A	N/A	N/A				
		N/A	N/A	N/A				
	<ul><li>Standby pump Head</li><li>Auto Starting /Manual</li></ul>	N/A	N/A	N/A				
		13//	g					
	stopping  > Pump House Access	N/A	N/A	N/A				
		3.47						
	Terrace Level     Discharge of pump	450 LPM	450 LPM	MR				
	> Head of the Pump	40 M	40M	MR				
	> Power supply	Required	Provided	MR				
	> Auto Starting of pump	Required	Auto	MR				
1.4	Captive Water Storage for Fire	N/A	N/A	N/A				
14	Fighting.	,,,,,	y (1)					
	<ul> <li>Underground tank capacity</li> </ul>	N/A	1,00,000 Ltrs	s. MR				
	> Draw-off connection	N/A	Provided	MR				
	Fire service inlet	N/A	Provided	MR				
	> Access to tank	N/A	Provided	MR				
		10,000 ltrs.	35,000 ltrs.	MR				
	Overhead Tank capacity     Exit Signage.	Required	Provided	MR				

## N16

	1		
Provision of Lifts.	2.14	NI/A	N/A
<ul> <li>Pressurization of Lift Shaft</li> </ul>			
<ul> <li>Pressurization of Lift lobby</li> </ul>	N/A		N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
		Provided	MR
		N/A	N/A
	N/A	N/A	N/A
· · · · · · · · · · · · · · · · · · ·	Required	Provided	MR
•		N/A	N/A
		N/A	N/A
protection of special Risks, if any:			I formation
	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication in lift car</li> <li>Firemen's grounding switch</li> <li>Lift Signage</li> <li>Standby power supply</li> <li>Refuge Area.</li> <li>Total area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector system panel</li> <li>Flow switch panel</li> <li>PA system panel</li> <li>Battery backup</li> <li>Building Floor Plans</li> <li>Special Fire Protection systems for protection of special Risks, if any:</li> </ul>	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>Communication in lift car</li> <li>Firemen's grounding switch</li> <li>Lift Signage</li> <li>N/A</li> <li>Standby power supply</li> <li>Required</li> <li>Refuge Area.</li> <li>Total area</li> <li>Location</li> <li>Fire Control Room</li> <li>Detector system panel</li> <li>Flow switch panel</li> <li>PA system panel</li> <li>PA system panel</li> <li>Battery backup</li> <li>Building Floor Plans</li> <li>Special Fire Protection systems for protection of special Risks, if any:</li> </ul>	<ul> <li>Pressurization of Lift Shaft</li> <li>Pressurization of Lift lobby</li> <li>N/A</li> <li>N/A</li> <li>Communication in lift car</li> <li>N/A</li> <li>Firemen's grounding switch</li> <li>Lift Signage</li> <li>N/A</li> <li>N/A</li> <li>Lift Signage</li> <li>N/A</li> <li>Required</li> <li>Provided</li> <li>N/A</li> </ul>

Fire protection systems provided in the building were tested checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measure as required under the rules. The fire safety certificate issued vide letter no. F.6/DFS/MS /EH/2011/1532 dated 08.07.2011 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the inspecting Officer

Name:-Virendra Singh Designation :- DO (ED)

