GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333 NO.F6/DFS/MS/ 2019 | 52 | 1322 Dated: 22 | 10 | 19

FIRE SAFETY CERTIFICATE

Issued on 22 10 11 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Te do nopoli

Copy to: -

1. The Authorized Signatory, M/s Moon Steels & General Industries Private Limited, A-23, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s Moon Steels & General Industries Private Limited, A-23,

Mohan Co-operative Industrial Estate, Mathura Road, New Delhi.

2. Type of Occupancy : Industrial

3. Type of Case : renewal

4. Details of previous NOC : N/A

5. Fire Safety directives letter No : F6/DFS/MS/2011/925 dated 16.05.2011

6. Date of inspection : 09.10.2014

7. Name of the Inspecting Officers: M.K Chattopadhyay, ADO (M. Road)

: 2008

8. Name and designation of officers

9. Year of Construction

from the building side : Shri Rakshak Kapoor, Owner

10. Applicant's letter No. : nil dated 11- 09-2014

Building is comprised of basement, ground plus two upper floors

S.	Minimum Standards on fire	NBC	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building					
	Road width	09 mts	Provided	MR		
	Gate width	4.5 mts	Provided	MR		
	Width of internal road	Required	Provided	MR		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-	-	*. =		
	Upper Floors	06	provided	MR		
	Basements	06 + 02 ramps	Provided	MR		
	b. Width of staircases	-	-	_		
	Upper Floors	1.5 mts each	Provided	MR		
	Basements	1.5 mts each	Provided	MR		
	c. Protection of exits	-	-	-		
	Fire check door	Required	Provided	MR		
	• Pressurization	N/A	N/A	N/A		
	e. No. of continuous staircases to terrace	06	06	MR		
	g. Width of Corridor	N/A	N/A	N/A		
	h. Door Size	N/A	N/A	N/A		
3	Compartmentation.					



	• Fire chook de				
	The check door	Required	Provided	MR	
	• Sealing of electrical shafts	Required	Provided		
	• Fire Rating of shaft door	N/A	N/A	MR N/A	
	Water Curtain	N/A	N/A	N/A	
4	• Fire Dampers	N/A	· N/A	N/A	
-	Smoke Management System.				
	BasementsUpper floors	30 a/c per hour	Provided	MR	
5		12 a/c per hour	N/A	N/A	
	Fire Extinguishers				
	• Total numbers	15	Provided	MD	
	• Types	ABC type	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6	First-Aid Hose Reels.		Trovided	MR	
	 Total numbers on each floor 	04	Provided	1.65	
	 Length of hose reel hose 	30 m	Provided	MR	
	 Nozzle diameter 	5 mm	Provided	MR	
7				MR	
	Type of detectors	Required	Provided(Smoke)	MR	
	• Location of Main Panel	Ground floor	Provided	MR	
	Location of Repeater Panel	Required at each flo	or Provided	MR	
	• Alternate source of power	Required	Provided	MR	
	Hooters' Location	Required at each floo		MR	
	MOEFA	Required	Provided	MR	
	Public Address System.	N/A	N/A		
A	Automatic Sprinkler System.				
	BasementUpper Floor	Required	Provided	MR	
	Sprinkler above false ceiling	Required	Provided	MR	
1		Required	Provided	MR	
1111	iternal Hydrants				
	Size of riser/down-comerNumber of hydrants per floor	100 mm	Provided	MR	
	Hose Box	04	Provided	MR	
		04	Provided		



12	Yard Hydrants.			
	 Total number of hydrants 	Required(04)	Provided	MR
	Hose Box	Required(04)	Provided	MR
13	Pumping Arrangements.			
	Ground Level			
	Discharge of main Pump	2280 LPM	Provided	MR
	Head of Main pump	60 mts	Provided	MR
	Number of main pumps	01	Provided	MR
	Jockey Pump out put	180 LPM	Provided	MR
	Jockey pump head	60 mts	Provided	MR
	Standby Pump out putStandby Pump Head	2280 LPM	Provided	MR
	➤ Auto Starting/ Manual	60 mts	Provided	MR
	stopping	Required	Provided	MR
	Pump House Access	Required	Provided	MR
	Terrace level	-	-	_
	Discharge of pump	900 LPM	Provided	MR
	Head of the pump	60 mts	Provided	MR
	Power Supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
-	Captive Water Storage for fire fighting.			
	 Underground tank capacity 	1,00,000 lts	Provided	MR
	Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tankOverhead Tank capacity	Required	Provided	MR
		20, 000 lts	Provided 20,000 lts	MR
- 1	Exit Signage.	Required	Provided	MR
+	Provision of Lifts.			
	Pressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
	Communication In lift Car	Required	Provided	MR
	• Fireman's Grounding Switch	Required	Provided	MR



	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided(750 KVA)	MR
18	Refuge Area.			
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	Required	Provided	MR
	Flow Switch Panel	Required	Provided	MR
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any	Required	Provided (02 ABC type fire extinguishers near electric panel) & FM-200 provided in Server room	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

The management has rectified all the shortcomings issued by this department vide letter No. F6/DFS/MS/2014/1747 dated 05.08.2014.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/2011/925 dated 16.05.2011, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY

Designation: - Asstt. Div. Officer (M.Rd)