GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. F6/DES/MS/SH/2014/52/1249

Dated: 67/10/14

FIRE SAFETY CERTIFICATE

Certified that the M/S Pizza Hut Restaurant at (Ground, Mezzanine and first floor only) 41, Basant Lok, Vasant Vihar, New Delhi-57, comprised of basement (Storage), ground, mezzanine plus three upper floors was granted NOC by this department vide letter No. F6/DFS/MS/EH/2011/330, dated 18-02-2011. The premises was re-inspected by the officer concerned of this department on 26-09-2014 in the presence of Sh. Kiran Kumar (Manager) and found that the said restaurant building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Restaurant" with effect from D. / 19./....2014 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr. G.C. Misra) Chief Fire Officer Ph: 011-23414333

Copy to: -.

- 1. The Dy. Health Officer, Health Department, SMCD, Green Park, New Delhi.
- 2. M/S Pizza Hut Restaurant at 41, Basant Lok, Vasant Vihar, New Delhi-57.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

	E Comment				
1 Namo 9 and a six		INSPECTION REPORT			
1. Name & address of the	e building : M/S P	izza Hut Restaurant a	t 41 Basant Lak V		
2 5	New	Delhi-57.	t 41, basant Lok, Vasa	ant Vihar,	
2. Building is comprised of			C		
9	(Base)	M+3,(Restaurant at B+ ment storage only)	G+M+1") 2" &3" flo	oors others prope	
3. Type of Occupancy	: Resta	The storage offig)			
4. Type of Case	: Old Ca				
5. Details of Previous NO					
6. Fire Safety direction let	: No.F.(6/DFS/MS/EH/2011/33	30, dated-18.02.11.		
7. Date of Inspection	. 1111.				
8 Name of the Land	: 26.09	.2014			
8. Name of the Inspecting	Officers: : Vedpal	(ADO)			
3. Name and designation (of Officer				
from the building side	: Sh. Kir	an Kumar (Manager)			
10. Year of Construction	: 1999.	(Wallagel)			
11. Applicant's letter No		, dated 06.08.14.			
S.No Minimum Standar	ds on fire				
prevention and fir	e safety LI/R33	Old NOC	Provided at	Remarks	
1 Access to building	January 0/1100	Requirements	Site	MR/NMR	
Road width					
Gate width		6m	9m	MR	
Width of internal ro	ad	N.A.	N.A.	N.A.	
2 Number Width To	manula	N.A.	N.A.	N.A.	
Number, Width, Ty	pe and Arrangem	ent of Exits.		1407 (
a. Number of Upper Floor	Staircases				
Basement B. Width of Staircases		02nos.	02nos.	MR	
		02nos.	02nos.		
Upper Floor	ses	_	021100.	MR	
Upper Floor		1.25m(old case)	1.20m & 84cm		
	Basement			MR(old case	
c. Protection of exit	S	1.25m(old case)	1.20m & 89cm	MR(old case	
Fire check door		Required	D		
Pressurization		N.A.	Provided	MR	
e. No. of continuous	s staircases to	01no.	N.A.	N.A.	
terrace		01110.	01no.	MR	
g. Width of Corridor		N.A.			
h. Door Size			N.A.	N.A.	
Compartmentation		N.A.	N.A.	N.A.	
Fire check door		N.A.	3		
	Sealing of electrical shafts		N.A.	N.A.	
Fire rating of shaft d	Fire rating of shaft door		N.A.	N.A.	
Water curtain			N.A.	N.A.	
Fire Dampers		N.A.	N.A.	4	
		N.A.		N.A.	
Smoke Management	System.	14./	N.A.	N.A.	
Basement	,	300/0 nor b			
Upper floor(in restau	rant only)	30a/c per hour	Exhaust Fan Prov		
,	- July)	12 a/c per hour	Exhaust Fan Prov	rided MR	

Fire Extinguisher		9				
Total numbers	08 nos.	08 nos.	MR			
types	CO ₂ & ABC	CO ₂ & ABC	MR			
IS marking	ISI marked	ISI marked	MR			
First-aid-Hose Reels.						
Total numbers at each floor	01no.	01no.	MR			
	30m	30m.	MR			
Nozzle diameter	5mm	5mm	MR			
Automatic fire detection and alarming system.						
Type of detectors	N.A.	N.A.	N.A.			
Location of main panel	N.A.	N.A.	N.A.			
	N.A.	N.A.	N.A.			
	N.A.		N.A.			
Hooters	1		N.A.			
MOEFA	SI TAKAN PECIN		MR			
	·		N.A.			
	IN./A.	IV.A.	IV.A.			
	Required	Provided	MR			
Secretary Statement Statement Secretary Secretary		The second second second	MR			
1		2 37 32 IS 9 Belliot (#62)	N.A.			
	IN.A.	IV.A.	IN.A.			
	100mm	100mm	MR			
	The second of th		MR			
Hose Box			MR			
	01110.	OTTIO.	IVID			
	ΝΔ	ΝΔ	N.A.			
			N.A.			
	14.7 G	14.74.	IN.A.			
	NΑ	ΝΔ	N.A.			
			N.A.			
9			N.A.			
or constitutional manages and an area and area area.			N.A.			
Jockey pump out put			N.A.			
> Jockey pump head			N.A.			
Standby pump out put			N.A.			
Standby pump Head	N.A.		N.A.			
			N.A.			
Pump House Access		The state of the s	N.A.			
Terrace Level	-		MR			
Discharge of pump	450LPM		MR			
	40m	40m.	MR			
Power supply	Required	Provided	MR			
Auto Starting of pump	negulieu	I I I I I I I I I I I I I I I I I I I	IVIII			
	Total numbers types IS marking First-aid-Hose Reels. Total numbers at each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MOEFA Public address System. Automatic Sprinkler System. Basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main Pump Head of Main Pump Number of main pumps Jockey pump out put Jockey pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump	Total numbers types IS marking First-aid-Hose Reels. Total numbers at each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters MAA. MOEFA Public address System. Automatic Sprinkler System. Basement upper floor sprinkler above false ceiling Internal Hydrants size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants. Total number of hydrants Head of Main Pump Auto Standby pump out put Auto Standby pump Head Auto Standby pump Auto Standby pump Lead of the Pump Audo Standby Pump Lead of the Pump Auto Standby Pump Lead of the Pump Lead of the Pump Auto Standby Pump Lead of the Pump	Total numbers 08 nos. 08 nos. types CO₂ & ABC CO₂ & ABC ISI marking ISI marked ISI marked First-aid-Hose Reels. Total numbers at each floor 01no. 01no. Length of hose reel hose 30m 30m. 30m. Nozzle diameter 5mm 5mm Automatic fire detection and alarming system. 5mm 5mm Type of detectors N.A. N.A. Location of main panel N.A. N.A. Location of repeater panel Alternate source of power N.A. N.A. Hooters N.A. N.A. N.A. MOEFA Required Provided Public address System. N.A. N.A. MOEFA Required Provided Public address System. N.A. N.A. Basement Required Provided Required Provided Required Provided Required Provided N.A. N.A. Number of hydrants per floor 100mm			

Az

14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	N.A.	N.A.	N.A.		
	Draw-off connection	N.A.	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A.		
	Access to tank Overhead Tank capacity	N.A.	N.A.	N.A.		
		5000Liters	10000Liters.	MR		
15	Exit Signage.	Required	Provided	MR		
Pressuriza	Provision of Lifts.					
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.		
	Pressurization of Lift lobby	N.A.	N.A.	N.A.		
	Communication in lift car	N.A.	N.A.	N.A.		
	Firemen's grounding switch	N.A.	N.A.	N.A.		
	Lift Signage	N.A.	N.A.	N.A.		
17	Standby power supply	Required	Provided DG Set 180KVA	MR		
18	Refuge Area.					
	Total area	N.A.	N.A.	N.A.		
	Location	N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel	N.A.	" N.A.	N.A.		
	Flow switch panel	N.A.	N.A.	N.A.		
	PA system panel	N.A.	N.A.	N.A.		
	Battery backup	N.A.	N.A.	N.A.		
	Building Floor Plans	N.A.	N.A.	N.A.		
20	Special Fire Protection systems for of special Risks, if any:	N.A.	N.A.	N.A.		

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the NOC issued vide letter No.F.6/DFS/MS/EH/2011/330, dated 18.02.2011 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Signature of the Inspecting Officer

Name: Vedpal

Designation: ADO

Divisional Officer (South)