GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/OFS as School noin | 52 | 1328

Dated: 22/10/14

FIRE SAFETY CERTIFICATE

Certified that The Tagore International School, at E-Block, East of Kailash, New Delhi-110065, comprises of Basement, ground plus three upper floors was granted NOC by this department vide letter No. F6/DFS/MS/2009/1264, dated 08-05-2009. The premises was re-inspected by the officers concerned of this department on 13-09-2014 in the presence of Sh. R.P. Singh (Assistant Administrative Officer) and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Educational" with effect from 22-2-1.(a.)...2014 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Dr.G.C.Misra) Chief Fire Officer T.No.011-23414333

Copy to:-.,

0

- Principal,
 Tagore International School,
 E-Block, East of Kailash, New Delhi-110065.
- Dy. Director of Education,Old Secretariat, Civil Lines, Delhi.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

vitas Duhys (2015)

1	Nome 9 11	INSPECTIO	N REPORT			
	Name & address of the building	Tagore International School, at E-Block, East of Kailash, New Delhi-110065.				
2	Type of Occupancy	Educational Building "B"				
3	Type of case	Renewal				
4	Details of previous NOC	F6/DFS/MS/2009/1	264, dated 08.05.2009.			
	Fire safety directives letter No		2 From Director of Education			
5	Date of inspection					
6	Name of the inspecting Officers :	13.10.2014				
7		A.D.O. Vedpal.				
8	Name and designation of officers from the building side	Sh. R.P. Singh (Ass	istant Administrative Officer)			
9	Building Comprised of	B+G+3 (Basement I	nas two Blocks)			
9	Year of construction	1986				
	Applicant's letter No.	Nil, dated 28.08.201	4.			
10						
S. NO.	Minimum Standards on fire prevention	Old NOC	Desided at 11			
	and fire safety U/R 33	Requirement	Provided at site	Remarks MR / NMR		
1	Access to building					
	1) Road width	6m	12m			
	2) Gate width	Required	Provided	MR		
	3) Width of internal road	N/A	Provided	MR *		
2	Number, width Type & arrangement of			N/A		
	a. Number of staircases	LAILS	- Cal			
	1. Upper floors	04Nos.	04nos.	MR		
				IVIN		
	2. basements	03nos.in one				
		basement &5nos in	03nos.in one basement &5nos in 2nd basement.	MR		
		2nd basement.	Ziid basement.			
	b. Width of staircase					
		1.5m (Each)	1.3m,1.05,1.05&1.10m	MR(Old case)		
	1. Upper floors			1		
		1.5(Each)	1.3m,1m,1m,1m &1.7m.in one	MR(Old case)		
			basement and 1.5,1.5&1.18m in	(Old case)		
	2. basements		2nd basement.			
	c. Protection of exits	A	*			
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	d. No. of continuous staircase to terrace	Required	1no.	MR		
	e. Width of corridor	N/A	N/A	N/A		
3	f. Door size	1 Mtr	Provided	MR		
	Compartmentation.					
		N/A	N/A	N/A		
	0 5 5	N/A	N/A	N/A		
		N/A	N/A	N/A		
		N/A	N/A	N/A		
and the same	5. Fire dampers	N/A	NI/A			

6	Date of inspection	13.10.2014				
7	Name of the inspecting Officers :	A.D.O. Vedpal.				
8	Name and designation of officers from the building side	Sh. R.P. Singh (Assistant Administrative Officer) B+G+3 (Basement has two Blocks)				
9	Building Comprised of					
9	Year of construction					
9	Applicant's letter No.	1986				
	Applicant's letter No.	Nil, dated 28.08.201	4.			
10						
S. NO.	Minimum Standards on fire prevention and fire safety U/R 33	Old NOC Requirement	Provided at site	Remarks MR / NMR		
1	Access to building					
	1) Road width	6m	140			
1	2) Gate width	Required	12m	MR		
	3) Width of internal road	N/A	Provided	MR		
2	Number, width Type & arrangement of			N/A		
	a. Number of staircases	CAITS				
	1. Upper floors	04Nos.	04nos.	MR		
	2. basements	03nos.in one basement &5nos in 2nd basement.	03nos.in one basement &5nos in 2nd basement.	MR		
	b. Width of staircase					
	1. Upper floors	1.5m (Each)	1.3m,1.05,1.05&1.10m	MR(Old case)		
	2. basements	1.5(Each)	1.3m,1m,1m,1m &1.7m.in one basement and 1.5,1.5&1.18m in	MR(Old case)		
	c. Protection of exits		2nd basement.			
	1. Fire check door	N/A				
	2. Pressurization	N/A	N/A	N/A		
	d. No. of continuous staircase to	Required	N/A 1no.	N/A		
	terrace	oquii ou	mo.	MR		
	e. Width of corridor	N/A	N/A			
	f. Door size	1 Mtr	Provided	N/A		
3	Compartmentation.	·	Frovided	MR		
		N/A	N/A	NI/A		
		N/A	N/A	N/A		
		N/A	N/A	N/A N/A		
		N/A	N/A	N/A		
		N/A	N/A			
4	Smoke Management system.		1.47	N/A		
		30 a/c per hour 12 a/c per hour	Exhaust fans provided	MR		
	upper floors	***	N/A	N/A		

his

N/3

	5	Fire Extinguishers					1	
		total numbers					1.3	
		Types		40nos.		40nos.	1	
		ISI marking						MR
	6	First Aid Hand		1		ABC & Water CO2	4	MR
		First-Aid Hose Reels.			12	ISI Mark	118	MR
		total numbers on each floor		04nos.			1	IMIL
		Length of Hose reel hose		30 m		04nos.	2	MD
	-	Nozzle Diameter				30m	-	MR
	7	Automatic fire detection and alar	rmina	5 mm		5mm	- 4	MR
1	- 1	Type of detectors						MR
	- 1	location of Main Panel		N/A		N/A		
1	1	ocation of Repeater panel	1	V/A		N/A	- 1	N/A
	1	Alternate source of power	. 1	V/A		N/A	5 14	N/A
	Ir	nooter's location	N	I/A				N/A
		MOEFA	N	I/A		N/A		N/A
	- 11			//A		N/A		N/A
	-	ublic Address System.		/A		N/A		N/A
	U A	utomatic Sprinkler System	- IN	/^		Provided		
	l Da	asement						N/A
	up	pper floors		equired	F	Provided		
		rinkler above false ceiling	N/	Ά		1/0		MR
11	1 In	ternal Hydrants	N/.	A		J/A		N/A
	Si	79 of rices/1				1/A		N/A
	NI.	ze of riser/down-corner	100	0mm	T.		1	
	livu	mber of Hydrants per floor		Vos.		00mm		MR
40	1108	se Box			0	4nos.		
12		rd Hydrants.	1041	Vos.	02	Inos.		MR
	tota	al number of hydrants						MR
	hos	e box	N/A		N/	A		
13	Pur	nping arrangements	N/A		N/A			N/A
	1. G	round level						N/A
	la. D	ischarge of		N/A			(1)	
	h Ho	ischarge of main Pump	N/A		NI//	N/A		V/A
	0.116	ead of main pump	N/A	2	N/A			V/A
	C.Nu	mber of main pumps	N/A		N/A			J/A
	d.joc	key pump out put	N/A		N/A		2.1/	I/A
	e.joc	key pump head			N/A		1.	
	f. Sta	indby Pump output	N/A		N/A			I/A
	g.Sta	nby Pump head	N/A		N/A			/A
	h.Aut	o Starting/Manual stopping	N/A		N/A		N	/A
	pump	house access	N/A		N/A		N,	/A
	2 Town	nouse access	N/A	49			N/	'A
	a Die	race level		-	N/A		N/	Α
	a. Dis	charge of pump	450LP	M(Fach) Oans	1501			
	16.6		.+03nd	os jockey.	3 450L	PM(Each),03nos.+03nos	MF	3
	b. hea	d of the pump	40 mtr	,	Jocke	y.		
	c. Pow	er supply				Each)	MF	
	d. Auto	starting of pump	Requir		Provid	ded	MA	
4	1		Require	ed	Provid	ded		
-	Captiv	e water storage for fire fighting					MR	61
	i. Und	erground tank capacity	N/A					*
	a. Drav	v-off connection			N/A		N/A	
	b. fire s	ervice inlet	N/A		N/A			
		ss to tank	N/A	14	N/A		N/A	2
1		ead tank Capacity	N/A		N/A	Barrier Committee	N/A	
	Over ne						N/A	

		location of Main Panel	,,	IN/A	- V	
		location of Repeater panel	N/A	N/A		N/A
		Alternate source of power	N/A	N/A		N/A
		hooter's location	N/A	N/A		N/A
	8	MOEFA	N/A	N/A		N/A
	9	Public Address System.	N/A	N/A		N/A
	10	Automatic Sprinkler System.	N/A	Provided	- 1	N/A
		basement		. vevided		N/A
		upper floors	Required	Provided	100	
			N/A	N/A		MR
1	1	sprinkler above false ceiling	N/A	N/A		N/A
		Internal Hydrants		INA		N/A
		Size of riser/down-corner	100mm	100		
		Number of Hydrants per floor	04Nos.	100mm		MR
12		hose Box	04Nos.	04nos.		MR
1		Yard Hydrants.		04nos.		MR
		total number of hydrants	N/A	N/A		
13		hose box	N/A	N/A		N/A
13		Pumping arrangements		N/A		N/A
		. Ground level	N/A		3)	
	la	a. Discharge of main Pump	N/A	N/A	1	V/A
	þ	.Head of main pump	N/A	N/A		V/A
	C.	Number of main pumps	N/A	N/A		V/A
	d.	jockey pump out put	N/A	N/A	2007	I/A
	e.	jockey pump head	N/A	N/A		I/A
	f.	Standby Pump output	N/A	N/A	1 2 -	I/A
	g.	Stanby Pump head	N/A	N/A	1	/A
	h./	Auto Starting/Manual stopping	N/A	N/A		/A
	pu	imp house access	N/A	N/A	N	
	2.1	Terrace level	IN/A	N/A	N,	
	a.	Discharge of pump	4501 PM/Each) 00		7	
			.+03nos jockey.	os 450LPM(Each),03nos.+03nos	M	R
	b. I	head of the pump	40 mtr(Each)	јоскеу.		*
		Power supply	Required	40m(Each)	MF	3
	d. /	Auto starting of pump	Required	Provided	MF	3
14	1		ricquired	Provided	MF	3
	1 1	otive water storage for fire fighting		-		
	2 0	Underground tank capacity	N/A	N/A		
		Praw-off connection	N/A	N/A	N/A	
		re service inlet	N/A	N/A	N/A	
		ccess to tank	N/A	N/A	N/A	
15	Evit	r head tank Capacity	10000 Ltr.each(3nos)	10000Liters each(3nos.)	N/A	
16	Dra	Signage.	Required	Provided	MR	X
10		vision of lifts.		i Tovided	MR	
	a. Pr	essurization of lift shaft	N/A	N/A		•
	b. pri	essurization of lift lobby	N/A	N/A	N/A	
	d -	mmunication in lift car	N/A	N/A	N/A	
	u. Fir	eman's grounding switch	11/4	N/A	N/A	
17	e. Lift	t signage	1/4	N/A	N/A	
17	Stand	Thy nower community	1/0	N/A	N/A	
			1	I V/A	N/A	No.
				<u></u>		_
			Mac >			
					-11	

18	Refuge Area.		Not Required	
	total area	N/A	N/A	N/A
	location	N/A	N/A	N/A
19	Fire control room			
	a. detector system Panel	N/A	N/A	N/A
	b. Flow switch Panel	N/A	N/A	N/A
	c. PA system Panel	N/A	N/A	N/A
	d. Batter backup	N/A	N/A	N/A
	e. Building floor plans	N/A	N/A	N/A
20	Special Fire Protection systems fo	r protection of spec	ial risks, if any: N/A	

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the NOC issued vide letter No.F.6/DFS/MS/2009/1264, dated 08.05.2009 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name: Vedpal

Designation: ADO

D.O. (South)

16/10/14