GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

NO. FA | DFS | MS | 4H | 2014 | 52 / 1364

Dated: 03.11, 2014

FIRE SAFETY CERTIFICATE

Issued on ... 3: 11:2014 at New Delhi by.

(Dr. G.C. Misra) Chief Fire Officer Delhi Fire Service Ph:- 011-23414333

Copy to:-.

- 1. The Joint. Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049.
- 2. M/S Blue Sapphire Guest House, located at A-23, Street No.-01, Mahipalpur, New Delhi-110037

Conditions for the validity of fire safety certificate are overleaf:-

INSPECTION REPORT 1. Name & address of the building : M/S Blue Sapphire Guest House, located at A-23, Street No.-01, Mahipalpur, New Delhi-110037. 2. Building is comprised of : B+G+3, (Basement storage, Ground floor reception, office & Pantry , 1st floor 13 guest rooms, 2nd 13 guest rooms & 3rd floor 12 guest rooms. Total 38 guest rooms. 3. Type of Occupancy : Lodging House 4. Type of Case : Old Case 5. Details of Previous NOC : No.F.6/DFS/MS/GH/2011/2007, dated-17.08.2011. 6. Fire Safety direction letter No :Nil. 7. Date of Inspection : 18.10.2014 8. Name of the Inspecting Officers: : Vedpal (ADO) 9. Name and designation of officer from the building side : Sh. Devender Singh (Owner) 10. Year of Construction :2004. 11. Applicant's letter No. : No.Nil, dated 09.10.14. Minimum Standards on fire S.N Old NOC Provided at prevention and fire safety U/R33 Remarks Requirements 1 Site Access to building Road width 12m 12 m Gate width MR N.A. N.A. Width of internal road N.A. N.A. N.A. Number, Width, Type and Arrangement of Exits. 2 N.A. Number of Staircases Upper Floor 02nos. 02nos. Basement MR 02nos. 02nos. B. Width of Staircases MR Upper Floor 1.5m &1.1m 1.5m &1.1m Basement MR 1.5m & 1.1m 1.5m & 1.1m c. Protection of exits MR Required Fire check door in basement only Provided MR Required Provided Pressurization MR N.A. e. No. of continuous staircases N.A. N.A. 1no. 1no. to terrace MR g Width of Corridor N.A. N.A. h Door Size N.A. N.A. N.A. N.A. 3 Compartmentation Fire check door Required Provided in basement only Sealing of electrical shafts MR N.A. N.A. Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. Smoke Management System. N.A. Basement 30a/c per hour Provided exhaust fans Upper floor MR 12 a/c per hour N.A. N.A.

110

5.	Fire Extinguisher							
	Total numbers	12 nos.	25 nos.	MR				
	types	WCO ₂ & ABC	WCO ₂ & ABC	MF				
	IS marking	ISI marked	ISI marked	MF	-			
6	First-aid-Hose Reels.							
	Total numbers of each floor	01no.	01no.	MF	3			
	Length of hose reel hose	30 m	30m	MF				
	Nozzle diameter	5mm	5mm	MF				
7	Automatic fire detection and alarming system.							
	Type of detectors	N.A.	N.A.	N.A	<u> </u>			
	Location of main panel Location of repeater panel Alternate source of power Hooters	N.A.	N.A.	N.A				
		N.A.	N.A.		100			
		N.A.		N.A.				
		S. Savissi and	N.A.	N.A.				
3	MOEFA	N.A.	N.A.	N.A				
)		Required	Provided	MA				
0	Public address System.	Required	Provided	MR				
0	Automatic Sprinkler System. Basement	T						
	upper floor	Required	Provided	MR				
	sprinkler above false ceiling	N.A.	N.A.	N.A.				
		N.A.	N.A.	N.A	١.			
1	Internal Hydrants							
	size of riser/down-comer	100mm	100mm	MR	L			
	Number of hydrants per floor	01no.	01no.	MR	1			
	Hose Box	01no.	01no.	MR				
2	Yard Hydrants.							
	Total number of hydrants	N.A.	N.A.	N.A.				
	Hose Box	N.A.	N.A	N.A				
3	Pumping Arrangements.							
	 Ground Level 	N.A.	N.A.		N	.A.		
	Discharge of main Pump	N.A.	N.A.		N	.A.		
	> Head of Main Pump	N.A.	N.A.	151	N	.A.		
	Number of main pumps	N.A.	N.A.	3	Ņ	.A.		
	Jockey pump out put	N.A.	N.A.		N	.A.		
	Jockey pump headStandby pump out put	N.A.	N.A.		N	.A.		
	, partipodi pat	N.A.	N.A.		N	.A.,		
	 Standby pump Head Auto Starting /Manual stopping Pump House Access 	N.A.	N.A.	ž.,	N	.A.		
		N.A.	N.A.	·	N	.A.		
	Terrace Level	N.A.	N.A.	V.A.		.A.		
	Discharge of pump	Required	Provided		M	R		
	Head of the Pump	450 LPM(02nos.)	450LPM(02nos.)		M	R		
	Power supply	40 Mtrs.	40Mtrs.			R		
	Auto Starting of pump	Required	Provided		M	R		
	and a bamb	Required	Provided		M	R		

M/S Blue Sapphire Guest House, located at A-23, Street No.-01, Mahipalpur, New Delhi-110037.

Captive Water Storage for Fire Fighting.						
Underground tank capacity	N.A.	N.A.	N.A.			
Draw-off connection	N.A.	N.A.	N.A.			
Fire service inlet	N.A.	N.A	N.A.			
	N.A.	N.A.	N.A.			
Overhead Tank capacity	15000Ltrs.	15000Ltrs.	MR			
Exit Signage.	Required	Provided	MR			
Provision of Lifts.	N.A.	Provided	MR			
Pressurization of Lift Shaft	N.A.	N.A.	N.A.			
Pressurization of Lift lobby	N.A.	N.A.	N.A.			
	N.A.	N.A.	N.A.			
	Required	Provided	MR			
Lift Signage	Required	Provided	MR			
Standby power supply	Required	D.G. Set	MR			
Refuge Area.						
Total area	N.A.	N.A.	N.A.			
Location	N.A.	N.A.	N.A.			
Fire Control Room						
Detector system panel	N.A.	N.A.	N.A.			
Flow switch panel	N.A.	N.A.	N.A.			
PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.			
	N.A.	N.A.	N.A.			
	N.A.	N.A.	N.A.			
Special Fire Protection systems for	N.A.	N.A.	N.A.			
of special Risks, if any:						
	Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage Standby power supply Refuge Area. Total area Location Fire Control Room Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans Special Fire Protection systems for	Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage Standby power supply Refuge Area. Total area Location Detector system panel PA system panel Batter backup Building Floor Plans N.A. N.A.	Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization in lift car Firemen's grounding switch Lift Signage Standby power supply Refuge Area. Total area Location Detector system panel PA system panel Batter backup Building Floor Plans N.A. N.A. N.A. N.A. N.A. N.A. N.A. N.			

The fire protection systems provided in the building were test checked randomly and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the NOC issued vide letter No.F.6/DFS/MS/GH/2011/2007 dated 17.08.11 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

20/10/14

Signature of the Inspecting Officer

Name : Vedpal

Designation: ADO

Divisional Officer (South)