GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/MS/2014/W2/1371

Dated 05 11 14

FIRE SAFETY CERTIFICATE

Certified that a Restaurant on ground floor and basement for storage in the name of Haldiram at A-17 Industrial Area, Najafgarh Road, Moti Nagar, New Delhi 110015 of a premises comprised of basement + ground floor + 2 upper floor only owned / occupied by Gagandeep Mahindru have complied with the fire prevention and fire safety requirement in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 22.09.2014 in the presence of Sh. Awasthi (G.M.) and that the building/premises is fit for occupancy Assembly excluding first and second floor with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire service rule, 2010.

(Santokh Singh) Chief Fire Officer Tel. No. 23414250 cfowz.dlfire@nic.in

Copy to:

 Gagandeep Mahindru B-2, Kirti Nagar, New Delhi Following fire safety directives must be adhered to:-

- 1) All the means of escape shall be kept free of all type of obstruction all the time.
- 2) All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3) All the fire fighting equipment shall be maintained in perfect working condition all the time and lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4) Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.
- 5) Basement shall be used as per NBC.
- 6) This NOC may not be treated in any case for regularizations of unauthorized construction, if any.
- 7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 8) "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

Basement - Storage, G.F.- Restaurant

Second Floor = Office purpose Hot yet readly

Name & address of the building 1.

: A-17 Industrial Area, Najafgarh Road, Moti Nagar, New Delhi-15

Type of Occupancy 2.

: Assembly - Restaurant at GF and basement for storage in the name of Haldiram's of Sons

Type of Case 3.

New

Details of previous NOC 4.

Nil

Fire Safety directives letter No. 5.

F6/DFS/MS/BP/2014/ 1702 dated 25.07.14

Date of inspection 6.

22.09.2014

Name of the Inspecting Officers 7.

D.O. (WZ) Sunil Chawdhary

8.

Name and designation of officers

From the building side

Sh. Awasthi (G.M.)

Year of Construction

2010

10. Applicant's letter No.

: nil dated 27. 08. 2014

NOC for ground floor only (Assembly)

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No.	Min Preve	nimum Standards on fire ntion and fire safety U/R 33	BBL/NBC Requirement	Provided at site	Remarks MR/NMR	
1.	Access to building					
	•	Road width	09mtrs	60 mtr	M.R.	
	•	Gate width	4.5 mtr	Provided	M.R.	
	•	Width of internal road	As per section plan	Provided	M.R.	
2.	Number, Width, Type & Arrangement of Exits			1, 1 2, 11, 12, 13, 14, 15, 15, 15, 15, 15, 15, 15, 15, 15, 15		
	a. Ni	umber of staircases			1.	
		Upper Floors	2	2 2	M.R.	
		Basement	2 2	2	M.R.	
	b. V	Width of staircases			N.D.	
		Upper Floors	N.R. N.R.	N.R.	N.R.	
	c. F	Basement Protection of exits	14.14.			
is .	C. 1	Fire check door	required	Provided	M.R.	
1		 Pressurization 	N.R.	N.R.	N.R.	
	1	No. of continuous staircases to terrace				
	e.	Width of Corridor	1.5 mtr.	Halls only	M.R.	
	f.	Door size	2x2 mtr for Restaurant	Provided	M.R.	
3.	Compartmentation.					
	•	Fire check door	Required	Provided	M.R.	
	•	Sealing of electrical shafts	Required Required	Provided Provided	M.R.	
	•	Fire Rating of shaft door	Required	11011000		

	Fire Dampers	N.R.	N.R.	N.R.		
4.	Smoke Management System.				3	
	Basements	Required	Provided	M.R.		
	I I I I I I I I I I I I I I I I I I I	Required	Provided	M.R.	7	
5.	• Upper floors Fire Extinguishers		*			
	Total numbers	10 for Basement + ground floor only	12	M.R.		
	• Types	ABC & CO ₂ type	Provided	M.R.		
	IS marking	ISI marks required	Provide	M.R.		
6.	First-Aid Hose Rees.	4				
	Total numbers on each floor	02	02	M.R.		
	Length of hose reel hose	30 m required	Provided	M.R.		
	Nozzle diameter	5 mm required	Provided	M.R.		
7.	Automatic fire detection and alar	ming system.	4			
	Type of detectors	Required	Provided	M.R.		
	Location of Main Panel	G.Floor	Provided			
		N.R.	N.R.	M.R N.R.		
	Location of Repeater PanelAlternate source of power	Required	Provided	M.R.		
	-	•				
0	Hooter's Location	Required	Provided	M.R.		
8.	MOEFA	Required	Provided	M.R.		
9.	Public Address System.	Required	Provided	M.R.		
10.	Automatic Sprinkler system		Ü		_	
	Basement	Required	Provided	M.R.	-	
	Upper Floor	N.R.	N.R.	N.R.		
1	 Sprinkler above false ceiling 	Required if basement have ceiling	No ceiling in basement	M.R.		
11.	Internal Hydrants					
	Size of riser/down-comer	Δ.			12 .	
•	Size of riser/down-come	150 m.m.	Provided	M.R.		
	 Number of hydrants per floor 	2	2	M.R.		
	Hose Box	2	2	M.R.		
12.	Yard Hydrants.					
	Total number of hydrants	04	Provided	M.R.	-1	
	Hose Box	04	Provided	M.R.		
13.	Pumping Arrangements.		* A			
	Ground Level	3-				
	D:	2280 LPM	Provided	M.R.		
	Discharge of main pumpHead of Main pump	2200 Li W	Tiovided	IVI.IC.		

	Number of main pumps	UZ.	02	112.20
	> Jockey Pump out put	180 LPM	Provided	M.R.
	> Jockey pump head	50 mtr	Provided	M.R.
	> Standby pump out put	2280 LPM	Provided	M.R.
	> Standby pump Head	50 mtr	Provided	M.R.
	> Auto Starting/Manual	required	Provided	M.R.
	stopping > Pump Hose Access	Required	Provided	M.R.
	Terrace level			
	> Discharge of pump	900 LPM	Provided	M.R.
	➤ Head of the pump	50 mtr	Provided	M.R.
	> Power supply	Required	Provided	M.R.
	> Auto Starting of pump	required	Provided	M.R.
14.	Captive Water Storage for fire fighti	ng.	n	
	Underground tank capacity	50,000 ltrs	Provided	M.R.
	> Draw -off connection	Required	Provided	M.R
		Required	Provided	M.R
	> Fire service inlet	Required	Provided	M.R
	> Access to tank	required		
	Overhead Tank Capacity	10,000 ltrs	Provided	M.R.
15	Exit Signage.	Required	Provided	M.R.
16.	Provision of Lifts			
		N.R.	N.R.	N.R.
	Pressurization of Lift Shaft	N.R.	N.R.	N.R.
	Pressurization of Lift lobby	N.R.	N.R.	N.R.
	Communication In lift Car	11.12.	0	
	Fireman's Grounding	N.R.	N.R.	N.R.
	Switch • Lift Signage	N.R.	N.R.	N.R.
177	Standby power supply	Required	Provided	M.R
17.	Standby power suppry	Roquirou		
18.	Refuge Area			
	> Total Area	N.R.	N.R.	N.R.
	> Location	N.R.	N.R.	N.R.
19.	Fire Control Room	Alex.		
	> Detector System Panel	Required	Provided	M.R
	> Flow Switch Panel	Required	Provided	M.R
	> PA system Panel	Required	Provided	M.R
		Required	Provided	M.R
	> Batter backup	Required		

11-6

20.	Special Fire Protection Systems for	N.R.	N.R.	N.R.	
	Protection of special Risks, if any:		6		

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chawdhary

Name

Designation D.O. (M.N.)

Designation

DYLFB-