GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/PFS/MS/Hospital/2014/ SZ/1224

FIRE SAFETY CERTIFICATE

Certified that Indraprastha Apollo Hospitals located at Sarita Vihar, Mathura Road, New Delhi comprised of two blocks (OPD Block and Main Block). Main block is comprised of two tier basements, ground plus six upper floors & OPD block is comprised of two tier basements, ground, service floor plus four upper floors and was granted Fire Safety Certificates by this department vide letter Nos. F.6/DFS/MS/Hospital/2011/2091 dated 26.08.2011 and F.6/DFS/MS/Hospital/2012/2454 dated 10.07.2012. The hospital was re-inspected by the officers concerned of this department on 16-08-2014 in presence of Mr. Dinesh Nehra, Fire Officer and found that the said hospital have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class **Group-C Institutional Building** (Hospital) with effect from 19/09/19 for a period of 3 (three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules, 2010 subject to conditions as mentioned below.

Issued on 19/09/14 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Chief Engineer, Indraprastha Apollo Hospitals, Sarita Vihar, Mathura Road, New Delhi.

Conditions for the validity of fire safety certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- 3. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- 4. The basement shall be used as per the provisions of Building Bye Laws.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in
- 6. * Fire check doors in staircases and lift lobbies, sprinkler system, detection system, ventilation system etc. in left out areas within 06 months shall be installed under intimation to this department.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building :Main Building & OPD block, Indraprastha Apollo Hospital,

Mathura Road, New Delhi

2. Type of Occupancy

: Institutional

3. Type of Case

: Renewal

4. Details of previous NOC

: Letter No. F.6/DFS/MS/Hospital/2011/2091 Dated: 26.08.2011

Letter No. F.6/DFS/MS/Hospital/2012/2454Dated: 10.07.2012

5. Fire Safety directives letter No : Letter No. F.6/DFS/MS/BP/Hospital/2010/3455 Dated: 31.12.2010

6. Date of inspection

: 30-08-2014

7. Name of the Inspecting Officers: Atul Garg(DCFO), Dharampal Bhardwaj (DO, SZ), M.K.Chattopadhyay, ADO(CC)

8. Name and designation of officers

from the building side

: Mr.Dinesh Nehra, Fire Officer

9. Year of Construction

: 1996

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirem	ent	Provided at site	Remarks MR/NMR	
1	Access to building					
	Road width	09 mts	5	provided	MR	
0	• Gate width	4.5 mts		Provided	MR	
	Width of internal road	06 mts	2: %	Provided	MR	**
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases			-		2
	Upper Floors	OPD-5, Mair		provided	MR	
	Basements	OPD-04 + ramp, Main		Provided	MR	
	b. Width of staircases	-		-	-	3
	• Upper Floors	Old case		0-1.07 mts(02), 2.0 mts(0 nin-1.05(3), 1.08(1), 1.55	(2), 1.87(1)	MR
	• Basements	Old case		OPD-1.07 mts(02), 1.0 Main- 1.05(4), 1.79(2),		MR
	c. Protection of exits					
	Fire check door	Required	<u> </u>	Provided	MR	
	 Pressurization e. No. of continuous staircases to terrace g. Width of Corridor 	Required		Provided	MR	
		OPD-4, Main-6		provided	MR	
		2.4 mts		Provided	MR	
	h. Door Size	2.0 mts		Provided	MR	
		11				

3	Compartmentation					
	• Fire check door	D				
		Required	Provided		MR	
	 Sealing of electrical shafts Fire Rating of shaft door 	Required	Provided		MR	
	Fire Rating of shaft doorWater Curtain	Required	Provided		MR	
	Fire Dampers	N/A	N/A		N/A	
		Required	Provided		MR	
4	Smoke Management System.					
5	BasementsUpper floors	30 a/c per hou 12 a/c per hou		12	MR	
			Provided		MR	
5	Fire Extinguishers					
	 Total numbers 	717	Provided		MR	
	• Types	WCO ₂ , CO ₂ , clea agent, water mis		MR		
	IS marking	, -	Provided	I	MR	
	First-Aid Hose Reels.					
2	Total numbers on each floorLength of hose reel hose	OPD-5, Main-8	Provided	MR		
		30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
	Automatic fire detection and alarming system.					
	Type of detectors	Smoke/heat	Provided	N	⁄IR	
	Location of Main Panel	Required	Provided	N	1R	
	Location of Repeater Panel	Each floor	Provided	N	1R	
	Alternate source of power	Required	Provided	N	1R	
	Hooters' Location	All areas	Provided	Provided MR		
	MOEFA	Required	Provided	Provided N		
	Public Address System.	Required	Provided	M	IR	
	Automatic Sprinkler System.					
	• Basement	Required	Provided		MR	
×	 Upper Floor Sprinkler above false ceiling	Required	Provided except (OPD-Gr, 1st floor), (Main-Gr, 1st & 2nd floor)		MR	
	acore raise centing	Required	Provided	Provided		
	Internal Hydrants					
	Size of riser/down-comer	150 mm	Provided	M	D	

8	Number of hydrants per floor	Main-8, OPD-5	Provided	MR		
	Hose Box	Main-8, OPD-5	Provided	MR		
12	Yard Hydrants.					
	Total number of hydrants	15	Provided	MR		
	Hose Box	15	Provided	MR		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	4950, 3132 LPM	Provided	MR		
	Head of Main pump	84.5 mts	Provided	MR		
	Number of main pumps	04	Provided	MR		
	Jockey Pump out put	550 LPM	Provided	MR		
	Jockey pump head	79.5 mts	Provided	MR		
	> Standby Pump out put	2500 LPM	Provided	MR		
	Standby Pump Head	84.5 mts	Provided	MR		
	➤ Auto Starting/ Manual stopping	Required	Provided	MR		
	Pump House Access	Required	Provided	MR		
	 Terrace level Discharge of pump 	N/A	N/A	N/A		
		950 LPM	Provided	MR		
	Head of the pumpPower Supply	50 mt	Provided	MR		
	Auto Starting of pump	Required	Provided	MR		
	Trace Stateming of pump	Required	Provided	MR		
	Captive Water Storage for fire fighting.					
	Underground tank capacity	5,70,000 lts	Provided	MR		
	> Draw-off connection	Required	Provided	MR		
	> Fire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided	MR		
8	Overhead Tank capacity	1,00,000 liters	Provided	MR		
	Exit Signage.	Required	Provided	MR		
,	Provision of Lifts.					
	Pressurization of Lift Shaft	Required	Provided	MR		
	Pressurization of Lift lobby	Required	Provided	MR		

-