GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. Fibrilms/ Enlow wz 1357

Dated: 31 / to /2014

FIRE SAFETY CERTIFICATE

Following fire safety directives must be adhered to:-

1) All the means of escape shall be kept free of all type of obstruction all the time.

2) All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3) All the fire fighting equipment shall be maintained in perfect working condition all the time and lapse rendering non-functional of fire safety measures, management shall be responsible.

4) Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5) Basement shall be used as per NBC.

6) This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs. delhigovt. nic.in.

8) "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

Issued on 31/(0) at New Delhi by

(Santokh Singh) Chief Fire Officer Delhi Fire Service

E-mail: cfowz.dlfire@nic.in

0/1 da

Copy to: Mr. Sameer Mittal, Mohan Leela Eating House/restaurant A-8/3, Wazirpur Ind. Area, Delhi

Renewal-

1. Name & address of the building

: Mohan Leela Eating House/restaurant at First floor, A-8/3, Wazirpur Ind. Area, Delhi (basement+G+ 2 upper floors)

Class D (Assembly) New Renewal

2 Type of Occupancy Type of Case

Details of previous NOC

Fire Safety directives letter No. 5.

6. Date of inspection

Name of the Inspecting Officers 7. Name and designation of officers

From the building side

Year of Construction 10. Applicant's letter No. F.6/DFS/MS/EH/2011/1127 dated 08/06/2011

17-09-2014

ADO (W.P) & DO (M.N.)

Mr. Sameer Mittal

1990 Nil dated Nil

INSPECTION REPORT

Point wise fire safety arrangem

S. No.	rieve	nimum Standards on fire ntion and fire safety U/R	NBC Requirement	Provided at sit	e Remarks
1.	Access	to building	requirement		MR/NMR
	•	Road width	06mtrs		
	•	Gate width	required	Provided	M/R
				Provided	M/R
2.		Width of internal road	N.A.	· N.A.	
	Numbe	r, Width, Type & Arra	ngement of Exits		N.A.
	a. Nur	mber of staircases	DAILS		
		Ilnnas Cl			
		• Upper Floors	Two	Provided	M/R
		Describent	Two	Provided	
	b. Wie	dth of staircases			M/R
	•	Upper Floors	Old case	Old case	
		Basement	Old case	Old case	Old case
	c. Pro	tection of exits		Old case	Old case
	•	Fire check door	Required		1.
	•	Pressurization	N.A.	Provided	M.R.
	d. No.	of continuous staircases		N.A.	N.A
	to te	rrace	one	Provided	M/R
		th of Corridor	required	0	WIK
	f. Door		Old case	Open hall	M.R
C	omparti	nentation.		Old case	M.R.
-					
	 Fire check door 		N.A.		
1	• Seal	ing of electrical shafts	N.A.	N.A.	N.A.
•		Rating of shaft door	IV.A.	N.A.	N.A.
		er Curtain	N.A.	N.A.	
		Dampers	N.A.		N.A.
		oampers .	N.A.	N.A.	N.A.
Sm	oke Ma	nagement System.	14.24.	N.A.	N.A.
e					
	Dasei	Hents	30 a/c per hour	Exhaust C	
	Unner	floors		Exhaust fans Provided	M.R
Minto			12 a/c per hour	D	
Fire	e Exting	uishers	3	TOVIDED	M.R.
	Total				
-		numbers	17	Descript 1	
•	Types	1	ARC 51- 9 CO	Provided	M.R
	IS mar	king	ABC -5 kg & CO ₂ 4.5 kg	Provided	MR

Trom the building side Mr. Sameer Mittal

9. Year of Construction10. Applicant's letter No.

1990

Nil dated Nil

INSPECTION REPORT

Point wise fire safety arrangements/equipments are mentioned as under:-

S. No	Minimum Standards on fire Prevention and fire safety U/R 3.	NBC Pagning	Provided at site	Remarks		
1.	Access to building	Requirement		MR/NMR		
	Road width	06mtrs				
	Gate width	required	Provided	M/R		
			Provided	M/R		
2.	Width of internal road	N.A.	N.A.	N.A.		
•	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases					
	Upper Floors	Two	Provided	1.500		
	Basement	Two	Provided	M/R		
	b. Width of staircases		Flovided	M/R		
	Upper Floors	Old case	011			
	Basement	Old case	Old case	Old case		
	c. Protection of exits	0.100 0000	Old case	Old case		
	Fire check door	Required				
	Pressurization	-	Provided	M.R.		
	d. No. of continuous staircases	N.A.	N.A.	N.A		
	to terrace	one	Provided	M/R		
	e. Width of Corridor	required	Open hall	MD		
	f. Door size	Old case	Old case	M.R.		
	Compartmentation.		0.14 0450	IVI.K.		
	Fire check door					
	THE CHECK GOOT	N.A.	N.A.	N.A.		
	of ciccurcai sharts	N.A.	N.A.	N.A.		
	Fire Rating of shaft door	N.A.	N.A.	N.A.		
	Water Curtain	N.A.	N.A.	· · · · · ·		
	Fire Dampers	N.A.		N.A.		
-	Smoke Management System.	IV.A.	N.A.	N.A.		
-						
-	Basements	30 a/c per hour	Exhaust fans	M.R		
	Upper floors	10 1	Provided			
4		12 a/c per hour	Provided	M.R.		
	Fire Extinguishers					
	Total numbers	17	Provided			
-	• Types			M.R		
	IS marking	ABC -5 kg & CO ₂ 4.5 kg	Provided	M.R		
-	Eine A' III	ISI marked	Provided	M.R		
+	First-Aid Hose Reels.					
	Total numbers on each floor	01	Provided	MD		
	 Length of hose reel hose 	30 m required	Provided	M.R M.R		
			1.011404	IVI.IX		

	Nozzle diameter	5 mm	Provided	M.R			
7.	Automatic fire detection and alar	ming system.					
		52	N.R.	N.R.			
	Type of detectors	N.R.	N.R.	N.R.			
	Location of Main Panel	N.R.	N.R.	N.R.			
	Location of Repeater Panel	N.R.	N.R.	N.R.			
	Alternate source of power	N.R.	N.R.	N.R.			
	Hooter's Location	IV.R.	14.12.	14.11.			
8.	MOEFA	Required	Provided	M.R			
9.	Public Address System	Required	Provided	M.R			
10.	Automatic Sprinkler system	Required	Provided	M.R			
	Basement	Required	Provided	M.R			
	Upper Floor	Required	Provided	M.R			
	Sprinkler above false ceiling	N.R.	N.R.	N.R.			
11.	Internal Hydrants						
	Size of riser/down-comer	100 mm	provided	M.R			
	Number of hydrants per	two	provided	M.R.			
	floor	two	provided	M.R			
12.	Hose Box						
14.	Yard Hydrants.						
	Total number of hydrants	N.R.	N.R.	N.R.			
	Hose Box	N.R.	N.R.	N.R.			
13.	Pumping Arrangements.			1			
11-12-20-20-20-20-20-20-20-20-20-20-20-20-20	Ground Level						
	Discharge of main pump	N.A.	N.A.	N.A.			
	Head of Main pump	N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
	Jockey Pump out put	N.A.	N.A.	N.A.			
	T11-1			The second secon			
	> Jockey pump head	N.A.	N.A.	N.A.			
	> Standby pump out put	N.A.	N.A. N.A.	N.A. N.A.			
	Standby pump out putStandby pump Head	N.A.	N.A.	N.A.			
	> Standby pump out put	N.A.	N.A.	N.A.			
	 Standby pump out put Standby pump Head Auto Starting/Manual 	N.A.	N.A.	N.A.			
	 Standby pump out put Standby pump Head Auto Starting/Manual stopping 	N.A. N.A.	N.A. N.A. N.A.	N.A. N.A. N.A.			
	 Standby pump out put Standby pump Head Auto Starting/Manual stopping Pump Hose Access 	N.A. N.A.	N.A. N.A. N.A.	N.A. N.A. N.A.			
	 Standby pump out put Standby pump Head Auto Starting/Manual stopping Pump Hose Access Terrace level	N.A. N.A. N.A.	N.A. N.A. N.A.	N.A. N.A. N.A.			
	 Standby pump out put Standby pump Head Auto Starting/Manual stopping Pump Hose Access Terrace level Discharge of pump 	N.A. N.A. N.A. N.A. 450 LPM & 225 LPM	N.A. N.A. N.A. Provided	N.A. N.A. N.A. M.A.			

	Hooter's Location	3 11851				
8.	MOEFA	Required	Provided	M.R		
9.	Public Address System	Required	Provided	M.R		
10.	Automatic Sprinkler system	Required	Provided	M.R		
	Basement	Required	Provided	M.R		
	Upper Floor	Required	Provided	M.R		
	Sprinkler above false					
	ceiling	N.R.	N.R.	N.R.		
11.	Internal Hydrants					
	Size of riser/down-comer	100 mm	provided	M.R		
	Number of hydrants per	two	provided	M.R.		
	floor	two	provided	M.R		
	Hose Box					
12.	Yard Hydrants.					
	Total number of hydrants	N.R.	N.R.	N.R.		
	Hose Box	N.R.	N.R.	N.R.		
13.	Pumping Arrangements.					
	Ground Level					
	Discharge of main pump	N.A.	N.A.	N.A.		
	Head of Main pump	N.A.	N.A.	N.A.		
	Number of main pumps	N.A.	N.A.	N.A.		
	Jockey Pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	> Standby pump out put	N.A.	N.A.	N.A.		
	Standby pump Head	N.A.	N.A.	N.A.		
	 Auto Starting/Manual stopping 	N.A.	N.A.	N.A.		
	Pump Hose Access	N.A.	N.A.	N.A.		
	Terrace level			2		
	Discharge of pump	450 LPM & 225 LPM	Provided *	M.R.		
	> Head of the pump	40 mtr	Provided	M.R.		
	Power supply	Required	Provided	M.R.		
	➤ Auto Starting of pump	Required	Provided	M.R		
14.	Captive Water Storage for fire fighting.					
	Underground tank capacity	N.A.	N.A.	N.A.		
	> Draw -off connection	N.A.	N.A.	N.A.		
	> Fire service inlet	N.A.	N.A.	N.A.		
	> Access to tank	N.A.	N.A.	N.A.		
	Overhead Tank Capacity	5,000 ltrs	Provided	M.R		

15	Exit S	signage.	required	Provided	M.R.
16.	Provi	sion of Lifts			
	• I	ressurization of Lift Shaft	N.R.	N.R.	N.R.
9	• I	ressurization of Lift lobby	N.R.	N.R.	N.R.
		Communication In lift Car	N.R.	N.R.	N.R.
	9 1	ireman's Grounding witch	N.R.	N.R.	N.R.
	• I	ift Signage	N.R.	N.R.	N.R.
17.	Stand	dby power supply	Required	Provided	M.R
18.	Refu	ge Area	A STATE OF THE STA		
	>	Total Area	N.A	N.A	N.A
	4	Location	N.A	N.A	N.A
19,	Fire C	ontrol Room			
	4	Detector System Panel	N.R.	N.R.	N.R.
	>	Flow Switch Panel	N.R.	N.R.	N.R.
	-	PA system Panel	N.R.	N.R.	N.R.
	>	Batter backup	N.R.	N.R.	N.R.
	~	Building Floor plans	N.R.	N.R.	N.R.
20.		Fire Protection Systems ection of special Risks, if	N.R.	N.R.	N.R.

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC vide letter No. F.6/DFS/MS/EH/2011/1127 dated 08/06/2011 renewal under rule 35 of the Delhi Fire Service rule 2010 is recommended.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Udax Vir Lingh

Name Sunil Chawdhary

Designation ADO (W.P.)

Designation DO (W)