GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F6/DFS/ans/2014/w2/1341

Dated: 27 /10 /2014

FIRE SAFETY CERTIFICATE

Pollowing fire safety directives must be adhered to:-

1) All the means of escape shall be kept free of all type of obstruction all the time.

2) All the employees shall be acquainted with the use and maintenance of a fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3) All the fire fighting equipment shall be maintained in perfect working condition all the time and lapse rendering non-functional of fire safety measures, management shall be responsible.

4) Any deviation, with regards to construction, electric installation etc. may be got verified from the concerned authorities.

5) Basement shall be used as per NBC. Part- IV

6) This NOC may not be treated in any case for regularizations of unauthorized construction, if any.

7) The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

8) "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

(Santoich Singh)
Chief Fire Officer
Delhi Fire Service
Ph:011-23414250
cfowz.dlfire@nic.in

90.90

Copy to:

Mr. Sunil Jain (Vice President) Aggarwal Cyber Plaza-II,

C-7 Netaji Subhash Place, Wazir Pur District Centre, Delhi-110034

INSPECTION REPORT Name & address of the building Aggarwal Cyber Plaza-II, C-7 Netaji Subhash Place, Wazir Pur District Centre, Delhi-110034. 2. Type of Occupancy Renewal Type of Case 3. Mercantile+Business (Mixed), (Basement+Ground+13 Upper Floors) 4. Details of previous NOC F.6/DFS/MS /2011/1669 dated 21/07/2011 5. Fire Safety directives letter No. F.6/DFS/MS/BP/ 2005/1037 dated 18-05-2005 6. Date of inspection 30-09-2014 7. Name of the Inspecting Officers Sunil Chawdhary DO (M.N.) Name and designation of officers 8. From the building side Mr. Sunil Jain (Vice President) 9. Year of Construction 2007 Applicant's letter No. Nil dated 18-09-2014 S. Minimum Standards on fire BBL Provided at site Remarks Prevention and fire safety U/R 33 No. Requirement MR/NMR ł. Access to building Road width 09 m 22.4 m M/R 06 m Provided Gate width M/R 06 m Provided M/R Width of internal road 2. Number, Width, Type & Arrangement of Exits Number of staircases 02 M/R Provided Upper Floors 02 Provided Basement M/R Width of staircases Old case Old case M.R. Upper Floors Old case Old case M.R. Basement Protection of exits Required Provided M.R. Fire check door Pressurization Required Provided M.R. d. No. of continuous staircases Required Provided M/R to terrace e. Width of Corridor Old case Old case M.R. Old case Old case M.R. f. Door size 3. Compartmentation. Fire check door Required Provided M.R. Sealing of electrical shafts Required Provided M.R. Fire Rating of shaft door Required Provided M.R. Water Curtain Required Provided M.R. Fire Dampers Required Provided M.R. 4. Smoke Management System. Basements 30 a/c per hour **Exhaust Fans** M.R Provided M.R. 12 a/c per hour Upper floors 5. Fire Extinguishers Total numbers 37 nos Provided M.R **Types** ABC & CO2 Provided M.R IS marking Provided M.R ISI marked 6. First-Aid Hose Reels.

-		1.
W	-	4
4 1	-	- 1

	Nozzle diameter	5 mm	Provided	M.R			
7.	Automatic fire detection and alar	ming system.					
	Type of detectors	Smoke & Heat	Provided	M.R.			
	CM: D	Required	Provided	M.R.			
		Required	Provided	M.R.			
	Location of Repeater Panel	Required	Provided	M.R.			
	Alternate source of power Hooter's Location	Required	Provided	M.R.			
3.	MOEFA	Required	Provided	M.R			
).	Public Address System	Required	Provided	M.R			
10.	Automatic Sprinkler system	Required	Provided	M.R			
	Basement	Required	Provided	M.R			
	BasementUpper Floor	Required	Provided	M.R			
	Sprinkler above false	Required	Provided	M.R			
	ceiling						
11.	Internal Hydrants		x = .				
	Size of riser/down-comer	150 mm	provided	M,R			
	Number of hydrants per	01	provided	M.R.			
	floor Hose Box	Required	provided	M.R			
12.	Yard Hydrants.						
	T. 1 1 C1 1	Required	Provided	M.R.			
	Total number of hydrants	*	Provided	M.R.			
	Hose Box	Required	Provided	IVI.K.			
13.	Pumping Arrangements.						
	Ground Level	- 08					
	Discharge of main pump	2850 LPM	Provided	M.R.			
	➤ Head of Main pump	100 m	Provided	M.R.			
		02	Provided	M.R.			
	> Number of main pumps						
	> Jockey Pump out put	180	Provided	M.R.			
	> Jockey pump head	100 m	Provided	M.R.			
	 Standby pump out put 	N.R.	N.R.	M.R. (as pumps are connected with DG)			
	> Standby pump Head	N.R.	N.R.	N.R.			
	Auto Starting/Manual	N.R.	N.R.	N.R.			
	stopping > Pump Hose Access	Required	Provided	M.R.			
	Terrace level						
	> Discharge of pump	450 LPM	Provided	M.R.			
	> Head of the pump	40 m	Provided	M.R.			
	> Power supply	Required	Provided	M.R.			
	> Auto Starting of pump	Required	Provided	M.R.			
14.	Captive Water Storage for fire t	ighting: Common with	nall M				
	Underground tank capacity	1,00,000 ltrs	Provided	M,R.			

AFD

15	Exit Signage.	required	Provided	M.R.
16.	Provision of Lifts			
	Pressurization of Lift Shaft	Required	Provided	M.R.
	Pressurization of Lift lobby	Required	Provided	M.R.
	Communication In lift Car	Required	Provided	M.R.
	Fireman's Grounding	Required	Provided	M.R.
	Switch • Lift Signage	Required	Provided	M.R.
17.	Standby power supply	Required	Provided	M.R
18.	Refuge Area			
	> Total Area	Old case	Old case	Old case
	> Location	5 th , 6 th , 8 th , 12 th floor	Provided	M.R.
19.	Fire Control Room			
	> Detector System Panel	Required	Provided	M.R.
	> Flow Switch Panel	Required	Provided	M.R.
	> PA system Panel	Required	Provided	M.R.
	> Batter backup	Required	Provided	M.R.
	Building Floor plans	Required	Provided	M.R.
20.	Special Fire Protection Systems for Protection of special Risks, if any:	CO ₂ Flooding for DG HT & LT Pannel	Provided	M.R.

The fire protection systems provided in the building were test checked and found functional at the time of inspection. Keeping in view the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC vide letter No. F.6/DFS/MS /2011/1669 dated 21/07/2011 renewal under rule 35 of the Delhi Fire Service rule 2010 is recommended.

Note: Description & alasm by stem base ment connected to delection & alasm by stem by stem sefuge asea.

Signature of the Inspection Officer

Signature of the Inspection Officer

Name Sunil Chawdhary

Name

Designation DO (W)

Designation