GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/0F5/ms/school/2014/402/1491 Dated: 28/11/14

FIRE SAFETY CERTIFICATE

Certified that the Govt. Girls Senior Secondary School at East Gokalpur, Loni Road, Delhi - 110094, owned/occupied by Govt. Girls Senior Secondary School, comprising of ground plus first floor only was issued FSC vide letter no-F6/DFS/MS/School/2011/3372 dated-05/12/2011. The school building was re-inspected by the officer concerned of this department on 05/11/2014 in the presence of Mrs. Adarsh Malhotra, Head of the school and found that the school building have deemed complied with the fire prevention and fire safety requirements in accordance with Circular Letter No-F16/Estate/CC/FS/2011/3298to3398 dt-01/03/11 issued by Director of Education and found that the school building is fit for occupancy class "B" 'Educational Building' for ground plus first floor with effect from Section 1.1.

Issued on at New Delhi by

(Dr.G.C.Misra) Chief Fire Officer Ph.011-23414333

To,

The Principal, Govt. Girls Senior Secondary School, East Gokalpur, Loni Road, Delhi -110094

Copy:-

- The Principal, Govt. Boys Senior Secondary School, East Gokalpur, Loni Road, Delhi -110094
- 2. The Dy. Director of Education, B–Block, Yamuna Vihar Delhi-110053.

olc

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry

1. Name & address of the building : Govt. Girls Senior Secondary School,

East Gokalpur, Loni Road, Delhi-110094.

2. Building is comprised of (In three Blocks) all ground plus first floor.

3. Type of Occupancy : Educational

4. Type of Case Renewal

5. Details of Previous NOC letter : F6/DFS/MS/School/2011/3372 dated-05/12/11

6. Fire Safety direction letter No : F16/Estate/CC/FireSafety/2011/3298to3398 dt-01/03/11

7. Date of Inspection : 05/11/2014

8. Name of the Inspecting officers : ADO Vijay Bahadur

9. Name and designation of Officer

from the building side : Mrs. Adarsh Malhotra (Head of the School)

10. Year of Construction : 2005

11. Applicant's letter No : Letter No.-EGP/LR/252, Dated-17/10/2014

Sr. No.	Minimum Standards on fire prevention and fire safety U/R33	Circular	Provided at Site	Remarks				
01	Access to building	Requirement	1	MR/NMF				
0 1	Access to building							
	 Road width 	06 mtr.	07 mtr.	MR				
	 Gate width 	N/A	N/A	N/A				
	 Width of internal road 	N/A	N/A	N/A				
02	Number, Width, Type and Arrangement of Exits							
	a. Number of Staircases							
	Upper Floor	03 nos.	05 nos. (02 nos, in	MR				
	and by factory to 1 20 Cot	00 1100.	first & Second blocks	IVITY				
			& 01 no. in third					
			block)					
	 Basement 	N/A	N/A	N/A				
	B. Width of Staircases			and the state of t				
	 Upper Floor 	1.50 mtr.	1.47, 1.38, 1.32, 1.38	MR				
	&1.50 mtr.in Dird block							
	Basement	N/A	• N/A	N/A				
	c. Protection of exits							
	 Fire check door 	N/A	N/A	N/A				
	Pressurization	N/A	N/A	N/A				
	d. No. of continuous staircases to terrace		- I	MANUFOCK COA				
	e. Width of Corridor	1.50 mtr.	1.40 mtr. (old	MR				
	C. Width of Corridor	1.00 11111	Acceptable)	IVIT				
	f. Door Size	01 mtr.	01 mtr.	MR				
03	Compartmentation.							
	Fire check door	N/A	NI/A	B. 1.4.5				
	Sealing of electrical	N/A	N/A N/A	N/A				
	shafts	N/A	N/A	N/A				
	Fire rating of shaft door	N/A	N/A	N/A N/A				
	Water curtain	N/A	N/A	N/A				
	Fire Dampers		18/73	IN/A				
)4	Smoke Management System.							
	Basement	N/A	N/A	AI/A				
	Upper floor	N/A	N/A	N/A N/A				

		11 nos.	12 nos.	MR				
	Total numbers	ABC /CO ₂	ABC /CO ₂	MR				
1	• types	ISI marked	ISI marked	MR				
	 IS marking 	191 Marken	I WITHOUT	1 100				
)6	First-aid-Hose Reels.							
	Total numbers on each floor	N/A	N/A	N/A				
1	Length of hose reel hose	N/A	N/A	N/A				
To supplied to	Nozzle diameter	N/A	N/A	N/A				
07	Automatic fire detection and alarming systematics		About the second	and the second second second second second				
J/								
	 Type of detectors 	N/A	N/A	N/A				
	 Location of main panel 	N/A	N/A	N/A N/A				
	 Location of repeater panel 	N/A	N/A	N/A				
	 Alternate source of power 	N/A	N/A					
	 Hooter's location 	N/A	N/A	N/A				
08	MOEFA	N/A	N/A	N/A				
09	Public address System.	N/A	N/A	N/A				
10	Automatic Sprinkler System.							
		N/A	N/A	N/A				
	Basement	14/7						
	upper floor	N/A	N/A	N/A				
	sprinkler above false ceiling	N/A	N/A	N/A				
11	Internal Hydrants							
		N/A	N/A	N/A				
		N/A	N/A	N/A				
			N/A	N/A				
	Hose Box	N/A	IWA	1 177				
12	Yard Hydrants.							
	Total number of hydrants	N/A	N/A	N/A				
	Hose Box	N/A	N/A	N/A				
13	Pumping Arrangements.							
		h : / A	N/A	N/A				
	Ground Level	N/A	N/A	N/A				
	Discharge of main Pump	N/A	N/A	N/A				
	➤ Head of Main Pump	N/A	N/A	N/A				
	> Number of main pumps	N/A	N/A	- N/A				
	Jockey pump out put	N/A	N/A	N/				
	> Jockey pump head	N/A	N/A N/A	. N/				
	> Standby pump out put	N/A N/A	N/A	N//				
	> Standby pump Head	N/A	N/A	N/				
	> Auto Starting /Manual stopping	N/A N/A	N/A	N/				
	> Pump House Access	N/A N/A	N/A	N/				
	Terrace Level	N/A	N/A	N/				
	➤ Discharge of pump	N/A	N/A	N/				
	> Head of the Pump	N/A	N/A	N/				
	Power supply	IWA	1 1/7/3	N/				

14	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A		
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	➢ Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	N/A	N/A	N/A		
15	Exit Signage.	N/A	N/A	N/A		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication in lift car	N/A	N/A	N/A		
	Firemen's grounding switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	N/A	N/A	N/A		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	• Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	 Flow switch panel 	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	more of the second			and the second s		
	Building Floor Plans	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no-F6/DFS/MS/Schooi/2011/3372 dated-05/12/11, renewal under the circular-

F16/Estate/CC/FireSafety/2011/3298to3398 dt-01/03/11 is recommended.

protection of special Risks, if any:

Signature of the Inspecting Officer Name- Vijay Bahadur Designation- A.D.O

Do(ED)

ubmitted for approval bleas