## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADOUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110 001.**

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ SZ/1462

Dated: 25/11/2019

## **FIRE SAFETY CERTIFICATE**

Certified that the Hotel Akshay Palace located at 26 B, Pusa Road, Karol Bagh, New Delhi-110005 is comprised of Basement, Ground floor, Mezzanine floor plus three upper floors, using basement as hall/storage, ground floor as bank, reception & hall, Mezzanine floor used as office & staff kitchen, first & second floor each having 11 guest rooms respectively, third floor having 01 guest room (Total 23 guest rooms) was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011/2498 dated 12.10.2011 owned/ occupied by Sh. Kuldeep Sobti. The guest house building was re- inspected by the officers concerned of this department on 17.11.2014 in the presence of Sh. Salimuddin (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 2.5/11/19 at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- The Joint Commissioner of Police (Lic.) 1<sup>st</sup> floor, P.S., Defence Colony, New Delhi. (Re. No.39681/Joint C.P./Lic.(H), Dated 17.10.2014)
- 2. Sh. Kuldeep Sobti (Owner) Hotel Akshay Palace, 26 B, Pusa Road, Karol Bagh, New Delhi-110005.

## Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

## Basement, Ground Floor, Mezzanine Floor plus three apper Floors.

	14/72			¥.		
	INCDE	TION DEDORT				
	1. Name & address of the building	TION REPORT		× 6		
	2. Type of Occupancy	the building: Hotel Akshay Palace, 26-B, Main Pusa Rd., Ke Residential (Collect House)				
	3. Type of Case	THE THE PARTY OF T				
	A Dataila & D.	. New Case/Renewal				
	5. Fire Safety directives letter No	: Letter No. F.6/DFS/MS/GH/2011/2498 Date 12.10.2				
	6. Date of inspection					
	7. Name of Inspecting Officer	fficer: D.O.S.K. Tomar & A.D.O. P.S. Dahiya				
	8. Name and designation of officers					
	From the building side			U		
	9. Year of Construction	Sh. Sali	muddin (Acco	cuntant)		
	10 0	1988		A STATE OF THE PARTY OF THE PAR		
S.	Minimum Standards on fire	: 39681 Joint C.P. LIC. CH) dated 17.10.20				
No.		MARCIABE	Provided at	Remarks		
1.	prevention and fire safety U/R 33 Access to building	Requirement	site	MR/NMR		
	Road width	Accessible	09mtr	MR		
	Gate width	_	180 cms	MR		
7	• Width of internal road					
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases .					
	• Upper Floors	Two				
	<ul> <li>Basements</li> </ul>	- do -	700	MR		
	b. Width of staircases	- 000 -	-do-	MR		
	<ul> <li>Upper Floor</li> </ul>	10 =				
	<ul> <li>Basements</li> </ul>	125 cms	125cms, loocms	MR, Old Ca		
	c. Protection of exits	125cms	100 cms Each	do _ !		
	Fire check door		, P (1)			
	• pressurization					
	d. No. of continuous staircases to		- 1. Ta.			
	terrace					
	e. Width of Corridor		One			
	f. Door Size	_	130 cms, 160cm	nA _		
				Standards and a suspensive of the second standards of the second		
3,	Compartmentation		85 cms x 205 cms			
	Fire check door		·	·		
	Sealing of electrical shafts					
	Fire Rating of shaft door	-	Sealed			
	Water Curtain					
1.	• Fire Dampers					
	Smoke Management System					
	* Basements	30 a/c per	Exhaust Pans	The second secon		
		1 30 0/1 1101				
	Upper floors	hour	are Provided	MR		

	N/26			•	
		12 a/c per hour			
5.	Fire Extinguishers				
	<ul> <li>Total numbers</li> </ul>	Two at each Flo	0		
	<ul><li>Types</li></ul>	Co2, WCo2	1 Dovided	MR	
	<ul> <li>IS marking</li> </ul>	ISI marked	-do-	MR	
6.	First-Aid Hose Reels		151 Marked	MR	
	<ul> <li>Total numbers on each floor</li> </ul>	Ohe	0		
	<ul> <li>Length of hose reel hose</li> </ul>	30 m	Provided	MR	
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	-do-	MR	
7.	Automatic fire detection and alarming	system	-do-	MR	
	<ul> <li>Type of detectors</li> </ul>			+	
İ	<ul> <li>Location of Main Panel</li> </ul>				
	<ul> <li>Location of Repeater Panel</li> </ul>	_			
	<ul> <li>Alternate source of power</li> </ul>	:	N C C 1111	+	
	<ul> <li>Hooters' Location</li> </ul>		D.G. Set of 62 SKVA	+1	
8.	MOEFA	Road	0	+	
9.	Public Address System	Required		NZR	
10.	Automatic Sprinkler System	- do -	1 - do -	MR	
	• Basement	Required	0		
	<ul> <li>Upper Floor</li> </ul>	rigured	Provided	MR	
	<ul> <li>Sprinkler above false ceiling</li> </ul>			<del>- 1</del>	
11.	Internal Hydrants				
August and a second	<ul> <li>Size of riser/down-comer</li> </ul>				
	<ul> <li>Number of hydrants per floor</li> </ul>			- 1	
	<ul> <li>Hose Box</li> </ul>		Parish	·	
12.	Yard Hydrants	ts - Provided +			
	<ul> <li>Total number of hydrants</li> </ul>		Provided		
	★ Hose Box		-do-		
13.	Pumping Arrangements				
	<ul> <li>Ground Level</li> </ul>		,		
	Discharge of main Pump				
	Head of Main pump			1. 1	
	Number of main pumps	-			
	Jockey Pump out put				
	<ul><li>Jockey pump head</li><li>Standby Pump out put</li></ul>			,	
	> Standby Pump Head				
	> Auto Starting/Manual		i.		
	stopping				
	acobbuig.			-	
		1	A SECOND	10 E	

17 New Delli - 110005.

Pump House Access Terrace level Discharge of pump 450 LPM MR, Old Case > Head of the pump MR, old Case Power Supply Required Auto Starting of pump 14. Captive Water Storage for fire fighting Underground tank capacity > Draw-off connection Fire service inlet Provided MR Access to tank Overhead Tank capacity , old Case Soco Ur Required Provided MR 15. Exit Signage. 16. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Provided MR • \* Fireman's Grounding Switch -do-Required MR Lift Signage -do--do -MR Required Provided MR 17. Standby power supply Refuge Area. 18. Total Area Location 19. **Fire Control Room** Detector System Panel Flow Switch Panel PA System Panel Batter backup Required Provided **Building Floor Plans** 20. Special Fire Protection System for Protection of special Risks, if any:

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. Fig. NFS MS GH 2011 2498 dated 12.10.2011 renewal under rule 35 of the

Delhi Fire Service rules 2010 is recommended.

0 20 mily

Signature of Inspecting Officer

Name S. K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Asstt. Divisional Officer