GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE : NEW DLEHI - 110 001

Fax:-011-23412593

E-mail ID: cfohq.dlfire@nic.in

No. F.6/DFS/MS/GH/2014/1402/1479

Dated: 27/11/19

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Paras International** located at 5/25, W.E.A, Karol Bagh, New Delhi-110005 comprises of Basement, Ground floor + Four Upper floors, using basement as hall/storage, Ground floor as reception and offices, first, second & third floor each having eight guest rooms respectively (**Total 24 guest rooms**) and a pantry with staff room on terrace was granted NOC by this department vide letter No.F.6/DFS/MS/GH/2011/2675 dated 24-10-2011. The premises was re- inspected by the officer concerned of this department on 18-11-2014 in the presence of Mr. Jai Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Residential**, **Sub-Division A-1 Guest House** for 24 guest rooms with effect from 2-7-1-11/2-2014 for a period of **three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on....2.7./........at New Delhi by.

(**Dr. G.C. Misra**) Chief Fire Officer Delhi Fire Service Ph-011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049 w.r.t. letter No. 39671/Joint C.P./Lic.(H) dated New Delhi 17-10-2014
- 2. Mr. Narender Arora (Owner) Hotel Paras International, 5/25, W.E.A, Karol Bagh, New Delhi-110005.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

-								
		ION REPORT						
		lame & address of the building : Hotel Paras International, 5/25, WEA, Karol Bagh,						
		New Delhi-110005.						
	2 -	e of Occupancy : Residential (Guest House) B+G+4 Floor total guest rooms-2						
		R <mark>enewal</mark>						
)11/2675 dated 24/	10/2011				
		N/A						
		18/11/2014						
	8. Name and designation of officers	<mark>Dy. C.F.O</mark> Rajesh Pa	nwar					
		Sh. Jai Kumar (Man	ager)					
		Before 2008	iagei j					
	10		c (H) dt New Delhi :	17/10/2014				
S. No.	Minimum Standards on fire prevention	NBC/BBL	Provided at site	Remarks				
	and fire safety U/R 33	Requirement	special area	MR/NMR				
l	Access to building		Special area	THE THE				
	Road width	Accessible	12 mtr	MR				
	Gate width	NA	NA	NA				
	Width of internal road	NA	NA	NA				
2.	Number, Width, Type & Arrangement of	Exits						
	a. Number of staircases							
	• Upper Floors	One	One	MR				
	Basements	Two	Two	MR				
	b. Width of staircases	1 WO	TWO	IVIR				
		125	126	2.62				
	 Upper Floor 	125 cms	136 cms	MR				
	 Basements 	125 cms	116 cm, 157 cms	MR				
	a Dantantian of a it			* ,				
	c. Protection of exits	NA	NA	NA				
	Fire check door	NA	NA	NA				
	Pressurizationd. No. of continuous staircases to							
	terrace	One	One	MR				
	e. Width of Corridor	1.0 Mtr .	1.60 Mtr	MR				
	or common	900 St. 41 - 901 - 900 PAZZ						
	f. Door Size	1 0 Mtm	96 V 202	MD OLLC				
		1.0 Mtr.	86cm X 203 cm	MR, Old Case				
3.	Compartmentation							
	Fire check door	NA	NA	NA				
	Sealing of electrical shafts	NA	Ball Shireston					
	• Fire Rating of shaft door		NA	NA				
	Water Curtain	NA	NA	NA				
	• Fire Dampers	NA	NA	NA				
	·	NA	NA	NA				
4.	Smoke Management System							
	Basements	≈30 ACPH	Exhaust Fans are	MR				
			provided					
	 Upper floors 	12 ACPH	Natural Ventilation	MR				
			Ventilation					
•	Fire Extinguishers							
	Total numbers	Two at each floor	Provided	MR				
	 Types 	Water Co2, Co2	Provided	MR				
	IS marking	Igi	ISI marked	MR				
		ISI marked	151 markeu	IVII				
). 	First-Aid Hose Reels	Ona	Descrided 1	- MD				
	Total numbers on each floor	One 30 m	Provided	MR				
	 Length of hose reel hose 	DU III	Provided	MR				
	Nozzle diameter	5 mm	Provided	MR				

7.	Automatic fire detection and alarming s	system			7
9	Type of detectors	NA	NA		NA
	Location of Main Panel	NA	NA		NA
	 Location of Repeater Panel 	NA	NA		NA
	Alternate source of power	Required	D.G set of 125 KVA		MR
¥	Hooters' Location	NA	NA		NA
8.	MOEFA	Required	Provided		MR
9.	Public Address System	Required	Provided		MR
10.	Automatic Sprinkler System	D 1	D :1.1		MD
	Basement	Required NA	Provided NA		MR NA
	Ground Floor Sprinkler above false spiling	NA NA	NA NA		NA
11.	Sprinkler above false ceiling Internal Hydronts	NA NA	NA		NA
11.	Internal Hydrants • Size of riser/down-comer	NA	NA		NA
	 Number of hydrants per floor 	NA NA	NA		NA NA
	Hose Box	NA	NA		NA
12.	Yard Hydrants	1111	1111		1121
	Total number of hydrants	NA	NA	1	NA
	Hose Box	NA	NA		NA
13.	Pumping Arrangements	1111	1111		1111
20.	Ground Level	<u> </u>	v ·		1
	Discharge of main Pump	NA	NA	+	NA
	➤ Head of Main pump	NA	NA	-	NA
	Number of main pumps	NA	NA NA	-	NA NA
	Jockey Pump out put				
	Jockey pump head	NA	NA	-	NA
	Standby Pump out put	NA	NA		NA
	> Standby Pump Head	NA	NA		NA
	> Auto Starting/Manual	NA	NA	a L	NA
	Stopping	NA	NA		NA
	> Pump House Access	*		Tall I	
	Terrace levelDischarge of pump	450 LPM	450 LPM		MR
	> Head of the pump	30 M	30 M		MR
	> Power Supply	Required	Provided		MR
	Auto Starting of pump	NA	NA *		NA
r.					
14.	Captive Water Storage for fire fighting		ar .	•	
,	Underground tank capacity	NA	NA		NA
	> Draw-off connection	NA	NA		NA
	➢ Fire service inlet	» NA	Provided		MR
	Access to tank	NA	NA	0	NA
	Overhead Tank capacity	5000 Ltr	5000 Ltr		MR
		Required	Provided		MR
15.	Exit Signage.	2007000			
16.	Provision of Lifts.				
	 Pressurization of Lift Shaft 	NA	NA		NA
	 Pressurization of Lift lobby 	NA	NA		NA
	Communication In lift Car	Required	Provided		MR
	 Fireman's Grounding Switch 	Required	Provided		MR
	Lift Signage	Required	Provided		MR
		Required	Flovided		IVII

17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			
	Total Area Location	NA	NA	NA
	Location	NA	NA	NA
19.	Fire Control Room			
	Detector System Panel	NA	NA	NA
	 Flow Switch Panel PA System Panel Batter backup Building Floor Plans 	NA	NA	NA
		NA	NA	NA
		Required	Provided	MR
		NA	NA	NA
20.	Special Fire Protection System for Protection of special Risks, if any:	NA	NA	NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/GH/2011/2675 dated 24.10.2011 renewal under rule 35 of Delhi Fire Service Rules 2010, is recommended please.

Signature of Inspecting

Name:- Rajesh Panwar

Designation:- Dy. C.F.O (NDZ)

Signature of Inspecting Officer

Name

Designation