GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI- 110001 Fax: 011-23412593, Email: cfohq.dlfire@nic.in, Ph. 011-23414333

NO. F6/DFS/MS/Indl/2014/SZ/ 1467

DATED: 26/11/19

FIRE SAFETY CERTIFICATE

Certified that the M/s Supreme Impex Industrial building at S-59, Okhla Phase-II, Industrial Area, New Delhi-110020 comprised of basement, ground plus three upper floors was granted NOC by this department vide letter No. F6/DFS/MS/IndI/2011/3698 dated 26.12.2011. The premises was re-inspected by the officer concerned of Delhi Fire Service on 10.11.2014 in the presence of Mr. Pram Singh Rana (Director) of the factory and observed that fire safety norms as required under Rule 33 of Delhi Fire Service Rules, 2010 are deemed complied and that the building / premises is fit for occupancy class G "Industrial building" with effect from [2.6.] [1.1.] [1.7....] for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rule 2010.

(Dr. G.C. Misra) Chief Fire Officer

Ofe the Assisted

Copy to,

- 1. The Executive Engineer (Bldg) HQ, Building Department, MCD, Town Hall, Delhi.
- 2. The Partner, M/s Supreme Impex, S-59, Okhla, Phase-II, Industrial Area industrial Estate, New Delhi-110020

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The basement shall be used strictly as per the provisions of Building Bye laws.
- e. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules-2010. The form is available on www.dfs.delhigovt.nic.in
- f. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

ĺ	INS	SPECTION REPO	RT			
1	Name & address of the building	M/s Supreme Impex, S-59, Okhla, Phase-II, Industrial Area, New Delhi-110020				
2	Type of Occupancy	Industrial G				
3	Type of case	Renewal	Renewal			
		F6/DFS/MS/Indl/20	F6/DFS/MS/Indl/2011/3698 dated 26.12.2011			
4	Details of previous NOC	Nil				
5	Fire safety directives letter No	10.11.2014				
6	Date of inspection					
7	Name of the inspecting Officers :		D.O. (South) D.P. Bhardwaj, ADO(BCP) D.B. Mukherjee			
8	Name and designation of officers	Sh. Pram Singh Rana (Director)				
	from the building side					
		1986 Bas		1	ment ground plus	
9	Year of construction	Nil Dated 13.10.20	14	three u	upper floors	
10 S. NO.	Applicant's letter No. Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provid	ed at site	Remarks MR / NMR	
-						
1	Access to building 1) Road width	14 mtrs	Provided		IMR	
	2) Gate width	Required	5 Mtr		MR	
	3) Width of internal road	N/A	N/A		N/A	
2	Number, width Type & arrangement of		14//		IN/A	
2	a. Number of staircases	T				
	1. Upper floors	2 Nos.	Provided		MR	
	2. basements	2 Nos.	Provided		MR	
	b. Width of staircase					
	1. Upper floors	1.5 mtrs	1.5 &0. 90	Mtr Provided	MR	
	2. basements	1.5 mtrs		Mtr Provided	MR	
	c. Protection of exits	110 111110	Provided N/A Provided			
	1. Fire check door	Required			MR	
	2. Pressurization	N/A			N/A	
	d. No. of continuous staircase to terrace				MR	
	e. Width of corridor	N/A	N/A		N/A	
	f. Door size	Required	Provided		MR	
3	Compartmentation.					
-	1. Fire check door	Required	Provided		MR	
	2. Sealing of electrical shafts	Required	Provided		MR	
	3. Fire Rating of shaft door	N/A	N/A		N/A	
	4. water curtain	N/A	N/A		N/A	
Water Control of the	5. Fire dampers	N/A	N/A		N/A	
	Smoke Management system.					
4		00 - /	TExhuet For	Provided	MR	
4	basement	30 a/c per hour 12 a/c per hour	EXITUST FAI			

5	Fire Extinguishers			THE ACCURATE AND SECURE AND ADDRESS AND AD	
	total numbers	ISI	17 Nos	MR	
	Types		ABC, Co2, Wco2	MR	
	ISI marking		Yes	MR	
6	First-Aid Hose Reels.				
	total numbers on each floor	One	Provided	MR	
u	Length of Hose reel hose	30 m	Provided	MR	
	Nozzle Diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming	system			
	Type of detectors	N/A N/A N/A			
	location of Main Panel	Required	Provided (Ground)	MR	
907	location of Repeater panel	N/A	N/A	N/A	
	Alternate source of power	Required	Battary Backup	MR	
v 12,3	hooter's location	Staircase	Provided	MR	
8	MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	basement	Required	Provided	MR	
	upper floors	Required	Provided	MR	
	sprinkler above false ceiling	N/A	N/A	N/A	
11	Internal Hydrants			*	
	Size of riser/down-corner	100 mm	Provided	MR	
	Number of Hydrants per floor	One	Provided	MR	
	hose Box	One	Porvided	MR	
12	Yard Hydrants.				
	total number of hydrants	N/A	N/A	N/A	
	hose box	N/A	N/A	N/A	
13	Pumping arrangements				
	1. Ground level				
	a. Discharge of main Pump	N/A	N/A	N/A	
	b.Head of main pump	N/A	N/A	N/A	
	c.Number of main pumps	N/A	N/A	N/A	
	d.jockey pump out put	N/A	N/A	N/A	
	e.jockey pump head	N/A	N/A	N/A	
	f. Standby Pump output	N/A	N/A	N/A	
	g.Stanby Pump head	N/A	N/A	N/A	
	h.Auto Starting/Manual stopping	N/A	N/A	N/A	
	pump house access	N/A	N/A	N/A	
	2.Terrace level		,	a sec	
	a. Discharge of pump	900 LPM	Provided	MR	
	b. head of the pump	40 mtr	Provided	MR	
	c. Power supply	Required	Provided	MR	
	d. Auto starting of pump	Required	Provided	MR	
1.0	Captive water storage for fire fighting				
14	Underground tank capacity	N/A	N/A	N/A	
	a. Draw-off connection	N/A	N/A	N/A	
-	b. fire service inlet	Required	Provided	MR	
	c.Access to tank	Required	Provided	MR	
	Over head tank Capacity	10,000 ltr	Provided	MR	
15	Exit Signage.	Required	Provided	MR	
15	-Ait orginage.	. toquilou	I TOVIGOG		

	1-	la de la companya de			1 To				
A	16	Provision of lifts.		Goods lift					
1		a. Pressurization of lift shaft	N/A	N/A	N/A				
		b. pressurization of lift lobby	N/A	N/A	N/A				
		c. communication in lift car	N/A	N/A	N/A				
		d. Fireman's grounding switch	N/A	N/A	N/A				
		e. Lift signage	N/A	N/A	N/A				
	17	Standby power supply	Required	Provided	MR				
	18	Refuge Area.	N/A	N/A	N/A				
		total area							
		location							
	19	Fire control room							
		a. Dtector system Panel	N/A	N/A	N/A				
		b. Flow switch Panel	N/A	N/A	N/A				
		c. PA system Panel	N/A	N/A	N/A				
		d. Batter backup	N/A	N/A	N/A				
		e. Bu <mark>i</mark> lding floor plans	N/A	N/A	N/A				
	20 Special Fire Protection systems for protection of special risks, if any:								
Th	The fire protection systems provided in the building were checked and found functional at the time of inspection.								
re	In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as								
ru	required under the rules of NOC issued vide letter no. F6/DFS/MS/Indl/2011/3698 dated 26.12.2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.								
	and the same and t								
	Adaptatingly DEA is not any (
	Accordingly DFA is put up for your approval and signature please.								
Si	anature (of the inspecting officer							
	Signature of the inspecting officer Signature of the inspecting Officer								
Na	ame	D.P. Bhardwaj	Nam	e D.B. Muki	nerjee				
Designation : Divisional Officer Designation:- ADO (BCP)									
				(()					