## CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

## **GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI** HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

No. F6/DFS/OS/School/2014/52/1470

Dated: 27/11/19

## FIRE SAFETY CERTIFICATE

Certified that Sarvodaya Bal Vidyalaya, Delhi Cant, New Delhi-10, comprises of ground plus two upper floors, owned/occupied by Directorate of Education, have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on dated 11.11.14 in the presence of Sh. Ranvir Singh, Vice Principal of the school and found that the building is fit for occupancy class B 'Educational Building' with effect from 2.7.11.1.1.4..................... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of Delhi Fire Service Rules,2010.

Issued on 27 / 11 / 14 at New Delhi by

(Dr.G.C.Misra)

Chief Fire Officer

T.No.011-23414333

To,

The Principal Sarvodaya Bal Vidyalaya, Delhi Cant, New Delhi-10.

Copy to:-.

The Director of Education Old Secretariat, Civil Lines, Delhi-52.

Conditions for the validity of fire safety certificate are overleaf:-

		<b>ECTION REPORT</b>						
2. Bu	ame & address of the building  : Sarvodaya Bal Vidyalaya, Delhi Cant, New Delhi-10.  : G+2(One Block) and G+1 (Two Block under construction).							
	ype of Occupancy : Education							
	Type of Case : New. Details of Previous NOC : Nil.							
	Details of Previous NOC : Nil.  Fire Safety direction letter No : F.16/Estate/CC/Fire safety/2011/3298 to 3398							
	Dated- (	01.03.11	11/3298 10 3398					
7. Da	ate of Inspection : 11.11.14	1						
8. Na	ame of the Inspecting Officers: : Vedpal	(ADO)						
9. Na	ume and designation of Officer om the building side : Ranvir							
	ear of Construction : 1939.	Singh (Vice Principal	)					
		C/NOC/2014/649, dat	ted 31 10 14					
		c/110 c/2014/04), dai	ica 51.10.14.					
S.N	Minimum Standards on fire	Requirement	Provided at Site	Remarks				
0	prevention and fire safety as per	~		MR/NMR				
	circular no.3298-3398 Dated01.03.11.							
1	Access to building		2					
	Road width	6 m	9 m	MR				
	Gate width	N.A.	N.A.	N.A.				
	Width of internal road	N.A.	N.A.	N.A.				
2	Number, Width, Type and Arrangeme	nt of Exits.						
	a. Number of Staircases							
	Upper Floor	2nos.	02nos.	MR				
	Basement	N.A.	N.A.	N.A.				
	B. Width of Staircases							
	Upper Floor	1.5 m(each)	1.50m&1.35m	MR				
	Basement	N.A.	N.A.	N.A.				
	c. Protection of exits	N.A.	N.A.	N.A.				
	Fire check door	N.A.	N.A.	N.A.				
	Pressurization	N.A.	N.A.	N.A.				
	e. No. of continuous staircases to	1no.	1no.	MR				
	terrace			5				
	g. Width of Corridor	1.5 m	1.5 m	MR				
	h. Door Size	1 m	1m	MR				
3	Compartmentation							
	Fire check door	N.A.	N.A.	N.A.				
	Sealing of electrical shafts	N.A.	N.A.	N.A.				
	Fire rating of shaft door	N.A.	N.A.	N.A.				
	Water curtain	N.A.	N.A.	N.A.				
	Fire Dampers	N.A.	N.A.	N.A.				
1	Smoke Management System.							
	Basement	30a/c per hour	N.A.	N.A.				
	Upper floor	12 a/c per hour	N.A.					
	Oppor noor	12 a/c per nour	IN.A.	N.A.				

5. Fire Extingu	Sarvodaya Bal Vidyal Jisher		) z .ow Dej	III-1U.			
types	ers	19 nos.		04			
IS marking		CO <sub>2</sub> & A	BC	21 nos.			MR
		ISI mark		CO <sub>2</sub> and	ABC	Туре	MR
· II St-alu-HOS	e Reels.	TOTTIAIK	ea	ISI marke	d		MR
I otal number	rs of each floor	02nos.		-			
Length of hos	Length of hose reel hose			02nos. MF		MR.	
Nozzie diame	eter	30m		30m		MR.	
7 Automatic fire	detection and alarmin	5cm		5cm		MR.	
Type of detec	tors					IVIT.	
Location of ma	Location of main panel		N.A. N.A.			NI A	
Location of rei	Location of repeater panel Alternate source of power			N.A.		N.A.	
Alternate sour						N.A.	N.A.
Hooters	oo or bowel	N.A.				N.A.	
0 16		N.A.		V.A.		N.A.	
8 MOEFA				V.A.		N.A.	
Public address	System.	N.A.	1	V.A.		N.A.	
Automatic Sprii	okler System	N.A.	1	I.A.		N.A	
Basement	Cyclem.					IV.A.	45.5
upper floor		N.A.	N	I.A.		NI A	
stage of auditor	ium	N.A.		.A.		N.A.	
		N.A.				N.A.	
mornar i yurani	Internal Hydrants Size of down-comer						
Number of b	mer	N.A.	40	10	1 2		
block	ants per floor in each	N.A.		00mm	1	V.A.	
Hose Box		N.A.		nos.	1	I.A.	
		14.7.	02	nos.	N	I.A.	
idid Hydrants.							
Total number of I	nydrants	N.A.	N.				4
		N.A.	N.A		N	.A.	
Pumping Arrange	ments.	14.74.	N.A	١.	·N	.A.	
► Ground Le	evel	N.A.	7.1		,		
Discharge	of main Pump		N.A			N.A.	
Head of M	ain Pump	N.A.	N.A			N.A.	
Number of	main pumps	N.A.	N.A			N.A.	
Jockey pur	np out put	N.A.	N.A		2 2	N.A.	
Jockey pur	np head	N.A.	N.A.				
Standby pu	Imp out put	N.A.	N.A.			N.A.	
Standby pu	mp Head	N.A.	N.A.			N.A.	
Auto Startir	ng /Manual	N.A.	N.A.			N.A.	
stopping	oau	N.A.	N.A.	The second		N.A.	
Pump Hous	e Access		IV.A.			N.A.	
> Terrace Lev	rel	V.A.	N.A.		Nil o		
Discharge o		Olno.				V.A.	
> Head of the	Pump	50LPM	02no		N	ЛR.	
Power suppl	v 4	-0m	450L	PM(Two)	٨	/IR	
> Auto Starting	I of numn	Required	40m(l		N	1R	
o tai tii ig		Required	Provid		N	1R	
		- quii eu	Provid	led	N	IR	

1/2

Sarvodaya Bal Vidyalaya, Delhi Cant, New Delhi-10.

14		y = o carre, recw De	:1111-10.	
14	Captive Water Storage for Fire Figh	ting.		
	Underground tank capacity Draw-off connection	N.A.	N.A.	N.A.
	Fire service inlet	N.A.	N.A.	N.A.
	Access to tank	N.A.	N.A.	N.A.
	Overhead Tank capacity	N.A.	N.A.	N.A.
15	Exit Signage.	10000 liters	10000Ltrs.	MR
16	Provision of Lifts.	Required	Provided	MR
	Pressurization of Lift Shaft			
	Pressurization of Lift lobby	N.A.	N.A.	N.A.
	Communication in lift car	N.A.	N.A.	N.A.
	Firemen's grounding switch	N.A.	N.A.	N.A.
	Lift Signage	N.A.	N.A.	N.A.
17	Standby power supply	N.A.	N.A.	N.A.
18	Refuge Area.	N.A.	N.A.	N.A.
	Total area			
	Location	N.A.	N.A.	N.A.
19	Fire Control Room	N.A.	N.A.	N.A.
	Detector system panel			
	Flow switch panel	N.A.	N.A.	N.A.
	PA system panel	N.A.	N.A.	N.A.
	Batter backup	N.A.	N.A.	N.A.
	Building Floor Plansp	N.A.	N.A.	N.A.
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.
20		N.A.	N.A.	N.A.
	procession of special Risks, if any:			

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules

Signature of the Inspecting Officer

Name: Vedpal

Designation: ADO