GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/GH/2014/ S2 \ 1554

Dated:

11/12/14

FIRE SAFETY CERTIFICATE

Certified that Sai Basera Guest House located at 6/1, Nangli Razapur, East Nizamuddin, New Delhi-110013 comprised of ground floor (Reception), first floor (02 guest rooms), second floor (02 guest rooms) & third floor (staff room) was inspected by the officer concerned of this department on 24-11-2014 in the presence of Mr. Ajay Chauhan, owner of the guest house and found that the said guest house have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from to premise for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules.2010.

Issued on 11 (2/14 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

2. The Manager, Sai Basera Guest House, 6/1, Nangli Razapur, East Nizamuddin, New Delhi-110013.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Sai Basera Guest House, 6/1, Nangli Razapur, East

Nizamuddin, New Delhi-110013.

2. Type of Occupancy : Lodging House

3. Type of Case : New Case

4. Details of previous NOC : N/A

5. Fire Safety directives letter No : Nil6. Date of inspection : 24.11.2014

7. Name of the Inspecting Officers : M.K.Chattopadhyay, ADO(M. Road)

8. Name and designation of officers

from the building side : Mr. Ajay Chauhan, owner

9. Year of Construction : 2003

10. Applicant's letter No. : 41699/joint C.P/Lic(H) dated New Delhi the 07-11-2014

The said guest house is comprised of ground floor (Reception), first floor (02 guest rooms), second floor (02 guest rooms) & third floor (staff room).

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	BBL Requiremen	Provided at site	Remarks MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	Gate width		Directly accessible	MR		
	Width of internal road	N/A	N/A	N/A		
2	Number, Width, Type & Arrangemen	t of Exits		4		
	a. Number of staircases	-	- , i	-		
	Upper Floors	01	Provided	MR		
	• Basements	N/A	N/A	N/A		
	b. Width of staircases	-	- b	· -		
	Upper Floors	0.90 mt	Provided 1.0 mts	MR		
	Basements	N/A	N/A	N/A		
	c. Protection of exits	-	-	-		
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to	01	01	MR		
	g. Width of Corridor	1.0 mt	Provided	MR		
	h. Door Size	1.0 mt	Provided	MR		
			1			

3	Compartmentation.						
	• Fire check door	N/A		N/A	N/A		
	 Sealing of electrical shafts 	N/A		N/A	N/A		
	 Fire Rating of shaft door 	N/A		N/A	N/A		
	Water Curtain	N/A		N/A	N/A		
9	• Fire Dampers	N/A		N/A	N/A		
1	Smoke Management System.						
	Basements	30 a/c per	a/c per hour N/A		N/A		
	• Upper floors	12 a/c per	hour	N/A	N/A		
5	Fire Extinguishers						
	Total numbers	05 ABC type		Provided	MR		
•	• Types			Provided	MR		
	IS marking	ISI mar	ked	Provided	MR		
5	First-Aid Hose Reels.						
	Total numbers on each floor	01		Provided	MR		
	 Length of hose reel hose 	30 m	1	Provided	MR		
	Nozzle diameter	5 mm		Provided	MR		
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A		N/A	N/A		
	 Location of Main Panel 	N/A		N/A	N/A		
	 Location of Repeater Panel 	N/A		N/A	N/A		
	Alternate source of power	N/A		N/A	N/A		
	Hooters' Location	N/A		N/A	N/A		
8	MOEFA	Requi	red	Provided	MR		
9	Public Address System.	N/A	1	N/A	N/A		
10	Automatic Sprinkler System.						
	• Basement	N/A	1	N/A	N/A		
	Upper Floor	N/A	Λ	N/A	N/A		
	Sprinkler above false ceiling	N/A		N/A	N/A		
11	Internal Hydrants						
	Size of riser/down-comer	N/A	A	N/A	N/A		
	Number of hydrants per floor	N/A		N/A	N/A		

n . The west fi

 Hose Box Yard Hydrants. Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A		
 Total number of hydrants Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A		
 Hose Box Pumping Arrangements. Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A		
 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A		
 Ground Level Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A		
 Discharge of main Pump Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A		
 Head of Main pump Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A		
 Number of main pumps Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A N/A	N/A N/A N/A	N/A N/A		
 Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head 	N/A N/A	N/A N/A	N/A		
 Jockey pump head Standby Pump out put Standby Pump Head 	N/A	N/A			
Standby Pump out putStandby Pump Head					
Standby Pump Head	N/A	and the second second	N/A		
, a samp 22000		N/A	N/A		
	N/A	N/A	N/A		
➤ Auto Starting/ Manual stopping	N/A	N/A	N/A		
Pump House Access	N/A	N/A	N/A		
Terrace level					
Discharge of pump	450 LPM	Provided	MR		
Head of the pump	40 mts	Provided	MR		
Power Supply	Required	Provided	MR		
Auto Starting of pump	Required	Provided	MR		
Captive Water Storage for fire fighting.					
Underground tank capacity	N/A	N/A	N/A		
➤ Draw-off connection	N/A	N/A	N/A		
Fire service inlet	N/A	N/A	N/A		
> Access to tank	N/A	N/A	N/A		
Overhead Tank capacity	5,000 lts	provided	MR		
Exit Signage.	Required	Provided	MR		
Provision of Lifts.					
Pressurization of Lift Shaft	N/A	N/A	N/A		
Pressurization of Lift lobby	N/A	N/A	N/A		
Tressurization of Lift loody	N/A	N/A	N/A		
1	Fire service inlet Access to tank Overhead Tank capacity xit Signage. rovision of Lifts. Pressurization of Lift Shaft	Fire service inlet N/A Access to tank Overhead Tank capacity 5,000 lts xit Signage. Required rovision of Lifts. Pressurization of Lift Shaft N/A N/A	Fire service inlet N/A N/A N/A N/A N/A N/A Overhead Tank capacity 5,000 lts provided xit Signage. Required Provided rovision of Lifts. Pressurization of Lift Shaft N/A N/A N/A N/A N/A N/A N/A N/		

	Fireman's Grounding Switch	N/A	N/A	N/A
	Lift Signage	N/A	N/A	N/A
17	Standby power supply	N/A	N/A	N/A
18	Refuge Area.		,	
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	 Building Floor Plans 	N/A	N/A	N/A
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect. panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant fire safety certificate under rule 35 of the Delhi Fire ervice rules 2010.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)