3

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ \$2 / 1428

Dated: / 9 /11 /1 9

FIRE SAFETY CERTIFICATE

Certified that the Guest House Jivitesh located at Plot No-11, Road No-34, Pusa Road, New Delhi-110005 is comprised of Basement, Ground floor plus three upper floors using basement as Hall/Storage, ground floor as reception, kitchen, lobby, office & 04 guest rooms, first & second floor each having 13 guest rooms & one store room respectively, third floor having 10 guest rooms & two room for personal use (Total 40 guest rooms) was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011/3663 dated 22.12.2011 owned/ occupied by Sh. Dinesh Singh Bhadauria. The guest house building was re-inspected by the officers concerned of this department on 11.11.2014 in the presence of Col. Suresh Rathi (Group Head HR & and found that the owner have deemed complied with the fire Administration) prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No.39863/Joint C.P./Lic.(H), Dated 20.10.2014)
- 2. Sh. Dinesh Singh Bhadauria (Owner) Guest House Jivitesh, Plot No-11, Road No-34, Pusa Road, New Delhi-110005.



- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	1 Name 9 - LL	INSPECTION	V REPORT		Manager Allahardia alagaila may manager international annual and annual			
	1. Name & address of the building: G. H. Tivitesh Plot No-11, Road No-34 Programmed Straight							
	3 Type of Occupancy	: Re	sidential	1 Con at Land	Koad No-31	+ YUS		
	1 Dataile - F Dataile		. COSCILENE	WHI				
	4. Details of Previous NOC	: Lett	er No. F. 6/1	relmoleulant				
	5. Fire Safety directives lett	.er No :	,	DFS/MS/GH/2011/	3663 Date <u>22</u>	.12.2		
	6. Date of inspection	:	11.11.	2011		-		
7. Name of Inspecting Officer								
	8. Name and designation of	fofficers former p. H. B.O. P. S. Dahiya						
	From the building side 9. Year of Construction	•	Col. Sur	resh Rathi (110 0 01	U		
	1.0 Applicant's latter N	:	2010	Can num	HK & Adm	unist		
5.	10. Applicant's letter No. Minimum Standards on fire	: 391	863 Join	t C.P.Lic.CH	1 -1 -1 1 0 -			
Vo.	prevention and the	1		Provided at	Remarks	.10.76		
L.	prevention and fire safety U/R Access to building		equirement	site	1			
-			Transport of the Control of the Cont	0,100	MR/NMR			
	William neon:	A	ecessible	12 mts	MR			
	• Gate width		-	4. Somts	MR	2.		
	Width of internal road	Side Road	-	09 mtr	1	1		
	Mumber, Width, Type & Arrange	gement of Ex	its		MR	<u>-</u> -		
	simber of staircases	3			The state of the s			
	• Upper Floors	The second secon	One	Τ.				
	* Basements	+	Two	Two	MR			
	b. Width of staircases		160	Two	MR			
	• Upper Floor		_		The same that the same the same that the sam			
	• Basements			125 cms, 75 cms	MR, Old	Case		
	c. Protection of exits	-		150 cms, 184 cms	MR			
	Fire check door				1			
1	pressurization			_				
	d. No. of continuous staircases	to		- 1, 1				
-	retrace				When the state of	7.		
	e. Width of Corridor			One	MR			
	f. Door Size			150 cms	MR			
	Colmadul		-	8 Sems x 204 cms	MR			
-	Compartmentation		No.		1.11			
	Fire check door				The state of the s	-		
	Sealing of electrical shafts	.5						
	* Fire Rating of shaft door			Sealed	MR			
	Water Curtain			-	******			
	 Fire Dampers 							
	Smoke Management System	*						
	* Basements							
1	• Upper floors		/c per	Exhaust fons are Provided	Management of the second secon			
1	- Innartie		Later Control of the	A D	MR	1 -		

Por Port

	N/8-	months and the second s	· · · · · · · · · · · · · · · · · · ·	
		12 a/c per		
		hour		8
5.				4
).	Fire Extinguishers			
	 Total numbers 	four at each floor	Provided	MR
	• Types	Co2, WCo2, ABC	- do -	MR
6.	IS marking First Aid II.	ISI marked	1SI Marked	MR
θ,	First-Aid Hose Reels			
	Total numbers on each floor	Two	Provided	. MR
	 Length of hose reel hose 	30 m	-do-	MR
7.	Nozzle diameter	5 mm	- do -	MR
<i>/</i>	Automatic fire detection and alarming	system		
ì	 Type of detectors 			
i.	 Location of Main Panel 	•		
	 Location of Repeater Panel 	_		
	 Alternate source of power 		02 D.G. Set of 200k	CVA MAR
	Hooters' Location	_	Lobby Stairco	
8.	MOEFA	Required	Provided	MR
9.	Public Address System	-do-	-do-	MOR
10.	Automätic Sprinkler System			
	 Basement 	Required.	Provided	MR
	 Upper Floor 			+
	 Sprinkler above false ceiling 	7		+
11.	Internal Hydrants	!	1	
	 Size of riser/down-comer 		100 M.M	MR
	 Number of hydrants per floor 	-	One	MR
	Hose Box	-	-do-	MR
12.	Yard Hydrants	10	J.	
	 Total number of hydrants 			
10	* Hose Box		_	
13.	Pumping Arrangements	,		
	 Ground Level 			
	Discharge of main Pump	-		
	Head of Main pump		-	
	Number of main pumps	-	E 8	
	> Jockey Pump out put > Jockey pump head			
	Jockey pump headStandby Pump out put			-
	> Standby Pump Head			2
	> Auto Starting/Manual	•	i.	
	stopping			
	acobbu12			

	4			
	Pump House Access			· ·
	Terrace level		1	
	Discharge of pump	1.0 10		·
	Head of the pump	450 LPM Each	4 SOLPM Each	MR LOZ
	Power Supply	30M Each	30 M Each	MR
	Auto Starting of pump	Required	Provided	MR.
	o pump		Both	MR
14.	Captive Water Storage for fire fighting			
	 Underground tank capacity 			
	Draw-off connection			
	Fire service inlet		0	
	Access to tank		Provided	MR
	Overhead Tank capacity	-	·	_
	overnedd fank capacity	15000 LAY	15000 Ltr	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			£
	Pressurization of Lift Shaft			
	 Pressurization of Lift lobby 	-	-	
	Communication In lift Car		**************************************	
	• * Fireman's Grounding Switch	Required	Provided	MR
	Lift Cignors	-do-	- do -	1
	Lift Signage	- do -	-do-	MR MR
17.	Standby power supply	Required	Provided	MR
4				!
18.	Refuge Area.			
	> Total Area			-
	> Location			
		-	_	
19.	Fire Control Room	9 8		
	Detector System Panel			1
	 Flow Switch Panel 			
	PA System Panel			ě
	Batter backupBuilding Floor Plans		^	
			Provided	MR
20.	Special Fire Protection System for Protection of special Risks, if any:	_	- "	
	1	-	al al	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/CH/2011/3663 dated <u>22.12.2011</u> renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Asstt. Divisional Officer