GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001 Fax: 23412593, E-mail: <a href="mailto:cfohq.dlfire@nic.in">cfohq.dlfire@nic.in</a>, <a href="mailto:Tel:-011-23414333">Tel:-011-23414333</a>

No. F6/DFS/ans/school/2014/52/1593 Dated: 17/12/14

## FIRE SAFETY CERTIFICATE

Certified that Dignity International Public School located at G-526, Sangam Vihar, New Delhi-62 was granted N.O.C. by this department for ground and one upper floor vide letter No. F6/DFS/MS/2011/School/3626 dated 20/12/2011. The school building was re-inspected by the officer concerned of this department on 10.12.2014 in presence of Sumita Siwas, Principal of the school and found that the School management have deemed complied with the fire prevention and fire safety requirements in accordance with Directorate of Education Circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 and that the school building is fit for occupancy class "Educational" with effect from the date of issue of this certificate for a period of three years, subject to compliance of the under mentioned conditions.

Issued on -- 17/12/14--- at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

## Copy to: -

- 1. The Principal, Dignity International Public School located at G-526, Sangam Vihar, New Delhi-62.
- 2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, NewDelhi-110006.

## Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in form 'K' Provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in

## INSPECTION REPORT

1. Name & address of the building : Dignity International Public School located at G-526, Sangam

Vihar, New Delhi-62

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2011/School/3626 dated 20/12/2011

5. Fire Safety directives letter No

: Directorate of Education circular No. F.16/Estate/CC/Fire

Safety/2011/3298 to 3398 dated 01-03-2011

6. Date of inspection

: 10.12.2014

7. Name of the Inspecting Officers: M.K.Chattopadhyay, ADO(M.Rd)

8. Name and designation of officers

from the building side

: Sumita Siwas, Principal

9. Year of Construction

: 2008-09

10. Applicant's letter No.

: Nil dated 27.11.2014.

Dignity International Public School located at G-526, Sangam Vihar, New Delhi-62 is comprised of ground plus one upper floor.

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building	·		THE THINK
	• Road width	06 mts	Provided	MR
	<ul><li> Gate width</li><li> Width of internal road</li></ul>	4.5 mts	Provided	MR
2		Required	Provided	MR
	Number, Width, Type & Arrangemen	t of Exits		,
	a. Number of staircases			
	<ul> <li>Upper Floors</li> </ul>	02	02	1.00
	<ul> <li>Basements</li> </ul>	N/A	N/A	MR
	b. Width of staircases			N/A
	• Upper Floors	1.5 mts or less & 0.75 mt	1.38 & 1.50 mts	MR
	<ul><li>Basements</li><li>c. Protection of exits</li></ul>	N/A	N/A	N/A
	• Fire check door			
	<ul> <li>Pressurization</li> </ul>	N/A	N/A	N/A
e	e. No. of continuous staircases to terrace	N/A	N/A	N/A
	g. Width of Corridor	02	02	MR
		1.5 mts	Provided	MR

	h. Door Size	1.0 mts	Provided	MR ·		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	Fire Rating of shaft door	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basements	30 a/c per hour	N/A	N/A		
	Upper floors	12 a/c per hour	N/A	N/A		
5	Fire Extinguishers					
	Total numbers	10 nos.	Provided	MR		
	• Types	ABC,CO <sub>2</sub> type	Provided	MR		
	IS marking	ISI marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor		N/A	N/A		
	Length of hose reel hose	30 m	N/A N/A	N/A N/A		
	Nozzle diameter	5 mm	N/A	IN/A		
7	Automatic fire detection and alarming system Not required					
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	N/A	N/A	N/A		
	Alternate source of power	N/A	N/A	N/A		
	Hooters' Location	N/A	N/A	N/A		
8	MOEFA	N/A	N/A	N/A		
9	Public Address System.	N/A	N/A	N/A		
10	Automatic Sprinkler System					
	Basement	N/A	N/A	N/A		
	Upper Floor	N/A	N/A	N/A		
	Sprinkler above false ceiling	N/A	N/A	N/A		
11	Internal Hydrants					

	Size of riser/down-comer	N/A	N/A	N/A
	Number of hydrants per floor	N/A	N/A	N/A
	<ul> <li>Hose Box</li> </ul>	N/A		
	Vowd Hadamat	IN/A	N/A	N/A
	Yard Hydrants.      Total number of hydrants			
	<ul><li> Total number of hydrants</li><li> Hose Box</li></ul>	N/A	N/A	N/A
3	Pumping Arrangements	N/A	N/A	N/A
	Ground Level			
	Discharge of main Pump			
		N/A	N/A	N/A
	or many	N/A	N/A	N/A
	or main pamps	N/A	N/A	N/A
	> Jockey Pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby Pump out put	N/A	N/A	N/A
	Standby Pump Head	N/A	N/A	N/A
	Auto Starting/ Manual	N/A	N/A	N/A
	stopping	N/A	N/A	N/A
	Pump House Access			
	Terrace level     Discharge of many		27/4	
	<ul><li>Discharge of pump</li><li>Head of the pump</li></ul>	N/A	N/A	N/A
	Power Supply	N/A	N/A	N/A
	<ul><li>Auto Starting of pump</li></ul>	N/A	N/A	N/A
		N/A	N/A	N/A
	Captive Water Storage for fire fighting			
	Underground tank capacity	N/A	N/A	N/A
	<ul><li>Draw-off connection</li><li>Fire service inlet</li></ul>	N/A	N/A	N/A
	<ul><li>Fire service inlet</li><li>Access to tank</li></ul>	N/A	N/A	N/A
	<ul><li>Overhead Tank capacity</li></ul>	N/A	N/A	N/A
	- Continue Tank Capacity	N/A	N/A	N/A
1	Exit Signage.	Required	Provided	MR
4	Provision of Lifts.	Not Applica	ble	
	<ul> <li>Pressurization of Lift Shaft</li> </ul>	N/A	N/A	N/A

				500	
	Pressurization of Lift lobby	N/A	N/A	N/A	
8	Communication In lift Car	N/A	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	N/A	
	Lift Signage	N/A	N/A	N/A	
17	Standby power supply	N/A	N/A	N/A	
18	Refuge Area.				
	> Total Area	N/A	N/A	N/A	
	> Location	N/A	N/A	N/A	
19					
	Detector System Panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	Batter backup	N/A	N/A	N/A	
	<ul> <li>Building Floor Plans</li> </ul>	N/A	N/A	N/A	
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	01 ABC type fire extinguisher is provided near elect. Panel.	MR	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/2011/School/3626 dated 20/12/2011, renewal under the Directorate of Education circular No. F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01-03-2011 is recommended.

DFA is put up for approval & signature please

Signature of the Inspecting Officer
Name (M.K. CHATTOPADHYAY)
Designation: - Assistant Divisional Officer