GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: cfohq.dlfire@nic.in, Tel:- 011-23414333

NO.F6/DFS/MS/GH/2014/52 | 16 05

Dated: 19/12/19

FIRE SAFETY CERTIFICATE

Certified that Neer Guest House located at 2A, Nangli Razapur, East Nizamuddin, New Delhi-110013 comprised of ground floor (Reception + 02 guest rooms + 01 staff room), first floor (03 guest rooms) & second floor (03 guest rooms) was inspected by the officer concerned of this department on 28-11-2014 in the presence of Mr. Narender Chauhan, owner/manager of the guest house and found that the said guest house have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules 2010 and that the premises / building is fit for occupancy class residential (guest house) with effect from 19/12/19 for a period of 3(three) years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi fire service Rules,2010.

Issued on 19/12/14 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER

Copy to: -

1. The Addl.C.P (Lic.), Police Station, Defence Colony, 1st floor, New Delhi.

The Manager, Neer Guest House, 2A, Nangli Razapur, East Nizamuddin, New

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s Neer Guest House 2A, Nangli Razapur, East Nizamuddin, New Delhi-110013. : Lodging House 2. Type of Occupancy : New Case 3. Type of Case : N/A 4. Details of previous NOC · Nil 5. Fire Safety directives letter No : 28.11.2014 6. Date of inspection : M.K.Chattopadhyay, ADO(M. Road) 7. Name of the Inspecting Officers 8. Name and designation of officers : Mr. Narender Chauhan, Owner /Manager from the building side : 2002 9. Year of Construction : 36437/joint C.P/Lic(H) dated New Delhi the 28-09-2014 10. Applicant's letter No. The said guest house is comprised of ground floor (Reception + 02 guest rooms + 01 staff room), first floor (03 guest rooms) & second floor (03 guest rooms). Provided at site Remarks BBL Minimum Standards on fire S. MR/NMR Requirement No. prevention and fire safety U/R 33 Access to building Provided MR 06 mts Road width Directly accessible MR Gate width N/A N/A N/A Width of internal road Number, Width, Type & Arrangement of Exits a. Number of staircases Provided MR 01 Upper Floors N/A N/A N/A Basements b. Width of staircases Provided (1.0 mts) MR Upper Floors 0.90 mts N/A N/A N/A Basements c. Protection of exits N/A N/A N/A Fire check door N/A N/A N/A Pressurization 01 e. No. of continuous staircases to 01 MR terrace Provided MR 1.0 mt

1.0 mt

Provided

MR

1

g. Width of Corridor

h. Door Size

		—		4/2			
3	Compartmentation.			1			
	• Fire check door	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A	N/A			
	 Fire Rating of shaft door 	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4	Smoke Management System.						
	Basements	30 a/c per hour	N/A	N/A			
	Upper floors	12 a/c per hour	N/A	N/A			
5	Fire Extinguishers						
	Total numbers	05	Provided	MR			
	• Types	ABC type	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	Provided	MR			
	Length of hose reel hose	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	·MR			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	N/A			
	 Location of Main Panel 	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	N/A	N/A	N/A			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	Upper Floor	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
11	Size of riser/down-comer	N/A	N/A	N/A			
	 Number of hydrants per floor 	N/A	N/A	N/A			

-	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
	 Total number of hydrants 	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N/A	N/A	N/A		
	➤ Head of Main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	> Jockey Pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	> Standby Pump out put	N/A	N/A	N/A		
	> Standby Pump Head	N/A	N/A	N/A		
	Auto Starting/ Manual stoppin	g N/A	N/A	N/A		
	> Pump House Access	N/A	N/A	N/A		
	Terrace level					
	Discharge of pump	450 LPM	Provided	MR		
	Head of the pump	40 mts	Provided	MR		
	Power Supply	Required	Provided	MR		
	Auto Starting of pump	Required	Provided	MR*		
14	Captive Water Storage for fire fighting.					
	Underground tank capacity	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inletAccess to tank	N/A	N/A	N/A		
		N/A	N/A	N/A		
	Overhead Tank capacity	5,000 lts	provided	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.	1	,			
	Pressurization of Lift Shaft	N/A	N/A	N/A		
* ×	Pressurization of Lift lobby	N/A	N/A	N/A		
250	Communication In lift Car	N/A	N/A	N/A		

	, and the second	NHY				
	• Fireman's Grounding Switch	N/A	N/A	N.		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	N/A	N/A	N/A		
18	Refuge Area.			IN/A		
	Total Area	N/A	N/A	N/A		
19	Fire Control Room	N/A	N/A	N/A		
	The Control Room					
	Detector System Panel	N/A	N/A	N/A		
	Flow Switch Panel	N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Batter backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
0	Special Fire Protection Systems for Protection of special Risks, if any:	Required	One ABC type fire extinguisher found provided near elect. panel	MR		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, it is recommended to grant fire safety certificate under rule 35 of the Delhi Fire Service rules 2010.

DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Designation: - Asstt. Div. Officer (M.Rd)