GOVERNMENT OF NATIONAL CAPITALTERRITORYOF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/GH/2014/ 202 1591

Dated 15/12/14

FIRE SAFETY CERTIFICATE

(Dr. G. C. Misra) Chief Fire Officer Ph – 011-23414333

Copy to:-

1. Shafaat Guest House, 3908, Urdu Bazar, Jama Masjid, New Delhi.

2. The Addl. Commissioner of police (Lic), 1st floor, P S Defence colony, New Delhi- for information. Letter No. 267-85 / Joint. C.P./Lic.(H) dated, New Delhi the 16/07/2014.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry"

INSPECTION REPORT

1. Jame & address of the building

: Shafaat Guest House at 3908, Urdu Bazar, Jama

Masjid, New Delhi.

2. Type of Occupancy

: Residential (Guest house) B+G+4floors (20 Guest rooms)

3. Type of Case

: Renwal

4. Details of previous NOC

: F6/DFS/MS/GH/2011/1829 dated 04/08/2011

5. Fire Safety directives Letter No.

: NA

6 Date of inspection

: 19/1/0/2014

7 Name of the Inspecting Officer

: Sh. Rajesh Kumar (Assistant Divisional Officer)

8 Name and designation of Officer

from the building side

: Sh. Haji Shafat Ali Azmi

9 Year of Construction

10. Applicant's letter No.

: 26785/Joint. C.P./Lic.(H) dated, New Delhi the 18/07/2014.

S No	Minimum standards on fire prevention	Existing	Duorid 1 1 1	Old Case
	and fire safety U/R 33	Requirements/PSS	Provided at site	Remarks MR/NMR
•	Access of building			
	• Road width	NA	8'	MR
	• Gate width	NA	NA	NA
	Width of internal road	NA	NA	NA
2.	Number, width, Type & Arrangements o	fexits		
	a. Number of staircases	1		
	• Upper floors	1 No.	1 No.	MR
	• Basements	1 No.	1 No.	MR
	b. Width of staircases			
	• Upper floors	0.80 Mtr.	97 cms.	MR
	Basements	0.80 Mtr.	97 cms.	MR
	c. Protection of exits			
	Fire check door	NA	NA	NA
Ť.		NA	NA	NA

1/19

		. // /		
	Pressurization	NA	NA	NA
	d. No of continuous staircase to terrace	01	01	MR
.1	e. Width Of Corridor	NA	NA	NA
	f. Door Size	NA	NA	NA NA
	Compartmentation			INA
	Fire check door	NA	NA	NA
	Sealing of electrical shafts	NA	NA	
	Fire Rating of shaft door	NA	NA	NA
	Water Curtain	NA	NA	NA
	Fire Dampers	NA	NA NA	NA
	Smoke managements System		INA	NA
	Basements	20 A CDIT		
	• Upper floors	30 ACPH	Exhaust fan	MR
1		12 ACPH	NA	NA
1	Fire Extinguishers			
	to add promoced in	10 11	12.100.	T. C.
	• Types	ABC, CO ₂ , Wco ₂	ABC, CO ₂ , Wco ₂	MR
	IS marking	Required	Provided	MR
F	First – Aid Hose Reels			
	Total numbers on each floor	01	01 Nos.	MR
	• Length of hose reel hose	30m	30m	MR
	Nozzle diameter	5mm	5mm	MR
A	utomatic fire detection and alarming sys	stem		1,11
	Type of detectors	NA	NA	NA
	• Location of Main Panel	NA	NA NA	
	• Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	1	NA
	Hooters' Location	NA	NA	NA
M	OEFA		NA	NA
	blic Address System	NA	NA	NA
-	atomatic Sprinkler	NA	NA	NA
At				
	Basements	NA	Provided	NA

	The state of the s	MAX		
	Upper floor	NA	NA	NA
111		NA	NA	NA
11	Internal Hydrants		,	
	Size of riser/down- comer	NA	NA	NA
	Number of hydrants per floor	NA	NA	NA
	Hose Box	NA	NA	NA
12	Yard Hydrants			
	Total number of hydrants	NA	NA	NA
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Hose Box	NA	NA	NA
13	Pumping Arrangements			1111
	o Ground Level			4
	Discharge of main pump	NA	NA	NA
	Head of main pump	NA	NA	NA
	Number of main pumps	NA	NA	NA NA
	Jockey pump out put	NA	NA	NA NA
	Jockey pump head	NA	NA	NA NA
*	Standby Pump out put	NA	NA	
·	Standby Pump Head	NA	NA	NA
	auto Staring/Manual stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	Terrace level		IVA	NA
	Discharge of pump	450 LPM	450 LPM	1 (D)
	Head of the pump	30 Mtr.	30 Mtr.	MR
	Power supply	Required	Provided	MR
	Auto starting of pump	Required	110000	MR
	rate starting of pump	required	Provided	MR
14	Captive water Storage for fire fighting			
*	Under ground tank capacity	NA	NA	NIA
2	• Draw of connection	NA	NA NA	NA
	Fire service inlet	NA		NA
	Access to tank		NA	NA
the l		NA	NA	NA

Au

		NIK		
15	Overhead Tank capacity	5,000 ltr.	5,000 ltr.	MR
16	Exit Signage	Required	Provided	MR
-	Provision of Lifts Pressurization of Lift Shaft	NA	NA	
	Pressurization of lift lobbyCommunication in lift Car	NA	NA	NA NA
	Fireman's Grounding Switch	NA	NA	NA
	Lift Signage	NA	NA	NA
7	Standby power supply	NA Page 1	NA	NA
	Refuge Area	Required	Provided (Inverter)	MR
_	Total area	NA		
	• Location	NA	NA	NA
	Fire control room	1111	NA	NA
	Detector system panel	NA	NA	NIA
	• Flow Switch Panel	NA	NA	NA NA
- 1	PA System Donal			1

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

NA

NA

NA

NA

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F6/DFS/MS/GH/2011/1829 dated 04/08/11 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name :- Rajesh Kumar

Designation :- A. D.O. (SPM)

NA

NA

NA

NA

Sumar D.O. (SPM)

NA

NA

NA

NA

Defect (NDZ)

PA System Panel

Building Floor Plans

Special Fire Protection Systems for

Protection of special Risks, if any;

Batter backup

20