GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/52 | 1609

Dated: 19/12/19

FIRE SAFETY CERTIFICATE

Certified that the Guest House **Exotica Inn** located at 6/88, Old Rajinder Nagar, New Delhi-110060 is comprised of Basement, Stilt, Ground floor plus three upper floors, using basement as storage, stilt floor as parking, ground floor used as reception & office, first & second floor each having 04 guest rooms respectively, third floor having 02 guest rooms (Total 10 guest rooms) and a kitchen for staff in temporary shed on terrace owned/occupied by Sh. Ashwani Kumar S/o Sh. Trilok Nath. The guest house building was inspected by the officers concerned of this department on 17.11.2014 in the presence of Sh. Ashwani Kumar (Owner) and found that the owner have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA)
CHIEF FIRE OFFICER
DELHI FIRE SERVICE
Ph: 011-23414333

Copy to:-

- The Joint Commissioner of Police (Lic.)
 1st floor, P.S., Defence Colony, New Delhi.
 (Re. No.39610-613/Joint C.P./Lic.(H), Dated 17.10.2014)
- 2. Sh. Ashwani Kumar (Owner) Guest House Exotica Inn, 6/88, Old Rajinder Nagar, New Delhi-110060.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The basement shall be used strictly as per the provisions of the building bye laws.
- 7. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

TO State of percent of the sec	M// 4						
	INSPEC	TION REPORT					
	 Name & address of the building: 	G.H Exotica	Inn 6/88 Ald	Rain dan Nagarla			
		The structure of the st					
	J. Type of Case	: New Case/Renewal					
	4. Details of Previous NOC	: Letter No.					
	5. Fire Safety directives letter No			National Association of Parallel States			
	6. Date of inspection	D.O.S.K. Tomax & A.D.O. P.S. Dahiya					
	7. Name of Inspecting Officer						
	8. Name and designation of officers			O .			
From the building side : Sh. Ashwani Kumar (Owner							
	9. Year of Construction : Before 01.07.2010 : 39610-613 Joint C.P. 1.0.64						
	Minimum Standards on fire	39610-613 70	int C.P LIG. CI	1) dated 17.10.2			
10.		NBC	Provided at	Remarks			
	prevention and fire safety U/R 33 Access to building	Requirement	site	MR/NMR			
•	Road width	100					
	• Gate width	Accessible	09 mts	MR			
		-	-				
	• Width of internal road						
	Number, Width, Type & Arrangemen	t of Exits					
	a. Number of staircases						
	• Upper Floors	One	One	MR, 01.07.20101			
	• Basements	- do -	- do -	-do-			
	b. Width of staircases			3			
	Upper Floor	125cms	125cms	MR (Bidg. before			
	Basements Protection of the in-	- 300	117 to 125cms	MR, (Area 88 sq. 6			
	c. Protection of exits			7			
	Fire check door	•		-			
	• pressurization	· · · · · · · · · · · · · · · · · · ·		-			
	d. Not of continuous staircases to terrace						
	e. Width of Corridor	-	One	-:			
	f. Door Size	-	120 cms				
			80cms x 225cms	:			
,	Compartmentation		ON CITICS XXXX CMS				
	Fire check door						
	 Sealing of electrical shafts Fire Rating of shaft door Water Curtain 	-					
			Sealed	-			
				,			
	• Fire Dampers						
1.	Smoke Management System		J				
	* Basements	30 a/c per	Exhaust Fans				
	Upper floors	hour	are Provided	MR			
-			atural Ventilati	oh MR			

	N/9_		gen o g			
		12 a/c per hour	_			
5.	Fire Extinguishers					
	Total numbers	Two at each Flod	A D			
	Types	Coz, ABC	Provided	MR		
	IS marking	ISI marked	-do-	MR		
6.	First-Aid Hose Reels		1 1SI Marked	MR		
	 Total numbers on each floor 	NIR				
	 Length of hose reel hose 	30 m				
1	 Nozzle diameter 	5 mm				
7.	Automatic fire detection and alarming system					
	 Type of detectors 					
	 Location of Main Panel 	_				
	 Location of Repeater Panel 					
	 Alternate source of power 	-	NC catable al			
	 Hooters' Location 		D.G. Set of 62.5 K	VA MAR		
8.	MOEFA	NIR				
9.	Public Address System	NIR				
10.	Automätic Sprinkler System	I NUN				
	 Basement 			Diatain 20		
	 Upper Floor 			Plotarea 88 sq		
	 Sprinkler above false ceiling 		_1			
11.	Internal Hydrants					
	 Size of riser/down-comer 					
	 Number of hydrants per floor 			7		
	 Hose Box 					
12.	Yard Hydrants		J.			
	 Total number of hydrants 	-				
	* Hose Box					
13.	Pumping Arrangements					
	 Ground Level 		ě			
	Discharge of main Pump					
	Head of Main pump					
	Number of main pumps					
	> Jockey Pump out put					
	Jockey pump headStandby Pump out nut	•				
9.	Standby Pump out putStandby Pump Head					
	> Auto Starting/Manual	*	i			
	stopping					
	J. Copping					

	Pump House Access			
- 1	Terrace level			4
	Discharge of pump			
	Head of the pump	NIR		
	Power Supply	NIR		
	Auto Starting C			
	Auto Starting of pump			
14	Canting Man			
	Storage for fire fighting	i		
	 Underground tank capacity 			
	Draw-off connection			
	Fire service inlet			
	Access to tank			
	 Overhead Tank capacity 			-
		NIR		
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			1
	 Pressurization of Lift Shaft 			
	 Pressurization of Lift lobby 		-	Out of order
57	Communication In lift Car			-do -
	• * Fireman's Grounding Switch		-	- do -:
	Lift Signage			- do -
		_		-do-
17.	Standby power supply	Required	Provided	MR
18.	Refuge Area.			
	> Total Area			
	Location			
		_	-	
19.	Fire Control Room			
	Detector System Panel		•	
	Flow Switch Panel			
	PA System Panel	-	- '	_
	Batter backupBuilding Floor Plans		_	
		-	Provided	
	3 1 3 1 1 1 1 1 1 3		·······································	
20.	Special Fire Protection System for Protection of special Risks, if any:	Mr.		
	p sour mans, it dily:			* * * * * * * * * * * * * * * * * * * *

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the above substantial compliance of the minimum standards on fire prevention and Fire Safety measures required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial

numbers...
ote: - The building is constructed on a blot area 88 sq. yard before 01.07.2010. The building is comprised of Basement, stilt, Ground Floor plus three upper Floors. The basement having seprate exit and used as storage, stilt as barking. Ground Floor as reception & office first &

exit and used as storage, stilt as parking, Ground Floor as reception & office, first & second Floor each having of Guest rooms respectively, third Floor having of Guest rooms [Total 10 Guest rooms only) Electric & Water bill for the year 2008 & 2009 are placed in the file regarding year of Construction. The fire Safety Certificate is recommended for 10 Guest rooms only

Signature of Inspecting Officer

Name S. K. Tomar

Designation Divisional Officer

\ A11 1/

Name A.C. Aslan

Name P.S. Dahiya

Signature of Inspecting Officer

Designation AssH. Divisional Officer