GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

Fax: 23412593, E-mail: <u>cfohq.dlfire@nic.in</u>, <u>Tel:-</u> 011-23414333

NO.F6/DFS/MS/ 2 =14/52 1544

Dated:

11/12/14

FIRE SAFETY CERTIFICATE

Issued on 11/12/19 at New Delhi by.

(Dr. G.C. MISRA) CHIEF FIRE OFFICER.

Copy to: -

- 1. The Manager, M/s. T & T Motors Limited, GA-2, block B-1 Extension, MCIE, Mathura Road, New Delhi.
- 2. The Executive Engineer (bldg.), MCD, Building Department, Civic Centre, Mintoo Road, New Delhi.

Conditions for the validity of fire safety certificate

- a. All the fire safety and means of escape facilities shall be maintained in good working conditions at all time. Any lapse rendering fire safety or means of evacuation facilities rendering non-functional shall be the responsibility of the management.
- b. Building Sanctioning authority may verify any deviation with regard to the construction / occupancy in the building. In case of any deviation, the fire safety certificate stands null and void.
- c. The staffs shall be trained for operating fire fighting system and mock evacuation drills be conducted at regular intervals and record be maintained.
- d. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on website www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: M/s. T & T Motors Limited, GA-2, block B-1 Extension,

MCIE, Mathura Road, New Delhi.

2. Type of Occupancy

: Industrial

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/2011/868 dated 13.05.2011

5. Fire Safety directives letter No : F.6/DFS/MS/BP/2009/696 dated 01.06.2009.

6. Date of inspection

: 26.11.2014

7. Name of the Inspecting Officers : Dharampal Bhardwaj, DO(SZ), M.K Chattopadhyay, ADO (M. Road)

8. Name and designation of officers

from the building side

: Coln. Dalip Singh Sodhi, DGM-Admn./HR

9. Year of Construction

: 2006-07

10. Applicant's letter No.

: nil dated 30.10.2014

		100 30.10.2014				
S.	Minimum Standards on fire	NBC	Provided at site	Remarks		
No.	prevention and fire safety U/R 33	Requirement		MR/NMR		
1	Access to building					
	Road width	06 mts	Provided	MR		
	Gate width	4.5 mts	Provided	MR		
	 Width of internal road 	N/A	N/A	N/A		
2	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	-		-		
	 Upper Floors 	02	02	MR		
	 Basements 	03	03	MR		
	b. Width of staircases	-	-	-		
	• Upper Floors	1.5 mts each	Provided	MR		
	• Basements	1.50 mts each	Provided	MR		
	c. Protection of exits	-	-	-		
	• Fire check door	Required	Provided	MR		
	 Pressurization 	Required	Provided	MR		
	e. No. of continuous staircases to terrace	0.3	03	MR		
	g. Width of Corridor	1.50 mts	Provided	MR		
	h. Door Size	1.50 mts	Provided	MR		
3	Compartmentation.					



	Communication In lift Car	Required	Provided	MR
	Fireman's Grounding Switch	Required	Provided	MR
	Lift Signage	Required	Provided	MR
17	Standby power supply	Required	Provided (750 KVA	.) MR
18	Refuge Area.		(/ COTIVI	1VIIC
	Total Area	N/A	N/A	N/A
-	> Location	N/A	N/A	N/A
19	Fire Control Room		,	
	Detector System Panel	Required	Provided	MR
	Flow Switch Panel	Required	Provided	MR
	 PA System Panel 	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	 Building Floor Plans 	N/A	N/A	N/A
0	Special Fire Protection Systems for Protection of special Risks, if any	Required	Provided 02 CO ₂ type fire extinguishers near elect. Panel	MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

The shortcomings pointed out in earlier inspection vide letter no. F.6/DFS/MS/2014/2194 dated • 17-09-2014 has been rectified by the building management.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F.6/DFS/MS/2011/868 dated 13.05.2011, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

DFA is put up for approval & signature please.

DHARAMPAL BHARDWAJ DO (SZ)

M.K.CHATTOPADHYAY ADO (M. Road)

T		Required	Provided	MR	
	• Fire check door	Required	Provided	MR	
	Sealing of electrical shafts	N/A		N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	Required	Provided	MR	
	• Fire Dampers				
S	Smoke Management System.	30 a/c per hour	Provided	MR	
	• Basements	12 a/c per hour		N/A	
	• Upper floors	12 are per neur	11112		
-	Fire Extinguishers			MR	
-	Total numbers	16	Provided		
	• Types	ABC, CO ₂ type		MR	
	IS marking	ISI marked	Provided	MR	
	First-Aid Hose Reels.) (D	
-	T. t-1 numbers on each floor	02	Provided	MR	
	I wath of hose reel hose	30 m	Provided	MR	
		5 mm	Provided	MR	
	Nozzle diameter Automatic fire detection and alarming system. Required Provided (smoke) M				
7		Required	Provided (smoke)	MR	
	Type of detectors	Required	Provided(GF)	MR	
	 Location of Main Panel 		N/A	N/A	
	 Location of Repeater Panel 	N/A	N/A		
	Alternate source of power	Required	Provided	MR *	
		Required	il I (an ataircase)	MR	
	Hooters' Location		Provided (near staircase)		
		Required	Provided	MR N/A	
8	MOEFA	N/A	N/A	11/12	
9	Public Address System.			-	
10		Required	Provided	MR	
	Basement	Required	Provided	MR	
	• Upper Floor		Provided	MR	
	Sprinkler above false ceiling	Required	11011464		
1	1 Internal Hydrants	100 mm	Provided	MR	
1	Size of riser/down-comer				
1	Number of hydrants per floor	Required	Provided (2 no	s.) MR	



és C	Hose Box	Required	Provided (2 nos.)	MR	
12	Yard Hydrants.				
	Total number of hydrants	Required	Provided (4 nos.)	MR	
	Hose Box	Required	Provided (4 nos.)	MR	
13	Pumping Arrangements.				
	Ground Level				
	Discharge of main Pump	2280 LPM	Provided	MR	
	➤ Head of Main pump	60 mts	Provided	MR	
	Number of main pumps	01	Provided	MR	
	Jockey Pump out put	180 LPM	Provided	MR	
	> Jockey pump head	60 mts	Provided	MR	
	> Standby Pump out put	2280 LPM	Provided	MR	
	> Standby Pump Head	60 mts	Provided	MR	
	Auto Starting/ Manual	Required	Provided	MR	
	stopping	Required	Provided	MR	
	Pump House Access	-	1101100	-	
	Terrace level	-	- 111		
	Discharge of pump	900 LPM	Provided	MR	
	➤ Head of the pump	40 mts	Provided	MR	
	Power Supply	Required	Provided	MR	
	Auto Starting of pump	Required	Provided	MR	
14	Captive Water Storage for fire fighting	ng.		žu,	
	Underground tank capacity	75,000 lts	Provided	MR	
	> Draw-off connection	Required	Provided	MR	
	> Fire service inlet	Required	Provided	MR	
	Access to tank	Required	Provided	MR	
	Overhead Tank capacity	20, 000 lts	Provided	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
10	Pressurization of Lift Shaft	Ň/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	

