GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/ 5 2 / 1644

Dated: 24/12/14

FIRE SAFETY CERTIFICATE

Certified that the Hotel Relax Palace located at 12A/9, WEA, Karol Bagh, New Delhi-110005 is comprised of Ground Floor plus two upper floors, using ground floor as reception & 07 guest rooms, first floor having 06 guest rooms, second floor having 04 guest rooms 17 issued NOC by this department vide letter (Total guest rooms) was No.F.6/DFS/MS/GH/2011/2436 dated 05.10.2011 owned/occupied by Smt. Darshan Kaur. The guest house building was re- inspected by the officers concerned of this department on 12.12.2014 in the presence of Sh. Harmeet Singh and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.) 1st floor, P.S., Defence Colony, New Delhi. (Re. No. 39675/Joint C.P./Lic.(H), Dated 17.10.2014)
- 2. Smt. Darshan Kaur (Owner), Hotel Relax Palace, 12A/9, WEA, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	Control of the Contro							
	INSPE	CTION REPORT						
	1. Name & address of the building	Hotel Relay P	21000 19210 11	in a second control of the second control of				
	2. Type of Occupancy	Hotel Relax Palace, 12A/9, WEA, Karol Bagh, No. 1 Residential (Guest House)						
	J. Type of Case	: New Case/Renewal						
	4. Details of Previous NOC							
	5. Fire Safety directives letter No							
	b. Date of inspection	9 Officer 12.12.2014						
	7. Name of Inspecting Officer							
	8. Name and designation of officers	S	148 P 17.D.U	P.S. Dahiya				
	From the building side			V				
	9. Year of Construction	2001-02	meet Singh (Oloner)				
S.	10. Applicant's letter No.	: 396751 Joint	C.P/LIC.(H) a	1-1-1-1-1-1				
		NBC/BBL	Provided at	lated 17.10.90				
No.	Troversion and the safety (1/R 33	Requirement	site	Remarks				
1.	Access to building	, reguli criterit	Site	MR/NMR				
	 Road width 	Accessible	07 mts	100				
	• Gate width		the second secon	MR				
	 Width of internal road 	_	180 cms	MR				
2.	Number, Width, Type & Arrangement							
	a. Number of staircases	. of Exits						
	• Upper Floors							
	• Basements		One	MR, Old Car				
	b. Width of staircases			No Basemen				
	Upper Floor			NU ENBEMEN				
		_	120 cms	NO ALLO				
	 Basements Protection of exits 		1000 (1017)	MR, Old Case				
	1 21			No Bosement				
	Fire check door							
	• pressurization							
	d. Not of continuous staircases to							
	terrace							
	e. Width of Corridor		One	1.7				
	f. Door Size		160 cms, 195 cms					
3.		_	90 cms x 202 cms	:				
3.	Compartmentation							
	Fire check door							
	Sealing of electrical shafts			-				
Ĭ	Fire Rating of shaft door	-	Sealed					
	Water Curtain	-						
7	• Fire Dampers			W. 100. 110.				
4.	Smoke Management System							
1	* Basements	30 a/c per						
	Upper floors	hour		No Basement				
		N	afural Ventilation	MR				

		hour		_		*
5.	Fire Extinguishers		1			
	 Total numbers 	Two at each Flo	48	0		
	Types	Co2, WCo2	1	Provided		1R
:	IS marking	ISI marked	1	-de-		7R
6.	First-Aid Hose Reels		H	1SI Marked		7 <i>R</i>
ta	 Total numbers on each floor 	One	H	Provided	Λ.	D.R.
	 Length of hose reel hose 	30 m		- do -		nR
1	 Nozzle diameter 	5 mm		- de'-	, ,	1R
7.	Automatic fire detection and alarming	system			<u> </u>	1//
	 Type of detectors 		İT	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
ì	 Location of Main Panel 					
	 Location of Repeater Panel 			•		
	 Alternate source of power 	-		D.G. Set of askva		
	 Hooters' Location 			D. O. S. E. I. O. S. KVA		
8.	MOEFA	Required		Provided	Λ.	DR
9.	Public Address System	- do -		-do-		DR
10.	Automatic Sprinkler System				L	
	 Basement 			-	No	Basement
	 Upper Floor 				/ 10	Lisasement
	 Sprinkler above false ceiling 			1		
11.	Internal Hydrants					1
	 Size of riser/down-comer 	_		*		
	 Number of hydrants per floor 					
	 Hose Box 	- Commence of the Commence of				
12.	Yard Hydrants		<u>. </u>	j.		
	 Total number of hydrants 					1
	* Hose Box		-		_	
13.	Pumping Arrangements			, 1	Tr a	
	 Ground Level 			*		3
	Discharge of main Pump					
	Head of Main pump				,	
	> Number of main pumps	Name -				_
	> Jockey Pump out put					_
B	Jockey pump headStandby Pump out put	No.				4
	startaby runip out put					2
	anip riedu			i.		11
	Auto Starting/Manual stopping			i		
	arobhing					
					L	
					,)	

				4				
	> Pump House Access							
	Terrace level							
	Discharge of pump	450 LPM	450 LPM	MR				
	Head of the pumpPower Supply	30 M	30 M	MR				
		Required	Provided	MR				
	> Auto Starting of pump							
14.	Captive Water Storage for fire fighting							
	 Underground tank capacity 		-	T				
	Draw-off connection							
	Fire service inlet							
	Access to tank							
	 Overhead Tank capacity 	5000 Ltr	4000 Ltr	1 100				
	f 1	0		MR, Old Ca				
15.	Exit Signage.	Required	Provided	MR				
16.	Provision of Lifts.	e e	× v					
	 Pressurization of Lift Shaft 		2	No Lift				
	 Pressurization of Lift lobby 			-do -				
	Communication In lift CarFireman's Grounding Switch							
				-do-				
	Lift Signage		—	-do-				
-			and the same of th	-do-				
17.	Standby power supply	Required	Provided	MR				
18.	Refuge Area.							
	> Total Area							
	Location							
				_				
19.	Fire Control Room	3						
	Detector System Panel							
	Flow Switch Panel							
	PA System Panel			:				
	Batter backup							
	 Building Floor Plans 			:				
20.	Special Fire Protection System for Protection of special Risks, if any:							

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6 NFS MS 6 H 2011 2436 dated OS 10 2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

12/4/14

Signature of Inspecting Officer

Name S.K. Tomar

Designation Divisional Officer

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Afft. Divisional Officer.

DICFOCSZ AMERICA