GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110 001.

E-mail:- cfohq.dlfire@nic.in

Fax:- 011-23412593

No. F.6/DFS/MS/GH/2014/52 //646

Dated: 24/12/14

FIRE SAFETY CERTIFICATE

Certified that the **Hotel Sun Shine** located at 17B/20-21, Dev Nagar, Karol Bagh, New Delhi-110005 is comprised of Ground Floor, Mezzanine Floor plus three upper floors, using ground floor as reception, office & 12 guest rooms, mezzanine floor having 08 guest rooms, first floor having 15 guest rooms, second floor having 16 guest rooms (Total 51 guest rooms) and a pantry for staff with one hall on third floor was issued NOC by this department vide letter No.F.6/DFS/MS/GH/2011/2565 dated 17.10.2011 owned/occupied by Smt. Innyisha Taneja. The guest house building was re- inspected by the officers concerned of this department on 12.12.2014 in the presence of Sh. M. Chatterjee (Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class residential w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on. 24.1.2.1.4. at New Delhi.

(DR. G.C. MISRA) CHIEF FIRE OFFICER DELHI FIRE SERVICE Ph:- 011-23414333

Copy to:-

- 1. The Joint Commissioner of Police (Lic.)

 1st floor, P.S., Defence Colony, New Delhi.

 (Re. No. 39669/Joint C.P./Lic.(H), Dated 17.10.2014)
- 2. Smt. Innyisha Taneja (Owner), Hotel Sun Shine, 17B/20-21, Dev Nagar, Karol Bagh, New Delhi-110005.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviation w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner/ occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	INCRE	TION 5.				
	1. Name & address of the building: 2. Type of Occupancy 3. Type of Case	TION REPORT				
	2. Type of Occupancy	Hotel Sun Shin	e, 178/20-21, De	V Noney Karal O		
	3. Type of Case	Residential (Guest House)	N.D.05		
	4 Details of Danie	LAGM CASE ROLE	ewal			
	5. Fire Safety 41: 11:	Sletter No. F. 6 DES MS GH 2011 2565 Date 17:10:20				
	5. Fire Safety directives letter No	letter No:				
	6. Date of inspection	12.12.2014				
	7. Name of Inspecting Officer	P litticer . A A O .				
	8. Name and designation of officers		4 P 11 B.C 1	S. Dahiya		
	From the building side :	Sh. Montu	Chatterjee (M	10.00		
	9. Year of Construction	2001	chacer jee (1	lanages)		
	10. Applicant's letter No.	39009 Tol. 1	10111111			
S.	Minimum Standards on fire	NBC/BBL	C.P. LIC. (H)	dated 17.10.20		
No.	prevention and fire safety U/R 33		Provided at	Remarks		
1.	Access to building	Requirement	site	MR/NMR		
	Road width	0.00				
	• Gate width	Accessible	09mts	MR		
		-	140 cms	MR		
2.	Width of internal road Side Road	_	OSmtr	Me alda		
A	Number, Width, Type & Arrangement	of Exits		MR, Old Ga		
	a. Number of staircases .					
	• Upper Floors	Two				
	 Basements 	100	760	MR		
	b. Width of staircases			No Basement		
	Upper Floor					
	 Basements 		105cms, 104 to 1100	ms MR, Old Ca		
	c. Protection of exits	-		No Basement		
	Fire check door			- Dasement		
	• pressurization	_		And the second section of the section		
	d. No of continuous at a					
	d. Not of continuous staircases to terrace					
		-	Two	Section beautiful annual facilities of the section		
	The contract		The state of the s	- Committee of the Comm		
	t. Door Size		106 cms, 110 cms	· ·		
3.		-	75 cm 8 x 202 cm 8 96 cm 8 x 200 cm 8			
·	Compartmentation		10 Cm8 x 200 cms			
	Fire check door					
	Sealing of electrical shafts					
	• Fire Rating of shaft door		Sealed			
	Water Curtain	to-				
1	• Fire Dampers					
1.	Smoke Management System					
	* Basements	20 - 1	1			
	Upper floors	30 a/c per		NIA GO.		
	17-2.770013	hour	tural Ventilation	No Basement		

	NIIG		, F.	1
		12 a/c per		
		hour	_	
5.	Fire Extinguishors			
٥.	Fire ExtinguishersTotal numbers	four at each floor	P	MR
	Types	Ce, WG, ABC	Provided - do,-	MR
:	IS marking	ISI marked	131 Marked	MR
6.	First-Aid Hose Reels		131 Markea	
	 Total numbers on each floor 	One	Provided	MR
	 Length of hose reel hose 	30 m	-do-	MR
	 Nozzle diameter 	5 mm	- do :	MR
7.	Automatic fire detection and alarming	system		
	Type of detectors			
1	 Location of Main Panel 			
	 Location of Repeater Panel 	-		
	 Alternate source of power 	-	D.G. Set of 25 KVA	
	 Hooters' Location 		_	
8.	MOEFA	Regleired	Provided	MR
9.	Public Address System	-do-	-do-	MR
10.	Automatic Sprinkler System			
	 Basement 			No Basement
	 Upper Floor 	,	1.	
	 Sprinkler above false ceiling 			
11.	Internal Hydrants			1
	 Size of riser/down-comer 	•		
	 Number of hydrants per floor 	-		,
	 Hose Box 	_		
12.	Yard Hydrants			
	 Total number of hydrants 			
	 Hose Box 			
13.				
	Ground Level			
	Discharge of main Pump			-
	> Head of Main pumps			-
	Number of main pumpsJockey Pump out put			•
	> Jockey pump head	-		-
	> Standby Pump out put			
	> Standby Pump Head			
	Auto Starting/Manual			
	stopping			
	*			

	N = 11	T		
	> Pump House Access	-		
	Terrace level			y #
	Discharge of pump	450 LPM	450 LPM	MR
	> Head of the pump	30 M		MR
	> Power Supply	Required	30 M Provided	MR
	Auto Starting of pump			
4.4				*
14.	Captive Water Storage for fire fighting			5,
	 Underground tank capacity 	-		
	Draw-off connection			
	Fire service inlet		0	
	Access to tank	. —	-	_
	Overhead Tank capacity	-	Socoltr	MR, Old Cas
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	ī		E -
	Pressurization of Lift Shaft			
	Pressurization of Lift lobby	`		
	 Communication In lift Car Fireman's Grounding Switch Lift Signage 		0	
		•	Provided	
		-		Old Cift
		_	Provided	
		1		
17.	Standby power supply	Required	Provided	MR
17.	Standby power supply	Required		MR
	Refuge Area.	Required		MR
Water Name of the State of the	Refuge Area. > Total Area	Required		MR
Water Name of the State of the	Refuge Area.	Required		MR.
	Refuge Area. > Total Area	Required		MR
18.	Refuge Area. > Total Area	Required		MR
18.	Refuge Area. > Total Area > Location	Required		MR
18.	Refuge Area. > Total Area > Location Fire Control Room	Required		MR
18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel	Required		MR
18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel	Required		MR
18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel	Required		MR
18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup	Required		MR.
17. 18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup • Building Floor Plans	Required		MR.
18.	Refuge Area. > Total Area > Location Fire Control Room • Detector System Panel • Flow Switch Panel • PA System Panel • Batter backup	Required		MR

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6 DES MS 6H 2011 2565 dated 17.10.2011 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Signature of Inspecting Officer

Name S.K. Tomar

Signature of Inspecting Officer

Name P.S. Dahiya

Designation Asstt. Divisional Officer

Designation Divisional Officer

Dy CFO (52/) Attack