GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

Fax: 23412593, Tel: 011-23414333

No.F6/MS/DFS/GH/2014/52 / 1613

Dated: ---- 12/19

FIRE SAFETY CERTIFICATE

Certified that the Sunrise Villa located at L-13, Kalkaji, New Delhi-110019, comprised of basement, ground & 03 upper floors (guest house is running on 1st,2nd & 3rd floor with 20 guest rooms), was granted FSC by this department vide letter No.F6/DFS/MS/GH/2011/3255 dated 29/11/2011. The premises was re-inspected by the officer concerned of this department on 10/12/2014 in the presence of Mr. Vinit and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Group-A, Residential (Lodging and rooming House) with effect from 22-11-11-for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued 22/12/14--at New Delhi by.

(Dr. G.C. Misra) **Chief Fire Officer**

Copy to:-

- (1) Joint. Commissioner of Police Licencing(H) 1st Floor, PS Defence Colony, New Delhi.
- (2) Mr. Vinit Le-Grand Guest House L-12, Kalkaji, New Delhi

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

Removed

INSPECTION REPORT

- 1. Name & address of the building:- Sunrise Villa, L-13, Kalkaji, New Delhi-110019
- 2. Type of occupancy:- Residential (Guest House)
- 3. Type of case: Renewal.
- 4. Details of previous NOC: F6/DFS/MS/ GH/ 2011/3255 dated 29/11/2011.
- 5. Fire safety directives No.- Nil
- 6. Date of inspection:- 10/12/2014
- 7. Name of the inspecting officer:- D.B.Mukherjee, A.D.O.(BCP)
- 8. Name & designation of officer From the building side: Mr. Vinit
- 9. Year of construction: 2008
- 10.Applicant's letter No:- 41449/Joint C.P./Lic.(H), dated: 03/11/2014.

Building is comprised of Basement, Ground + 03 Upper Floors. Basement and ground floor is others property, 1st, 2nd & 3rd floor is being used for guest house.

| SI. No | Minimum Standards on fire Prevention and fire safety U/R 33 | BBL/NBC Requirement | Provided at site | Remarks MR/NMR | | |
|-----------|--|------------------------|------------------|-------------------|--|--|
| 1. | Access to Building | | | | | |
| | 1) Road width | 9 m | Provided | MR | | |
| | 2) Gate width | Required | Approachable | MR | | |
| | 3)Width of internal road | N/A | N/A | N/A | | |
| • | Number, Width Type & Arrangement of Exits | | | | | |
| | A. Number of staircases | | | | | |
| | 1. Upper floors | 01 | Provided 01 no. | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | B. Width of staircase | | | 11/11 | | |
| | 1. Upper floors | 1.25 m | 1.25m | MR | | |
| | 2. Basements | N/A | N/A | N/A | | |
| | C. Protection of exits | | | | | |
| | 1. Fire check door | N/A | N/A | N/A | | |
| | 2. Pressurization | N/A | N/A | N/A | | |
| | D. No. of continuous staircase to terrace | Required | 01 nos. | MR | | |
| | E. Width of corridor | N/A | N/A | N/A | | |
| | F. Door size | N/A | N/A | N/A | | |
| | Compartmentation | | | | | |
| | 1) Fire check door | N/A | N/A | N/A | | |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A | | |
| | 3) Fire rating of shaft door | N/A | N/A | N/A | | |
| | 4) Water curtain | N/A | N/A | N/A | | |
| | 5) Fire Dampers | N/A | N/A | N/A | | |
| | Smoke Management System | | | | | |
| | 1) Basements | 30 a/c per hour | N/A | N/A | | |
| | 2) Upper floors | 12 a/c per hour | N/A | N/A | | |
| | Fire Extinguishers | | | | | |
| | 1) Total numbers | ISI Marked | 10 Nos. Provided | MR | | |
| 5. | 2) Types | | ABC, Co2 | MR | | |
| | 3) I\$I marking | | Yes | MR | | |
| | First-Aid Hose Reel | | | | | |
| | 1) Total number of each floor | Required 01 | Provided | MR | | |
| | 2) Length of hose reel hose | 30 m | Yes | MR | | |
| | 3) Nozzle diameter | 5 mm | Yes | MR | | |

| 7. | Automatic Fire Detection & Alarming S | vstem | | | |
|------|---------------------------------------|--------------|--|-------|--|
| | 1) Type of detectors | N/A | N/A | N/A | |
| | 2) Location of main panel | N/A | N/A | N/A | |
| | 3) Location of repeater panel | N/A | N/A | N/A | |
| 2 | 4) Alternate source of power | N/A | N/A | N/A | |
| | 5) Hooter's Location | N/A | N/A | | |
| | MOEFA | Not Required | Provided | N/A | |
| | Public Address System | N/A | N/A | MR | |
| | Automatic Sprinkler System | IV/A | IN/A | N/A | |
| | 1) Basement | N/A | N/A | 127/4 | |
| | 2) Upper floors | N/A N/A | A STATE OF THE PROPERTY OF THE | N/A | |
| 3 | 3) Sprinkler above false ceiling | N/A N/A | N/A | N/A | |
| 1. I | Internal Hydrants | IN/A | N/A | N/A | |
| 1 |) Size of riser/down-comer | D , 1 | | | |
| | 2) Number of hydrants per floor | Required | Provided | MR | |
| | Hose box | Required | Provided | MR | |
| | | Required | Provided | MR | |
| | Yard Hydrants | | | | |
| |) Total number of hydrants | N/A | N/A | N/A | |
| |) Hose box | N/A | N/A | N/A | |
| 3. P | Pumping Arrangement | | | | |
| | 1) Ground level | N/A | N/A | N/A | |
| | a) Discharge of main pump | N/A | N/A | N/A | |
| | b) Head of main pump | N/A | N/A | N/A | |
| | c) Number of main pump | N/A | N/A | N/A | |
| | d) Jockey pump out put | N/A | N/A | N/A | |
| | e) Jockey pump head | N/A | N/A | N/A | |
| | f) Stand by pump output | N/A | N/A | N/A | |
| | g) Stand by pump head | N/A | N/A | N/A | |
| | h) Auto starting/Manual stopping | N/A | N/A | N/A | |
| | 2)Terrace level | | | | |
| | a) Discharge of pump | 450 LPM | 450 Lpm & 840Lpm | MD | |
| | b) Head of pump | Required | 30m & 34m | MR | |
| | c) Power supply | Required | | MR | |
| | d) Auto starting of pump | Required | Provided | MR | |
| Cant | tive Water Storage for Fire Fighting | Required | Provided | MR | |
| Cup | 1) Under ground tank capacity | N/A | NI/A | | |
| - | a) Draw-off connection | N/A | N/A | N/A | |
| -77 | b) Fire service inlet | N/A N/A | N/A | N/A | |
| - | c) Access to tank | | N/A | N/A | |
| - | d) Over head tank capacity | N/A | N/A | N/A | |
| . E: | xit Signage. | 5,000 Ltrs. | Provided 10,000 ltrs. | MR | |
| | rovision of Lifts. | Required | Provided | MR | |
| · FI | a) Pressurization of lift shaft | NI/A | 1277 | | |
| | | N/A | N/A | N/A | |
| | b) Pressurization of lift lobby | N/A | N/A | N/A | |
| - | c) Communication in lift car | N/A | N/A | N/A | |
| | d) Fireman's switch | N/A | N/A | N/A | |
| | e) Lift signage | N/A | N/A | N/A | |
| | and by Power Supply | Yes | Provided DG Set | MR | |
| | efuge Area | N/A | N/A | N/A | |
| To | otal area location | N/A | N/A | N/A | |

| 9. | Fire Control Room | N/A | N/A | N/A |
|----|--|-----|-----|-----|
| | a) Detector system panel | N/A | N/A | |
| | (b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | | N/A | N/A |
| 0. | | N/A | N/A | N/A |
| | Special Fire Protection System for Protection of special Risk, if any: | | | N/A |

The fire protection system provided in the building were checked and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/GH/2011/3255 dated 29/11/2011, renewal under rules 35 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly DFA is put up for perusal and signature pl.

Signature of the inspecting officer Name: - D.B.Mukherjee. Designation: - Assistant Divisional Officer (BCP)