GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. FGIDFS/12014/32/1841

Dated: 27112114

FIRE SAFETY CERTIFICATE

Certified that M/S TK'S The Tri Kitchens(Voda, Moti Mahal Deluxe, Princess Garden Restaurant at 3rd floor), E-31,32, South Extn. Market-II, New Delhi-49, comprised of Basement, Ground plus three upper floors (Restaurant at 3rd floor only), was granted NOC by this department vide letter No. F6/DFS/MS/EH/2011/1964, dated 12-08-2011. The premises was re-inspected by the officer concerned of this department on 24-11-2014 in the presence of Sh. Satish Kumar(Manager) and found that the said restaurant building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class **Restaurant** (Assembly) at third floor only with effect from 2.3 1.12 1.2014 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 2.7.1.2.1.1.4 at New Delhi by.

(Dr.G.C.Misra)
Chief Fire Officer
T.No.011-23414333

Copy to:-.

- 1. The Dy. Health Officer, Health Deptt. South MCD, Green Park, New Delhi.
- 2. M/S TK'S The Tri Kitchens(Voda, Moti Mahal Deluxe, Princess Garden Restaurant at 3rd floor), E-31,32, South Extn. Market-II, New Delhi-49.

Conditions for the validity of fire safety certificate are overleaf:-

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate, six month prior to its expiry.

INSPECTION REPORT 1. Name & address of the building : M/S TK'S The Tri Kitchens(Voda, Moti Mahal Deluxe, Princess Garden Restaurant at 3rd floor), E-31,32, South Extn. Market-II, New Delhi-49. 2. Building is comprised of : Basement, Ground plus three upper floors. (Restaurant at 3rd floor only). 3. Type of Occupancy : Assembly. 4. Type of Case : Old Case 5. Details of Previous NOC : No.F.6/DFS/MS/EH/2011/1964, dated-12.08.11. 6. Fire Safety direction letter No :Circular No.718, dated 4.4.2005. 7. Date of Inspection : 24.11.2014 8. Name of the Inspecting Officers: : Vedpal (ADO) 9. Name and designation of Officer from the building side : Sh. Satish Kumar (Manager) 10. Year of Construction : 1947. 11. Applicant's letter No : No.Nil, dated 07.11.14. S.No Minimum Standards on fire Old NOC Provided at Remarks prevention and fire safety U/R33 Requirements Site 1 Access to building Road width 6m 24 m MR Gate width N.A. N.A. N.A. Width of internal road N.A. N.A. N.A. Number, Width, Type and Arrangement of Exits. 2 Number of Staircases Upper Floor 02nos. 02nos MR Basement N.A. N.A. N.A. B. Width of Staircases Upper Floor 1.5m 1.14m(each) MR(old case) Basement N.A. N.A. N.A. c. Protection of exits N.A.

N.A. N.A. Fire check door N.A. N.A. N.A. Pressurization N.A. N.A. e. No. of continuous staircases to N.A. 01no. 01no. MR terrace g. Width of Corridor N.A. N.A. N.A. h. Door Size 1.5m 122 &110 cm MR(old case) 3 Compartmentation Fire check door N.A. N.A. N.A. Sealing of electrical shafts N.A N.A. N.A. Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. 4 Smoke Management System. Basement 30a/c per hour N.A. N.A. Upper floor 12 a/c per hour Exhaust fans MR provided

211

5.	Fire Extinguisher								
	Total numbers	04 nos.	06 nos.	MR					
	types	CO ₂ & ABC	CO ₂ & ABC	SACRETURE AND AND ADDRESS OF THE PARTY OF TH					
	IS marking	ISI marked	ISI marked	MR					
6	First-aid-Hose Reels.								
	Total numbers on each floor	01no.	01no.	MD					
	Length of hose reel hose	30m.		MR					
	Nozzle diameter	5mm	30m.	MR					
7	Automatic fire detection and alarming		5mm	MR					
	Automatic fire detection and alarming system. Type of detectors N.A. N.A. N.A.								
	Location of main panel	N.A.	N.A.	N.A.					
	Location of repeater panel		N.A.	N.A.					
	Alternate source of power Hooters	N.A.	N.A.	N.A.					
		N.A.	N.A.	N.A.					
	1. 3.1	N.A.	N.A.	N.A.					
8	MOEFA	Required	Provided	MR					
9	Public address System.	N.A.	N.A.	N.A.					
10	Automatic Sprinkler System.			, , , , , , , , , , , , , , , , , , ,					
	Basement	N.A.	N.A.	N.A.					
	upper floor	Required	Provided	MR					
	sprinkler above false ceiling	N.A.	N.A.	N.A.					
11	Internal Hydrants		1407 G	IN.A.					
	size of riser/down-comer	100mm	100mm	MR					
	Number of hydrants per floor	01no.	01no.	MR					
	Hose Box	01no.	10no.	MR					
12	Yard Hydrants.	011101	10110.	IVIE					
	Total number of hydrants	N.A.	N.A.	NA					
	Hose Box	N.A.	N.A.	N.A.					
13	Pumping Arrangements.	IV.A.	IN.A.	N.A.					
	Ground Level	N.A.	N.A.						
	Discharge of main Pump	N.A.	N.A.	N.A.					
	Head of Main Pump	N.A.		N.A.					
	Number of main pumps	N.A.	N.A.	N.A.					
-	> Jockey pump out put	N.A.	N.A.	N.A.					
	> Jockey pump head	N.A.	N.A.	N.A.					
	Standby pump out put	N.A.	N.A.	N.A.					
	Standby pump Head	N.A.	N.A.	N.A.					
	Auto Starting /Manual stopping	N.A.	N.A.	N.A.					
	Pump House Access	N.A.	N.A.	N.A.					
	 Terrace Level 	Required	N.A.	N.A.					
	Discharge of pump	450LPM	Provided	MR					
	Head of the Pump	40m	450LPM	MR					
	Power supply	Required	40m	MR					
	Auto Starting of pump	Required	Provided	MR					
		riequired	Provided	MR					

NI

M/S TK,S The Tri Kitchens Restaurant at 3rd floor, E-31,32, South Extn. Market-II, New Delhi-49.

14	Captive Water Storage for Fire F	ant at 3" floor, E-31,3	2, South Extn. Marke	et-II, New D	elhi-49
	On ground tank capacity	ighting.			
	Diaw-Off Connection	N.A.	N.A.		
	Fire service inlet	N.A.	N.A.	N.A	١.
	Access to tank	N.A.	N.A.	N.A	
	Overhead Tank capacity	N.A.	N.A.	N.A.	
15	Exit Signage	5000Ltrs.		N.A.	
16	Provision of Lifts.	Required	5000Litrs. Provided	MR	
	Pressurization of Lift Shaft		riovided	MR	
	riessurization of Lift John.	N.A.	N.A.		
	Communication in lift cor	N.A.	N.A.		N.A.
	Firemen's grounding switch	N.A.	N.A.		N.A.
	Lift Signage	Required	Provided	1	V.A.
7	Standby power supply	Required	Provided	Λ	MR
	y power supply	Required		N	/IR
8	Refuge Area.		Provided 50k Generator se	(va N	1R
	Total area		deficiator se	Ţ	
	Location	N.A.	N.A.	AL A	
9	Fire Control Room	N.A.	N.A.	N.A.	
	Detector system panel		14.74.	N.A.	
	Tiow switch panel	N.A.	N.A.	NIA	
	A system panel	N.A.	N.A.	N.A.	
E	Batter backup	N.A.	N.A.	N.A.	
E	Building Floor Plans	N.A.	N.A.	N.A.	
	pecial Fire Protection systems for	N.A.	N.A.	N.A.	
of	special Risks, if any:	N.A.	N.A.	N.A.	
	mono, il ally.		14.4.	N.A.	

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the NOC issued vide letter Noc.F.6/DFS/MS/EH/2011/1964, dated 12.08.2011 renewal under rule 35 of the Delhi Fire Service Rule 2010 is recommended.

Signature of the Inspecting Officer
Name: Vedpal

Designation : ADO